CANNON
INDUSTRIAL PRODUCTS, INC.
Music City, U.S.A.

GHT GREASE™

All Purpose Grease

GHT GREASE is a rough, durable, gold-colored non-soap bentone base, non-meld grease, fortified with extreme pressure additive that provide a Timken load capacity of 65. This is one of very few grease compounds that is designed to absorb shock loads and impact pressures of 65 Timken load capabilities; yet remain extremely stable under a wide variety of conditions including heat, moisture, acid and alkaline.

AREAS OF USE

SCHOOLS
APARTMENTS
HOSPITALS
MUNICIPALITIES
NURSING HOMES
INDUSTRIAL PLANTS
COMMISSARIES
HOTELS/MOTELS
PLACES OF WORSHIP

APPLICATIONS

BALL & ROLLER BEARINGS
SLEEVE BEARINGS
FIFTH WHEELS
KING PINS

TECHNICAL DATA

FORM: Tube or Pail
ODOR: Oil
COLOR: Metallic Gold
NLGI RATING: 2
TIMKEN LOAD: 65
pH: N/A
TEMP RANGE: -32ºF – 550ºF
ASTM DROP POINT: Non-Melt
SOLUBILITY IN WATER: None
SPECIFIC GRAVITY: 0.8
EVAPORATION RATE: N/A

TO ORDER CALL:
CANNON
INDUSTRIAL PRODUCTS, INC.
Music City, U.S.A.

1-888-879-6124
NO. 941