



**DURABILITY**  
**QUALITY OF CUT**  
**EASE OF OWNERSHIP**





# OUR THREE PILLARS

The foundation of every BOB-CAT® mower, from entry-level residential to top-of-the-line commercial, is our Three Pillars philosophy — Durability, Quality of Cut and Ease of Ownership are our guiding principles and your assurance that when you buy a BOB-CAT® mower, you're getting a product that you can depend on for years of reliable, high-performance operation. So let's look a little closer at what each of the Three Pillars means.

## DURABILITY

From their welded, heavy-gauge steel frames to their robust hydrostatic transaxles to their heavy-duty cutting decks, BOB-CAT® mowers are made to take the kind of abuse that would send other mowers to the repair shop. They're built to take this punishment because we spend a lot of time with our customers, learning what they want in a mower. And we build them like you would build them, because you want to spend your time out on them mowing. And making money. Not in the shop wrenching on another repair.

## QUALITY OF CUT

Powerful lift. Sharp, durable steel blades. Consistent, even cutting action and clipping dispersal. These are what make for an exceptional quality of cut. They're also what make for rave reviews from your customers. To deliver the kind of cut quality that creates a sense of pride among professional contractors and homeowners alike, BOB-CAT® cutting decks feature the innovative Double Wave™ Baffle System, which increases lift to make sure every blade of grass gets cut. Their anti-scalp rollers keep the cutting height consistent, no matter the terrain. High-quality steel blades slice, rather than chop. And the oversized discharge chute controls airflow to ensure clippings are spread evenly. All while operating at peak productivity travel speeds.

## EASE OF OWNERSHIP

This can mean different things to different people. A professional contractor might be more concerned about the peace of mind you get with our industry-leading MOW WITH CONFIDENCE™ limited warranties or money-saving financing options. Homeowners might be more interested in the way our mowers are built for convenient access to internal components for fast and easy maintenance. But however you define it, BOB-CAT® mowers are at the top of the food chain when it comes to Ease of Ownership.







BOB-CAT® Predator-Pro™



**BOB-CAT CRZ™**

# MOW LIKE A PRO



MOW WITH  
**5** YEAR LIMITED  
WARRANTY  
CONFIDENCE™



# PROFESSIONAL PERFORMANCE AT AN AFFORDABLE PRICE.

## More mower for your money.

No one can match the combined features and price of the CRZ™ residential zero-turn mower. From its high-performance engines and 10-gauge steel decks with our patented Double Wave™ baffle system to its comfortable high-back seat, the CRZ™ gives you the durability, quality of cut and comfort you need, and value you won't find anywhere else.



## THE CRZ™ FEATURES:

- » **5-Year / 500 hour**  
MOW WITH CONFIDENCE™ limited warranty
- » Powerful Kawasaki® FR series engines
- » Tough, smooth-running Hydro-Gear® ZT-2800® transaxles
- » 7-mph ground speed
- » BOB-CAT® exclusive 20-inch Zero-T drive tires
- » Durable TufDeck™ mower decks with 7-gauge side skirts and single-layered 10-gauge top
- » Patented Double-Wave™ Baffle System deck design lifts grass for a clean cut
- » 6-gallon, impact-resistant, roto-molded fuel tank
- » Comfortable, adjustable, high-back seat with spring-dampened suspension and armrests
- » Convenient flip-up floor plate and open-frame design for easy access and maintenance

MODEL	MODEL #	ENGINE MAKE	DECK SIZE
CRZ™	942604	Kawasaki® FR651V	48SD
	942605	Kawasaki® FR651V	52SD
	942606	Kawasaki® FR691V	61SD



**BOB-CAT XRZ™**

# A CUT ABOVE



MOW WITH  
**6** YEAR LIMITED  
WARRANTY  
CONFIDENCE





# THE NEXT STEP IN PERFORMANCE AND AFFORDABILITY.

**Amped up for the homeowner who wants more.**

The BOB-CAT® XRZ™ brings performance and value to the next level with added features and durability. The XRZ™ has added power, responsiveness and agility with proven, heavy-duty transaxles. You get a smooth ride and ground-gripping traction with BOB-CAT® exclusive 22-inch Zero-T drive tires. And stepped up mowing comfort with a premium, high-back, adjustable seat with standard armrests. The BOB-CAT® XRZ™, the residential mower with power, durability, comfort and value.



## THE XRZ™ FEATURES:

- » **6-year / 600 hour**  
MOW WITH CONFIDENCE™ limited warranty
- » Powerful Kawasaki® FR series engines
- » Tough, smooth-running Hydro-Gear® ZT-3100® transaxles
- » 8-mph ground speed
- » BOB-CAT® exclusive 22-inch Zero-T drive tires
- » Durable TufDeck™ mower decks with 7-gauge side skirts and single-layered 10-gauge tops
- » Patented Double-Wave™ Baffle System deck design lifts grass for a clean cut
- » Large, flexible, molded-polymer discharge chute
- » 6-gallon, impact-resistant, roto-molded fuel tank
- » Comfortable, spring-suspended, premium, high-back, adjustable seat with elastomeric vibration control (EVC) and armrests
- » Convenient flip-up floor plate and open-frame design for easy maintenance

MODEL	MODEL #	ENGINE MAKE	DECK SIZE
XRZ™	942610	Kawasaki® FR651V	48SD
	942611	Kawasaki® FR691V	52SD
	942612	Kawasaki® FR730V	61SD



**XRZ™ Pro**

# GRIT, GUTS AND A PROFESSIONAL CUT



MOW WITH  
**6** YEAR LIMITED  
WARRANTY  
CONFIDENCE™





# TAKE YOUR MOWING SERIOUSLY.

## The peak of performance and value.

Whether you're a lawn care start-up or a homeowner looking for the ultimate zero-turn mower, the BOB-CAT® XRZ™ Pro is the perfect combination of performance and value. Featuring professional-grade Kawasaki® FX series engine options, powerful transaxles for productive ground speeds up to 8 mph, and our quick-lift assist foot pedal, the XRZ™ Pro offers more than the average consumer zero-turn mower. Add power, durability, an exceptional cut quality, and mowing comfort and you get the XRZ™ Pro - a high-quality, affordable mower that does it all.



### THE XRZ™ PRO FEATURES:

- » **6-year / 1000 hour**  
MOW WITH CONFIDENCE™ limited warranty
- » Powerful Kawasaki® FX series engines
- » Tough, smooth-running Hydro-Gear® ZT-3400® transaxles
- » 8-mph ground speed
- » BOB-CAT® exclusive 22-inch Zero-T drive tires
- » Durable TufDeck™ Pro mower deck with 7-gauge side skirts and single-layered 10-gauge top
- » Mower deck features professional-grade spindles, C-channel anti-scalp brackets, adjustable leading edges and welded, reinforced front and trim-side edges
- » Patented Double-Wave™ Baffle System deck design lifts grass for a clean cut
- » Large, flexible, molded-polymer discharge chute
- » 6-gallon, impact-resistant, roto-molded fuel tank
- » Easy-to-use quick-lift assist foot pedal
- » Premium, high-back, adjustable seat with elastomeric vibration control (EVC) and armrests
- » Convenient flip-up floor plate and open-frame design for easy maintenance

MODEL	MODEL #	ENGINE MAKE	DECK SIZE
XRZ™ PRO	942620	Kawasaki® FX651V	48SD
	942621	Kawasaki® FX691V	52SD
	942622	Kawasaki® FX730V	61SD



***FastCat™ Pro***

# PROFESSIONAL PRODUCTIVITY AND A QUALITY CUT



MOW WITH  
**6** YEAR LIMITED  
WARRANTY  
CONFIDENCE™



# CUT TIME AND GRASS.

**Tough jobs and tight corners have met their match.**

The FastCat™ Pro takes speed and maneuverability to new heights. Light on its feet, the FastCat™ Pro features a compact frame and low center of gravity to help you maneuver around obstacles and cling to slopes for productive mowing. And with many of the same operator comfort features as our larger mowers, the FastCat™ Pro is comfortable and easy to operate.



## THE FASTCAT™ PRO FEATURES:

- » **6-year / 2000 hour** MOW WITH CONFIDENCE™ limited warranty
- » Powerful Kawasaki® FX series engines
- » 9.5-gallon, impact-resistant, roto-molded fuel tank
- » Tough, smooth-running Hydro-Gear® ZT-3400® transaxles
- » Fast 10-mph ground speed
- » BOB-CAT® exclusive Zero-T drive tires
- » Heavy-duty DuraDeck™ Cutting System mower decks with 7-gauge side skirts and double-layered 10-gauge top
- » DuraDeck™ lifetime deck, deck cradle and engine deck warranty
- » Patented Double-Wave™ Baffle System deck design with Extreme Discharge System lifts grass for a clean cut and disperses clippings evenly
- » Large, flexible, molded-polymer discharge chute
- » Quick-lift assist foot pedal with hand-assist lever
- » Premium, high-back, adjustable seat with elastomeric vibration control (EVC) and armrests

MODEL	MODEL #	ENGINE MAKE	DECK SIZE
FastCat™ Pro SE	942297	Kawasaki® FX541V	36SD
	942302	Kawasaki® FX600V	42SD
	942406	Kawasaki® FX691V	52SD
FastCat™ Pro	942407	Kawasaki® FX730V	61SD



**QuickCat™**

# STAND YOUR GROUND



MOW WITH  
**6** YEAR LIMITED  
WARRANTY  
CONFIDENCE





# THE STAND-ON MOWER WITH STAND-OUT PERFORMANCE.

Wherever you need to mow, there's a QuickCat™ to get you there.

The QuickCat™ wowed the industry, setting a new standard for stand-on zero-turn mowers. Now, with the new QuickCat™ 36-inch model, designed to mow smaller areas, you can choose from a full line of QuickCat™ stand-on mowers that all deliver power, durability and a comfortable ride. Even at fast mowing speeds, our DuraDeck™ mowing deck provides an unmatched quality cut, allowing you to get jobs done quicker. This year, step onto a QuickCat™ and step up to profitability.



## THE QUICKCAT™ FEATURES:

- » **6-year / 2000 hour** MOW WITH CONFIDENCE™ limited warranty
- » Powerful Kawasaki® FX series engines
- » Large fuel tank with built-in reserve tank
- » Tough, smooth-running Hydro-Gear® ZT-3400® transaxles
- » Selectable ground speeds up to 10.5 mph
- » BOB-CAT® exclusive 23-inch Zero-T drive tires
- » BOB-CAT® exclusive 20-inch Zero-T drive tires on QuickCat™ 36-inch model
- » 48-inch, 52-inch and 61-inch models feature extra-high ground clearance for climbing curbs
- » Heavy-duty DuraDeck™ Cutting System mower decks with 7-gauge side skirts, double-layered 10-gauge top (single 10-gauge top on 36" model) and trim-side deck guard
- » Large, flexible, molded-polymer discharge chute
- » Vibration-dampened operator platform flips up to let you mow like a walk-behind and for more room on your trailer
- » Tethered, removable rider pad for easy access and maintenance



### REMOVABLE RIDER PAD

Convenient access for easy maintenance

MODEL	MODEL #	ENGINE MAKE	DECK SIZE
QuickCat™	912360	Kawasaki® FX600V	36SD
	912480	Kawasaki® FX651V	48SD
	912520	Kawasaki® FX691V	52SD
	912610	Kawasaki® FX730V	61SD



**ProCat™**

# TAKE IT TO THE BANK





# LAYING STRIPES AND KICKING GRASS.

**Serious power and reliability for the serious professional.**

If you're ready to take your business to the next level, the ProCat™ is the machine to get you there — and fast, with speeds up to 11.5 mph. BOB-CAT® exclusive Zero-T drive tires grip on challenging turf while the premium, high-back seat and intuitive controls keep you comfortable all day. Built for the serious professional who demands unflinching performance and durability, the ProCat™ is all business.



## THE PROCAT™ FEATURES:

- » **Best-in-Industry 6-year / 2750 hour** MOW WITH CONFIDENCE™ limited warranty
- » Powerful Kawasaki® FX series engines
- » 14-gallon, impact-resistant, roto-molded fuel tank
- » Commercial-grade, twin 12cc Hydro-Gear™ variable displacement pumps with hydraulic oil cooler and Parker wheel motors
- » Productive 11.5-mph ground speed
- » BOB-CAT® exclusive extra-large Zero-T drive tires
- » Warner® MagStop 225 ft. lb. deck drive clutch
- » New DuraDeck™ XF 61-inch deck with innovative baffle system for maximum vacuum and lift, fast, efficient grass disbursement and enhanced cut quality.
- » Heavy-duty DuraDeck™ Cutting System mower deck features 7-gauge side skirts, double-layered 10-gauge top and trim-side deck guard
- » 52-inch DuraDeck™ features patented Double-Wave™ Baffle System deck design with Extreme Discharge System that lifts grass for a clean cut and even dispersal of clippings
- » Large, flexible, molded-polymer discharge chute
- » Maintenance-free, 1-inch-shaft spindles with double-sealed, precision-ground ball bearings
- » DuraDeck™ and DuraDeck™ XF lifetime deck, deck cradle and engine deck warranty
- » Comfortable operator zone features a premium, mechanical-suspension, high-back seat with full vibration isolation, fore and aft seat adjustments, and adjustable armrests
- » One-handed deck height selector with left/right interchangeable quick-lift assist foot pedal
- » New, smoother controls for easy operation
- » On-the-fly tracking for easy, straight-line mowing
- » Standard ROPS

MODEL	MODEL #	ENGINE MAKE	DECK SIZE
ProCat™	942532	Kawasaki® FX691V	52SD
	942542	Kawasaki® FX730V	61SD DuraDeck™ XF
	942535	Kawasaki® FX801V	52SD
	942543	Kawasaki® FX801V	61SD DuraDeck™ XF



***Predator-Pro™***

**FEARLESS  
POWER  
PEERLESS  
PERFORMANCE**







# IT DOESN'T GET ANY BETTER THAN THIS.

**Mow down the competition with the leader in productivity and performance.**

Want the absolute best? Then the Predator-Pro™ is the machine for you. Backed by the most ferocious warranty in the business — 6-year / 2750 hours — the Predator-Pro™ was bred for one single purpose: to make you money. With the ultimate combination of speed, power, durability and ease of maintenance, the Predator-Pro™ will move your business to the top of the food chain. The 61-inch deck boasts our new DuraDeck™ XF design, delivering enhanced cut quality and a gapped baffle system for improved clipping dispersal.



## THE PREDATOR-PRO™ FEATURES:

- » **Best-in-Industry 6-year / 2750 hour** MOW WITH CONFIDENCE™ limited warranty
- » Powerful Kawasaki® FX series engines
- » 14-gallon, impact-resistant, roto-molded fuel tank
- » Commercial-grade, twin 16cc Hydro-Gear™ variable displacement pumps with hydraulic oil cooler and Parker wheel motors
- » Productive 12.5-mph ground speed
- » BOB-CAT® exclusive extra-large 24-inch Zero-T drive tires
- » Rounded, no-flat front caster wheels
- » Warner® MagStop 250 ft. lb. deck drive clutch
- » New DuraDeck™ XF 61-inch deck with innovative baffle system for maximum vacuum and lift, fast, efficient grass disbursement and enhanced cut quality (Model 942545 only)
- » 72-inch DuraDeck™ Cutting System mower deck features 7-gauge side skirts, double-layered 10-gauge top and trim-side deck guard
- » 72-inch heavy-duty DuraDeck™ features patented Double-Wave™ Baffle System deck design with Extreme Discharge System that lifts grass for a clean cut and even dispersal of clippings
- » Large, flexible, molded-polymer discharge chute
- » Maintenance-Free, 1-inch-shaft spindles with double-sealed, precision-ground ball bearings
- » DuraDeck™ and DuraDeck™ XF lifetime deck, deck cradle and engine deck warranty
- » ISO-Ride™ Comfort System custom operator zone with mechanical-suspension, high-back seat, full vibration isolation with fore and aft seat adjustments, and adjustable armrests
- » One-handed deck height selector with left/right interchangeable quick-lift assist foot pedal
- » New, smoother controls for easy operation
- » On-the-fly tracking for easy straight-line mowing
- » Standard ROPS

## LIQUID PROPANE FOR SOLID SAVINGS & GREENER MOWING

The Predator-Pro™ LP delivers a full day of work without refueling, thanks to a direct-withdrawal liquid propane system that equals gasoline performance with half the emissions.

MODEL	MODEL #	ENGINE MAKE	DECK SIZE
Predator-Pro™	942545	Kawasaki® FX1000V	61SD
	942519	Kawasaki® FX1000V	72SD
Predator-Pro™ LP (Liquid Propane)	942509	Generac® GTV990 Gen LP	61SD



*Hydro-Drive Walk-Behind*

# TAKE A WALK ON THE PRODUCTIVE SIDE





# PUT THE CONTROL IN YOUR HANDS.

**The ultimate in walk-behind quality, durability and easy operation.**

With a range of options to suit your budget and mowing needs, BOB-CAT® Hydro-Drive walk-behind mowers are the benchmark for productive performance and superior results. Available with a standard or floating deck and your choice of our patented Z-Control™ or SoftGrip™ EZ controls, the Hydro-Drive models will keep you comfortable all day while delivering a killer cut.



## THE HYDRO-DRIVE WALK-BEHIND FEATURES:

- » **Industry-leading 3-year / 2500 hour** MOW WITH CONFIDENCE™ limited warranty
- » Powerful Kawasaki® FS or Kawasaki® FX series engines (depending on model)
- » 5-gallon, impact-resistant, roto-molded fuel tank
- » Hydro-Gear® variable displacement pumps and wheel motors
- » Warner® MagStop 175 ft. lb. or 125 ft. lb. deck drive clutch (depending on model)
- » Heavy-duty DuraDeck™ Cutting System mower decks
- » Maintenance-free, 1-inch-shaft spindle assemblies with double-sealed, precision-ground ball bearings
- » Available float deck model helps prevent scalping
- » Patented Double-Wave™ Baffle System deck design with Extreme Discharge System lifts grass for a clean cut and disperses clippings evenly
- » Large, flexible, molded-polymer discharge chute
- » Hydrostatic dynamic braking
- » BOB-CAT® exclusive 16-inch or 18-inch Zero-T drive tires
- » No-flat front caster wheels



### HYDRO-DRIVE FLOAT DECK

Our float deck moves independently of the drive and caster wheels, to follow undulating terrain without scalping. It features a single-point height-of-cut adjustment for easy mowing height changes.

MODEL	MODEL #	ENGINE MAKE	CONTROLS	DECK SIZE
Hydro-Drive	933305	Kawasaki® FS481V	Pistol Grip	36SD
	934306	Kawasaki® FS541V	Pistol Grip	48SD
	934307	Kawasaki® FS541V ES*	Pistol Grip	48SD
	935308	Kawasaki® FS600V	Pistol Grip	52SD
Hydro Z-Control	934332	Kawasaki® FS541V	Z-Control™	48SD
Float Deck	936600	Kawasaki® FX541V ES*	Pistol Grip	48 Float SD
	936601	Kawasaki® FX600V ES*	Pistol Grip	52 Float SD

\*ES - Electric Start





# FIELD-PROVEN POWER, PERFORMANCE AND DURABILITY.

Decades of trust, quality and reliability.

For over 40 years, our Classic Pro Gear-Drive Walk-Behind has earned its place on countless trailers with unsurpassed reliability and value. Ultra-rugged, yet tamed with modern features for all-day comfort and convenience, the Classic Pro Gear-Drive Walk-Behind is the pinnacle of no-nonsense, get-the-job-done practicality.

## THE CLASSIC PRO GEAR-DRIVE WALK-BEHIND FEATURES:

- » **Best-in-Industry 3-year / 2500 hour** MOW WITH CONFIDENCE™ limited warranty
- » Powerful Kawasaki® FS series engines
- » 5-gallon, impact-resistant, roto-molded fuel tank
- » Peerless® 5-speed transmission with reverse assist
- » Warner® MagStop 125 ft. lb. deck drive clutch
- » Heavy-duty DuraDeck™ Cutting System mower decks
- » Maintenance-free 1-inch-shaft spindle assemblies with double-sealed, precision-ground ball bearings
- » Patented Double-Wave™ Baffle System deck design with Extreme Discharge System lifts grass for a clean cut and disperses clippings evenly
- » Large, flexible, molded-polymer discharge chute
- » No-flat front caster wheels
- » Aluminized steel muffler positioned low to eliminate damage when mowing under shrubs and bushes
- » Comfortable handling with intuitive SoftGrip™ EZ controls
- » BOB-CAT® exclusive 13-inch Zero-T drive tires



MODEL	MODEL #	ENGINE MAKE	CONTROLS	DECK SIZE
Classic Pro (Gear-Drive)	932007	Kawasaki® FS481V	Pistol Grip	32SD
	933007	Kawasaki® FS481V	Pistol Grip	36SD
	934007	Kawasaki® FS481V	Pistol Grip	48SD



**BOSS-Vac Collection Systems**

**PICK UP  
PROFITS**

## THE NEW STANDARD IN GRASS COLLECTION SYSTEMS

**Clean up on lawns and profits.**

The Boss-Vac™ VL dump-from-seat models feature patented vertical lift technology that lets you raise the hopper straight up and back within inches of an obstacle. A high-powered blower, clog-reducing grass tube and excellent front and rear visibility make the Boss-Vac™ VL the ultimate in collection systems. The Boss-Vac™ is also available in two-bag or three-bag models.

### THE BOSS-VAC™ COLLECTION SYSTEM FEATURES:

- » Available in 8- or 12-bushel dump-from-seat models
- » Choice of 8- or 12-bushel collection-bag models
- » Electrical dump operation
- » Double-hinge lift-pivot-dump system
- » Front counterweight system improves stability without limiting visibility
- » Oversized air vent hood for enhanced collector filling
- » Large 15-inch fan quickly moves debris
- » Molded, high-density tube reduces clogging
- » Smooth inner panel construction for complete dumping
- » Outer support frame for added strength
- » Quick-disconnect bumper mount for easy on and off



8-Bushel 2-Bag



12-Bushel 3-Bag



8-Bushel Dump-From-Seat



# CUSTOMIZE YOUR CAT

	CRZ™	XRZ™ PRO XRZ™	FastCat™ Pro	QuickCat™	ProCat™	Predator-Pro™	Walk-Behinds
<b>MULCHING BAFFLE KIT: Eliminator blades</b>	48", 52", 61"	48", 52", 61"	36", 48", 52", 61"	36", 48", 52", 61"	52", 61"	52", 61"	32", 36", 48", 52"
<b>MULCHING BAFFLE KIT: Medium lift blades</b>			42"				
<b>ECO PLATE</b>	48", 52", 61"	48", 52", 61"	36", 42", 48", 52", 61"	36", 48", 52", 61"	52", 61"	52", 61", 72"	32", 36", 48", 54"
<b>GRASS CATCHER: Poly dump, 3.75 or 5.0 bushel</b>	X	X	X	X			X
<b>GRASS CATCHER: Metal, jumbo easy-dump, 4.3 cu. ft.</b>							X
<b>WEIGHT KIT</b>							36", 48", 54"
<b>HYDRO COLD START KIT</b>							X
<b>BOSS-VAC™ PRO 12-BUSHEL COLLECTION SYSTEM</b>					X	X	
<b>BOSS-VAC™ 8-BUSHEL COLLECTION SYSTEM</b>			X				
<b>DECK STRIPING KIT</b>			61"		52", 61"	52", 61"	
<b>ZT HITCH KIT</b>			X		X	X	
<b>MAGNETIC LIGHT KIT</b>		X	X		X	X	
<b>61" WIDE TRACK KIT: Widens track on 61" unit</b>					X	X	
<b>MAGNETIC LIGHT 12V KIT</b>	X			X			



**GRASS CATCHER: 5.0 Bushel**



**GRASS CATCHER: Jumbo**



**MAGNETIC LIGHT KIT**



**ZT HITCH KIT**

**SPECS**





	MODEL	CRZ™ 942604	CRZ™ 942605	CRZ™ 942606	XRZ™ 942610	XRZ™ 942611	XRZ™ 942612
ENGINE	Make	Kawasaki® FR651V	Kawasaki® FR651V	Kawasaki® FR691V	Kawasaki® FR651V	Kawasaki® FR691V	Kawasaki® FR730V
	Displacement	726 cc	726 cc	726 cc	726cc	726 cc	726 cc
	Fuel Capacity	6 gal.	6 gal.	6 gal.	6 gal.	6 gal.	6 gal.
	Air Filtration	Single Stage	Single Stage	Single Stage	Single Stage	Single Stage	Single Stage
ELECTRICAL	Charging System	15 amp	15 amp	15 amp	15 amp	15 amp	15 amp
	Clutch	105 ft. lb.	105 ft. lb.	125 ft. lb.	125 ft. lb.	125 ft. lb.	125 ft. lb.
DECK	Mower Deck	TufDeck™ 10-gauge fabricated, welded and reinforced steel			TufDeck™ 10-gauge fabricated, welded and reinforced steel		
	Leading Edges	Adjustable, 2 positions			Adjustable, 2 positions		
	Width	48"	52"	61"	48"	52"	61"
	Anti Scalp Rollers	3	3	7	3	3	7
	Cutting Height	1.5" – 4.875"	1.5" – 4.875"	1.5" – 4.875"	1.5" – 4.875"	1.5" – 4.875"	1.5" – 4.875"
	Blade Tip Speed	17,365 fpm @ 3550 engine rpm	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm	17,365 fpm @ 3550 engine rpm	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
	Discharge Chute	Flexible, Molded-Polymer			Flexible, Molded-Polymer		
FRAME	Form Welded	Welded 7-gauge steel 1.5" x 2.5" steel tubing			Welded 7-gauge steel 1.5" x 2.5" steel tubing		
	Machine Weight	736 lb.	752 lb.	795 lb.	736 lb.	752 lb.	795 lb.
	ROPS	N/A			N/A		
TRANSMISSION	Type	HG ZT-2800 Hydrostatic Transaxles			HG ZT-3100 Hydrostatic Transaxles		
	Displacement	10 cc	10 cc	10 cc	10 cc	10 cc	10 cc
	Oil Capacity	4 qt.	4 qt.	4 qt.	4 qt.	4 qt.	4 qt.
	Ground Speed	7 mph	7 mph	7 mph	8 mph	8 mph	8 mph
	Motion Control Levers	Adjustable & Dampened			Adjustable & Dampened		
WHEELS	Drive Wheel Size	20 x 10.0-10	20 x 10.0-10	20 x 12.0-10	22 x 11.0-10	22 x 11.0-10	22 x 11.0-10
	Front Caster Size	13 x 5.0-6	13 x 5.0-6	13 x 5.0-6	13 x 5.0-6	13 x 5.0-6	13 x 5.0-6
	Caster Type	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic
SEAT	Description	High-Back w/ Armrests			High-Back w/ Armrests		
	Adjustment	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever
	Suspension	Spring Suspension	Spring Suspension	Spring Suspension	EVC & Spring Suspension	EVC & Spring Suspension	EVC & Spring Suspension
	Armrests	Yes	Yes	Yes	Yes	Yes	Yes
WARRANTY		5-year / 500 hour MOW WITH CONFIDENCE™ Limited Warranty			6-year / 600 hour MOW WITH CONFIDENCE™ Limited Warranty		



		XRZ™ PRO	XRZ™ PRO	XRZ™ PRO
MODEL		942620	942621	942622
ENGINE	Make	Kawasaki® FX651V	Kawasaki® FX691V	Kawasaki® FX730V
	Displacement	726 cc	726 cc	726 cc
	Fuel Capacity	6 gal.	6 gal.	6 gal.
	Air Filtration	Dual-stage canister	Dual-stage canister	Dual-stage canister
ELECTRICAL	Charging System	15 amp	15 amp	15 amp
	Clutch	125 ft. lb.	125 ft. lb.	125 ft. lb.
DECK	Mower Deck	TufDeck™ Pro with 7-gauge side skirts and single-layered 10-gauge top	TufDeck™ Pro with 7-gauge side skirts and single-layered 10-gauge top	TufDeck™ Pro with 7-gauge side skirts and single-layered 10-gauge top
	Leading Edges	Adjustable front lip standard	Adjustable front lip standard	Adjustable front lip standard
	Width	48"	52"	61"
	Anti Scalp Rollers	3	3	7
	Cutting Height	1.5" – 4.875"	1.5" – 4.875"	1.5" – 4.875"
	Blade Tip Speed	17,365 fpm @ 3550 engine rpm	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
	Discharge Chute	Flexible, Molded-Polymer	Flexible, Molded-Polymer	Flexible, Molded-Polymer
FRAME	Form Welded	Welded 7-gauge steel 1.5" x 2.5" steel tubing	Welded 7-gauge steel 1.5" x 2.5" steel tubing	Welded 7-gauge steel 1.5" x 2.5" steel tubing
	Form Welded	758 lbs	774 lb.	817 lbs
	ROPS	N/A	N/A	N/A
TRANSMISSION	Type	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles
	Displacement	12 cc	12 cc	12 cc
	Oil Capacity	4 qt.	4 qt.	4 qt.
	Ground Speed	8 mph	8 mph	8 mph
	Motion Control Levers	Adjustable & Dampened	Adjustable & Dampened	Adjustable & Dampened
WHEELS	Drive Wheel Size	22 x 11.0-10	22 x 11.0-10	22 x 11.0-10
	Front Caster Size	13 x 5.0-6	13 x 5.0-6	13 x 5.0-6
	Caster Type	Pneumatic	Pneumatic	Pneumatic
SEAT	Description	High-Back w/ Armrests	High-Back w/ Armrests	High-Back w/ Armrests
	Adjustment	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever
	Suspension	EVC & Spring Suspension	EVC & Spring Suspension	EVC & Spring Suspension
	Armrests	Yes	Yes	Yes
WARRANTY		6-year / 1000 hour MOW WITH CONFIDENCE™ Limited Warranty		

		FastCat <sup>™</sup> Pro SE	FastCat <sup>™</sup> Pro SE	FastCat <sup>™</sup> Pro	FastCat <sup>™</sup> Pro
	MODEL	942297	942302	942406	942407
ENGINE	Make	Kawasaki® FX541V	Kawasaki® FX600V	Kawasaki® FX691V	Kawasaki® FX730V
	Displacement	603 cc	603 cc	726 cc	726 cc
	Fuel Capacity	9.5 gal.	9.5 gal.	9.5 gal.	9.5 gal.
	Air Filtration	Canister Air Filter	Canister Air Filter	Canister Air Filter	Canister Air Filter
ELECTRICAL	Charging System	15 amp	15 amp	15 amp	15 amp
	Clutch	125 ft. lb.	125 ft. lb.	200 ft. lb.	200 ft. lb.
DECK	Mower Deck	DuraDeck <sup>™</sup> Cutting System	DuraDeck <sup>™</sup> Cutting System	DuraDeck <sup>™</sup> Cutting System	DuraDeck <sup>™</sup> Cutting System
	Leading Edges	Adjustable, 2 positions	Adjustable, 2 positions	Adjustable, 2 positions	Adjustable, 2 positions
	Width	36"	42"	52"	61"
	Anti Scalp Rollers	0	2	3	6
	Cutting Height	1.5" – 4.875"	1.5" – 4.875"	1.5" – 4.875"	1.5" – 4.875"
	Blade Tip Speed	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
	Discharge Chute	Flexible, Molded-Polymer	Flexible, Molded-Polymer	Flexible, Molded-Polymer	Flexible, Molded-Polymer
	Form Welded	Welded 7-gauge steel 1.5" x 2.5" steel tubing	Welded 7-gauge steel 1.5" x 2.5" steel tubing	Welded 7-gauge steel 1.5" x 2.5" steel tubing	Welded 7-gauge steel 1.5" x 2.5" steel tubing
FRAME	Machine Weight	705 lb.	744 lb.	840 lb.	905 lb.
	ROPS	Folding Optional	Folding Optional	Folding Optional	Folding Standard
TRANSMISSION	Type	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles
	Displacement	10 cc	10 cc	12 cc	12 cc
	Oil Capacity	4 qt.	4 qt.	4 qt.	4 qt.
	Ground Speed	8 mph	8 mph	10 mph	10 mph
WHEELS	Motion Control Levers	Adjustable & Dampened	Adjustable & Dampened	Adjustable & Dampened	Adjustable & Dampened
	Drive Wheel Size	20 x 6.5-10	20 X 8.0-10	23 x 10.5-12	23 x 10.5-12
	Front Caster Size	11 x 4.0-5	11 x 4.0-5	13 x 6.5-6	13 x 6.5-6
	Caster Type	Pneumatic	Pneumatic	Pneumatic	Pneumatic
SEAT	Description	High-Back w/ Armrests	High-Back w/ Armrests	High-Back w/ Armrests	High-Back w/ Armrests
	Adjustment	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever
	Suspension	EVC	EVC	EVC	EVC
	Armrests	Yes, Adjustable	Yes, Adjustable	Yes, Adjustable	Yes, Adjustable
WARRANTY		6-year / 2000 hour MOW WITH CONFIDENCE <sup>™</sup> Limited Warranty			





		QuickCat™	QuickCat™	QuickCat™	QuickCat™
MODEL		912360	912480	912520	912610
ENGINE	Make	Kawasaki® FX600V	Kawasaki® FX651V	Kawasaki® FX691V	Kawasaki® FX730V
	Displacement	603 cc	726 cc	726 cc	726 cc
	Fuel Capacity	5.1 gal.	6.5 gal.	6.5 gal.	6.5 gal.
	Air Filtration	Dual-Stage Canister	Dual-Stage Canister	Dual-Stage Canister	Dual-Stage Canister
ELECTRICAL	Charging System	15 amp	15 amp	15 amp	15 amp
	Clutch	125 ft. lb.	200 ft. lb.	200 ft. lb.	200 ft. lb.
DECK	Mower Deck	DuraDeck™ Cutting System	DuraDeck™ Cutting System	DuraDeck™ Cutting System	DuraDeck™ Cutting System
	Leading Edges	Adjustable	Adjustable	Adjustable	Adjustable
	Width	36"	48"	52"	61"
	Anti Scalp Rollers	3	4	4	7
	Cutting Height	1.5" – 4.5"	1.5" – 4.5"	1.5" – 4.5"	1.5" – 4.5"
	Blade Tip Speed	17,600 fpm @ 3550 engine rpm	18,000 fpm @ 3550 engine rpm	18,400 fpm @ 3550 engine rpm	18,800 fpm @ 3550 engine rpm
	Discharge Chute	Flexible, Molded-Polymer	Flexible, Molded-Polymer	Flexible, Molded-Polymer	Flexible, Molded-Polymer
FRAME	Form Welded	Form Welded with Structural Tubing	Form Welded with Structural Tubing	Form Welded with Structural Tubing	Form Welded with Structural Tubing
	Machine Weight	775 lb.	886 lb.	916 lb.	953 lb.
TRANSMISSION	Type	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles
	Displacement	10 cc	12 cc	12 cc	12 cc
	Oil Capacity	4 qt.	4 qt.	4 qt.	4 qt.
	Ground Speed	9 mph	10.5 mph	10.5 mph	10.5 mph
	Motion Control Levers	Adjustable; Cut and Transport Speed Control	Adjustable; Cut and Transport Speed Control	Adjustable; Cut and Transport Speed Control	Adjustable; Cut and Transport Speed Control
WHEELS	Drive Wheel Size	20 x 8-10	23 x 8.5-12	23 x 10.5-12	23 x 10.5-12
	Front Caster Size	11 x 4.0-5	13 x 5.0-6	13 x 5.0-6	13 x 5.0-6
	Caster Type	Pneumatic	Pneumatic	Pneumatic	Pneumatic
OPERATOR PLATFORM	Adjustment	Flip Up and Latch	Flip Up and Latch	Flip Up and Latch	Flip Up and Latch
	Rider Pad	Tethered, Removable for Service	Tethered, Removable for Service	Tethered, Removable for Service	Tethered, Removable for Service
	Vibration Isolation	Dampened	Dampened	Dampened	Dampened
WARRANTY		6-year / 2000 hour MOW WITH CONFIDENCE™ Limited Warranty			

SPECS

	MODEL	ProCat™	ProCat™
		942532	942535
ENGINE	Make	Kawasaki® FX691V	Kawasaki® FX801V
	Displacement	726 cc	852 cc
	Fuel Capacity	14 gal.	14 gal.
	Air Filtration	Canister	Canister
ELECTRICAL	Charging System	15 amp	15 amp
	Clutch	MagStop 225 ft. lb.	MagStop 225 ft. lb.
DECK	Mower Deck	DuraDeck™ Cutting System	DuraDeck™ Cutting System
	Leading Edges	Adjustable	Adjustable
	Width	52"	52"
	Anti Scalp Rollers	7	7
	Cutting Height	1" – 5.5"	1" – 5.5"
	Blade Tip Speed	18,404 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
FRAME	Discharge Chute	Flexible, Molded-Polymer	Flexible, Molded-Polymer
	Form Welded	Welded 3- and 7-gauge steel	Welded 3- and 7-gauge steel
	Machine Weight	1256 lb.	1256 lb.
	ROPS	Standard	Standard
TRANSMISSION	Type	HG Pumps with Parker Wheel Motors	HG Pumps with Parker Wheel Motors
	Displacement	12 cc	12 cc
	Oil Capacity	7.5 qt.	7.5 qt.
	Ground Speed	11.5 mph	11.5 mph
WHEELS	Motion Control Levers	Adjustable & Dampened	Adjustable & Dampened
	Drive Wheel Size	23 x 10.5-12	23 x 10.5-12
	Front Caster Size	13 x 6.5-6	13 x 6.5-6
	Caster Type	Pneumatic	Pneumatic
SEAT	Description	High-Back, Mechanical Suspension	High-Back, Mechanical Suspension
	Adjustment	Yes	Yes
	Suspension	Mechanical Weight Adjustment	Mechanical Weight Adjustment
	Armrests	Yes, Adjustable	Yes, Adjustable
WARRANTY		Best-in-Industry 6-year / 2750 hour MOW WITH CONFIDENCE™ Limited Warranty	





	MODEL	ProCat™	ProCat™
		942542	942543
ENGINE	Make	Kawasaki® FX730V	Kawasaki® FX801V
	Displacement	726 cc	852 cc
	Fuel Capacity	14 gal.	14 gal.
	Air Filtration	Canister	Canister
ELECTRICAL	Charging System	15 amp	15 amp
	Clutch	MagStop 225 ft. lb.	MagStop 225 ft. lb.
DECK	Mower Deck	DuraDeck™ XF Cutting System	DuraDeck™ XF Cutting System
	Leading Edges	Adjustable	Adjustable
	Width	61"	61"
	Anti-Scalp Rollers	7	7
	Cutting Height	1" – 4.75"	1" – 4.75"
	Blade Tip Speed	18,809 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
	Discharge Chute	Flexible, Molded-Polymer	Flexible, Molded-Polymer
FRAME	Form Welded	Welded 3- and 7-gauge steel	Welded 3- and 7-gauge steel
	Machine Weight	1293 lb.	1293 lb.
	ROPS	Standard	Standard
TRANSMISSION	Type	HG Pumps with Parker Wheel Motors	HG Pumps with Parker Wheel Motors
	Displacement	12 cc	12 cc
	Oil Capacity	7.5 qt.	7.5 qt.
	Ground Speed	11.5 mph	11.5 mph
WHEELS	Motion Control Levers	Adjustable & Dampened	Adjustable & Dampened
	Drive Wheel Size	24 x 12.0-12	24 x 12.0-12
	Front Caster Size	13 x 6.5-6	13 x 6.5-6
	Caster Type	Pneumatic	Pneumatic
SEAT	Description	High-Back, Mechanical Suspension	High-Back, Mechanical Suspension
	Adjustment	Yes	Yes
	Suspension	Mechanical Weight Adjustment	Mechanical Weight Adjustment
	Armrests	Yes, Adjustable	Yes, Adjustable
WARRANTY		Best-in-Industry 6-year / 2750 hour MOW WITH CONFIDENCE™ Limited Warranty	

SPECS

		Predator-Pro™ LP	Predator-Pro™	Predator-Pro™
MODEL		942509	942545	942519
ENGINE	Make	Generac GTV990 LP	Kawasaki® FX1000V	Kawasaki® FX1000V
	Displacement	992 cc	999 cc	999 cc
	Fuel Capacity	2 - 35 lb. LP Tanks	14 gal.	14 gal.
	Air Filtration	Canister	Canister	Canister
ELECTRICAL	Charging System	15 amp	15 amp	15 amp
	Clutch	MagStop 250 ft. lb.	MagStop 250 ft. lb.	MagStop 250 ft. lb.
DECK	Mower Deck	DuraDeck™ Cutting System	DuraDeck™ XF Cutting System	DuraDeck™ Cutting System
	Leading Edges	Adjustable	Adjustable	Adjustable
	Width	61"	61"	72"
	Anti Scalp Rollers	7	7	7
	Cutting Height	1" – 5.5"	1" – 4.75"	1" – 5.5"
	Blade Tip Speed	18,809 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm	18,770 fpm @ 3550 engine rpm
	Discharge Chute	Flexible, Molded-Polymer	Flexible, Molded-Polymer	Flexible, Molded-Polymer
FRAME	Form Welded	Welded 3- and 7-gauge steel	Welded 3-and 7-gauge steel	Welded 3-and 7-gauge steel
	Machine Weight	1293 lb.	1293 lb.	1404 lb.
	ROPS	Standard	Standard	Standard
TRANSMISSION	Type	HG Pumps with Parker Wheel Motors	HG Pumps with Parker Wheel Motors	HG Pumps with Parker Wheel Motors
	Displacement	16 cc	16 cc	16 cc
	Oil Capacity	7.5 qt.	7.5 qt.	7.5 qt.
	Ground Speed	13.5 mph	12.5 mph	12.5 mph
WHEELS	Motion Control Levers	Adjustable & Dampened	Adjustable & Dampened	Adjustable & Dampened
	Drive Wheel Size	24 x 12.0-12	24 x 12.0-12	24 x 12.0-12
	Front Caster Size	13 x 6.5-6	13 x 6.5-6	13 x 6.5-6
	Caster Type	No-flat	No-flat	No-flat
SEAT	Description	High-Back, Mechanical Suspension	High-Back, Mechanical Suspension	High-Back, Mechanical Suspension
	Adjustment	Yes	Yes	Yes
	Suspension	Mechanical Weight Adjustment	Mechanical Weight Adjustment	Mechanical Weight Adjustment
	Armrests	Yes, Adjustable	Yes, Adjustable	Yes, Adjustable
WARRANTY		Best-in-Industry 6-year / 2750 hour MOW WITH CONFIDENCE™ Limited Warranty		



# Walk-Behind Mowers

		Classic Pro	Classic Pro	Classic Pro	Hydro	Hydro
MODEL		932007	933007	934007	933305	934306
ENGINE	Make	Kawasaki® FS481V	Kawasaki® FS481V	Kawasaki® FS481V	Kawasaki® FS481V	Kawasaki® FS541V
	Displacement	603 cc			603 cc	
	Lubrication	Full pressure - Spin on filter			Full pressure - Spin on filter	
	Fuel Capacity	5 gal.			5 gal.	
	Air Filtration	Dual Element			Dual Element	
DECK	Mower Deck	DuraDeck™ side discharge with molded-rubber chute, fabricated 7-gauge deck top plus 7-gauge reinforcements			DuraDeck™ side discharge with molded-rubber chute, fabricated, 7-gauge deck top plus 7-gauge reinforcements	
	Width	32"	36"	48"	36"	48"
	Cutting Height	1.5" – 4.5"			1.38" – 4.63"	
	Blade Tip Speed	17,886 fpm @ 3600 engine rpm	18,784 fpm @ 3600 engine rpm	17,886 fpm @ 3600 engine rpm	16,964 fpm @ 3600 engine rpm	15,315 fpm @ 3600 engine rpm
	Deck Skirts	7-gauge skirts			7-gauge skirts	
	Spindle Type	Maintenance-free with 1" shaft			Maintenance-free with 1" shaft	
	Spindle Bearing	Double-sealed, precision-ground ball bearings			Double-sealed, precision-ground ball bearings	
	Deck Drive	Warner® MagStop 125 ft. lb. electric clutch			Warner® MagStop 125 ft. lb. electric clutch	
SIZE	Machine Length	78"			78"	
	Machine Height	40.3"			40.3"	
	Machine Weight	400 lb.	428 lb.	476 lb.	528 lb.	582 lb.
TRANSMISSION	Type	Peerless® 5-speed with rev assist			Hydro-Gear variable displacement pumps	
	Pump Size	N/A			10 cc pumps with separate wheel motors	
	Ground Speed	5.1 mph			6 mph	
WHEELS	Front Tires	9 x 3.5-4 no-flats			9 x 3.5-4 no-flats	
	Rear Tires	13 x 5-6 4-ply	13 x 6.5-6 4-ply	13 x 6.5-6 4-ply	16 x 7.5-8 4-ply	
WARRANTY		Best-in-Industry 3-year / 2500 hour MOW WITH CONFIDENCE™ Limited Warranty				

SPECS

Hydro-Electric Start	Hydro	Z-Control Hydro	Hydro Float Deck	Hydro Float Deck
934307	935308	934332	936600	936601
Kawasaki® FS541V	Kawasaki® FS600V	Kawasaki® FS541V	Kawasaki® FX541V	Kawasaki® FX600V
603 cc		603 cc	603 cc	603 cc
Full pressure – Spin on filter		Full pressure – Spin on filter	Full pressure – Spin on filter	Full pressure – Spin on filter
5 gal.		5 gal.	5 gal.	5 gal.
Dual Element		Dual Element	Dual-stage canister	Dual-stage canister
DuraDeck™ side discharge with molded-rubber chute, fabricated 7-gauge deck top plus 7-gauge reinforcements		DuraDeck™ side discharge with molded-rubber chute, fabricated 7-gauge deck top plus 7-gauge reinforcements	DuraDeck™ side discharge with flexible molded-polymer chute & fabricated two-layer 10-gauge deck top	
48"	52"	48"	48"	52"
1.38" – 4.63"		1.38" – 4.63"	1.5" – 5.0"	1.5" – 5.0"
15,315 fpm @ 3600 engine rpm	16,964 fpm @ 3600 engine rpm	15,315 fpm @ 3600 engine rpm	18,600 fpm @ 3600 engine rpm	18,600 fpm @ 3600 engine rpm
7-gauge skirts		7-gauge skirts	7-gauge skirts	7-gauge skirts
Maintenance-free with 1" shaft		Maintenance-free with 1" shaft	Maintenance-free with 1" shaft	Maintenance-free with 1" shaft
Double-sealed, precision-ground ball bearings		Double-sealed, precision-ground ball bearings	Double-sealed, precision-ground ball bearings	Double-sealed, precision-ground ball bearings
Warner® MagStop 125 ft. lb. electric clutch		Warner® MagStop 125 ft. lb. electric clutch	Warner® MagStop 175 ft. lb. electric clutch	Warner® MagStop 175 ft. lb. electric clutch
78"		78"	80.7"	80.7"
40.3"		40.3"	40.3"	40.3"
582 lb.	593 lb.	528 lb.	780 lb.	795 lb.
Hydro-Gear variable displacement pumps		Hydro-Gear variable displacement pumps	Hydro-Gear variable displacement pumps	Hydro-Gear variable displacement pumps
10 cc pumps with separate wheel motors				
6 mph		6 mph	6.7 mph	6.7 mph
9 x 3.5-4 no-flats		9 x 3.5-4 no-flats	11 x 4-5 no-flats	11 x 4-5 no-flats
16 x 7.5-8 4-ply		16 x 7.5-8 4-ply	18 x 7.5-8 4-ply	18 x 7.5-8 4-ply

Best-in-Industry 3-year / 2500 hour MOW WITH CONFIDENCE™ Limited Warranty



# NEVER SETTLE FOR LESS

Durability. Quality of Cut. Ease of Ownership. At BOB-CAT®, we give you all three, because we know you'd rather be thinking about more than whether your mower is going to do its job. Those are our three pillars — a stable base on which to rest easy knowing that whatever the job calls for, your BOB-CAT® mower is up to the challenge.



One BOB-CAT Lane, P.O. Box 0469  
Johnson Creek, WI 53038-0469

**1.866.469.1242 | [bobcatturf.com](http://bobcatturf.com)**

