

VERTECON®

3, 4 AND 5-STAGE OPEN HIGH PRESSURE BREATHING AIR COMPRESSORS

BAUER's VERTECON series of high pressure breathing air compressor systems have been an industry leader for many years. An economical design featuring the latest BAUER technological enhancements and unsurpassed maintenance accessibility are incorporated within the simplistic platform. The series now features an integral base which eliminates the guess work of product placement, insuring the system has been installed correctly for system ventilation and maintenance accessibility. With the advent of the integral base the compressor package also has the ability of having a sound attenuated enclosure optionally installed at a later date. A refreshed HMI operations panel and electrical control system allow you to tailor the system to your specific requirements. When simple is what you want look to BAUER.

EFFECTIVE: 05/01/18

- › **PRESSURE:**
Up to 6000 PSIG
(414 BAR)
- › **CHARGING RATE:**
5 to 26.4 SCFM
(142 to 748 L/MIN)
- › **POWER:**
5 to 20 HP (3.7 to 15 kW)



› VERTECON

STANDARD SCOPE OF SUPPLY

- › BAUER breathing air purification system
- › Open vertical design incorporating formed sheet and plate goods provide a firm foundation for all pressure bearing components
- › Modern design with unsurpassed maintenance accessibility (no hand tools are required for normal maintenance checks and fluid level confirmation)
- › BAUER PLC based controller with 7” HMI display
- › Belt adjustment tool
- › NEMA 4 rated electrical enclosure with UL® listed control panel
- › All wiring harnesses incorporated within a corrugated loom with number coding for easy system diagnosis
- › Emergency stop push button
- › .049 wall thickness stainless steel tubing and high pressure hoses throughout
- › Rugged powder coat finish
- › Zero loss automatic condensate drain system
- › Interstage pressure gauges (locally mounted)
- › Compressor on/off, final pressure, oil pressure and high temperature shutdown
- › Motor overload indication
- › Final separator counter with shutdown and operator indication
- › Unique integrated positioning base which ensures correct installation everytime

TECHNICAL DATA

Model	Charging Rate ¹		Number of Stages	Motor		FAD ²	RPM	Purification System	Price
	SCFM	L/MIN		HP	kW				
5000 PSIG (345 BAR)									
VEC08-E1	8.4	238	3	7.5	5.6	7	1250	P31	\$15,067.00
VEC08-E3	8.4	238	3	7.5	5.6	7	1250	P31	\$14,798.00
VEC20-E3	21	595	4	15	11	17.5	1300	P5	\$30,648.00
VEC26-E3	26.4	748	4	20	15	22	1350	P5	\$34,589.00
6000 PSIG (414 BAR)									
VEC05-E1	5	142	3	5	3.7	4	1050	P2 SECURUS	\$19,774.00
VEC05-E3	5	142	3	5	3.7	4	1050	P2 SECURUS	\$19,697.00
VEC10-E1	9.7	275	4	7.5	5.6	8.1	1180	P2	\$24,018.00
VEC10-E3	9.7	275	4	7.5	5.6	8.1	1180	P2	\$23,465.00
VEC13-E1	13	368	4	10	7.5	10.8	1420	P2	\$24,569.00
VEC13-E3	13	368	4	10	7.5	10.8	1420	P2	\$24,014.00
VEC18-E3	18	510	4	15	11	15	1325	P5	\$34,802.00
VEC25-E3	25.2	714	5	20	15	21	1300	P5	\$38,865.00

1) Based on recharging an 80 cubic foot tank from 500 to 3000 psig.
2) Compressor capacity referenced to standard inlet conditions.
E1= Single phase electric, 230 VAC/60 Hz. E3=Three phase electric, 208/230/460 VAC/60 Hz. Other voltages available on request. Dimensions and weight are approximate and are subject to change.

AVAILABLE ACCESSORIES (FACTORY INSTALLED)

- › CO monitoring system
- › SECURUS - Electronic moisture monitoring for the purification system
- › B-Kool (floor mount only)
- › H₂S monitoring system with audible alarm
- › Insulated sound attenuated cabinet

SYSTEM FOOTPRINT

- VTC05 - VTC13:**
DIMENSIONS L X W X H inches (mm)
› 54” x 34” x 56” (1372.6mm x 863.6mm x 1422.4mm)
WEIGHT pounds (kg)
› 800 - 900 lb (363 - 408.2 kg)
- VTC18 - VTC26:**
DIMENSIONS L X W X H inches (mm)
› 54” x 34” x 63” (1372.6mm x 863.6mm x 1600.2mm)
WEIGHT pounds (kg)
› 1200 - 1300 lb (544.3 - 589.7 kg)

OPTIONAL ACCESSORIES - VERTECON

Item	Description	Price
0001	SECURUS	\$875.00
0002	Electronic carbon monoxide monitor complete with calibration kit wired for alarm and shutdown (calibration gas included)	\$3,848.00