DReeM BL 4910

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 03/25/2021 Revision date: 04/15/2021

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Name : DReeM BL 4910

1.2. Recommended use and restrictions on use

Recommended use : Boiler Water Dispersant

1.3. Supplier

Supplier
Kurita America Inc.
6600 94th Ave North
Minneapolis, MN 55445 - USA
T 866-663-7632
kai_sds@kurita-water.com - www.kuritaamerica.com

1.4. Emergency telephone number

Emergency number : CHEMTEL, For Chemical Emergency Call 800-255-3924 24hr/day 7days/week
Kurita America: 866-663-7633 International: +01-813-248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Reproductive toxicity, Category 1B	H360	May damage fertility or the unborn child.

Full text of H- and EUH-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage.
H318 - Causes serious eye damage.
H360 - May damage fertility or the unborn child.

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
sodium hydroxide	(CAS-No.) 1310-73-2	1 – 5	Met. Corr. 1, H290 Skin Corr. 1, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402

Full text of hazard classes, H- and EUH-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	:	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.
Hygiene measures	:	Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	:	Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DReeM BL 4910	
No additional information available	

sodium hydroxide (1310-73-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sodium hydroxide
ACGIH OEL C	2 mg/m³
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Sodium hydroxide
OSHA PEL TWA [1]	2 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	:	Ensure good ventilation of the work station.
Environmental exposure controls	:	Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Clear. Light yellow. Amber.
Odour	:	Mild
Odour threshold	:	No data available
pH	:	~ 9.3 (10% v/v)
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	100 °C (212 °F)
Flash point	:	Nonflammable (T.C.C.)
Relative evaporation rate (butylacetate=1)	:	No data available
Flammability (solid, gas)	:	Not applicable.
Vapour pressure	:	No data available
Relative vapour density at 20 °C	:	No data available
Relative density	:	1.1 (H2O = 1)
Solubility	:	Water: Dispersible.
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosive limits	:	No data available
Explosive properties	:	No data available
Oxidising properties	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified

Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified
Skin corrosion/irritation	:	Causes severe skin burns. pH: ~ 9.3 (10% v/v)
Serious eye damage/irritation	:	Causes serious eye damage. pH: ~ 9.3 (10% v/v)
Respiratory or skin sensitisation	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	May damage fertility or the unborn child.
STOT-single exposure	:	Not classified
STOT-repeated exposure	:	Not classified
Aspiration hazard	:	Not classified
Viscosity, kinematic	:	No data available
Symptoms/effects after skin contact	:	Burns.
Symptoms/effects after eye contact	:	Serious damage to eyes.
Symptoms/effects after ingestion	:	Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	:	Before neutralisation, the product may represent a danger to aquatic organisms.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT)	:	UN1760 Corrosive liquids, n.o.s., 8, PG III
UN-No.(DOT)	:	UN1760
Proper Shipping Name (DOT)	:	Corrosive liquids, n.o.s.
Class (DOT)	:	8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT)	:	PG III - Minor Danger
Hazard labels (DOT)	:	8 - Corrosive

DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203
DOT Packaging Bulk (49 CFR 173.xxx)	:	241
DOT Special Provisions (49 CFR 172.102)	:	IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	60 L
DOT Vessel Stowage Location	:	A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	:	40 - Stow ‘‘clear of living quarters’’
Emergency Response Guide (ERG) Number	:	154
Other information	:	No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

UN-No. (IMDG)	:	1760
Proper Shipping Name (IMDG)	:	CORROSIVE LIQUID, N.O.S.
Class (IMDG)	:	8 - Corrosive substances
Packing group (IMDG)	:	III - substances presenting low danger
Limited quantities (IMDG)	:	5 L

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

sodium hydroxide (1310-73-2)	
CERCLA RQ	1000 lb

15.2. International regulations

CANADA

sodium hydroxide (1310-73-2)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations
No additional information available

National regulations
No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
sodium hydroxide(1310-73-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 04/15/2021

Full text of H-statements:

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H360	May damage fertility or the unborn child.
H402	Harmful to aquatic life

Kurita - SDS US (GHS HazCom 2012)

***Author**: Kurita Water Industries Ltd.*
***Revision Notes**: Updated to GHS format*
***Disclaimer**:*
Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s). The above information is not claiming characteristics of the product in term of legal claims of performance / guarantee. This information only describes safety measures and no liability may arise from the use or application of the product described herein. This information is given in good faith and based on our current knowledge of the product.