YOU CAN RELY ON CERTIFIED®

KUSTOM™ 221

THE NEW GENERATION OF PARTS-WASHING SOLVENTS

SPECIMEN

Read the entire label before using this product.

Si usted no entiende esta etiqueta, pida a alguien que sepa inglés que se la explique completamente antes de usar este producto.

- **NONFLAMMABLE/ NONCOMBUSTIBLE; High Flash Point >205ºF -** Classified as nonflammable by OSHA and DOT
- **HEAVY-DUTY DEGREASER** - Powerful formula dissolves the heaviest grease
- **NO RESIDUE -** Leaves parts sparkling clean
- **QUICKER EVAPORATION -** Allows for quick, efficient cleaning
- **NO CITRUS SMELL**
- **CONTAINS NO BENZENE OR TOLUENE -** OR any other known cancer-causing constituent

NET CONTENTS: _____

CERTIFIED LABORATORIES
A Division of NCH Corporation
P.O. Box 2493, Ft. Worth, Texas 76113-2493
Kendall Park, NJ • Mountain View, CA
www.certifiedlabs.com
©2009 NCH Corporation

KUSTOM 221 was specifically designed as the New Generation of Parts-Washing Solvents.

- KUSTOM 221 will not contribute to your hazardous waste stream*
- Requires NO Form R Reporting under SARA Title III, Section 313
- Contains NO hazardous waste constituents listed under RCRA
- Meets Military Qualified Products Database (QPD) 680; MIL-PRF-680b, Type III

* Providing the spent solution has no hazardous waste characteristics and contains no listed hazardous waste

DIRECTIONS FOR USE

NOTE

1. Do not use on electric motors, electrical boxes, automated electronic process control or monitoring systems, computers, or data-processing equipment.
2. KUSTOM 221 may affect some sensitive plastics and paints. Pre-test in an inconspicuous area before use.

RECIRCULATING PARTS WASHERS: For optimum results, remove all loose grease and grime deposits with air pressure or a brush before placing in the KUSTOM 221. After the parts are sprayed with KUSTOM 221, agitation may be required to remove stubborn deposits.

SOAK TANK CLEANING: Immerse parts in any parts washer or metal tank that has a tight cover to prevent evaporation. (Consult American National Standards Institute [ANSI], Standard Z9, 1-1991, "Exhaust Systems-Open Surface Tanks-Ventilation and Operation.") Dip parts or equipment directly into the KUSTOM 221. Allow to soak clean, then remove and wipe or blow dry. Re-lubricate after cleaning if necessary.

DESIGNED FOR USE WITH PATENTED SSC-1™ ADVANCED CHEMICAL CLARIFIER: Refer to the label directions for specific application rates.

STORAGE RECOMMENDATIONS: For maximum product life, store indoors. Outdoor storage tip: store containers on their side to help prevent water accumulation on a flat end and consequent product contamination.

CAUTION

MAY CAUSE SKIN AND EYE IRRITATION
MAY BE HARMFUL IF INHALED
MAY BE HARMFUL IF SWALLOWED

Contains Petroleum distillates.
Avoid contact with skin, eyes, and clothing. Wear neoprene or nitrile rubber gloves if repeated or prolonged skin contact is likely. Wear safety glasses with side shields if the method of application presents the likelihood of eye contact. Wash thoroughly after handling. Keep the container closed when not in use. Avoid breathing the vapor or mist. Use sufficient ventilation to prevent the buildup of vapor or mist. Do not swallow.

DANGER: Ingestion and subsequent vomiting of this product can lead to aspiration of the product into the lungs, which can cause damage and may be fatal.

CSPA Product Care®

FIRST AID

FOR SKIN CONTACT: Wash affected areas with plenty of soap and water for several minutes. Seek medical attention if irritation develops.

FOR EYE CONTACT: Rinse the eyes with water. Remove any contact lenses and continue flushing with plenty of water for several minutes. Seek medical attention if irritation develops.

IF INHALED: Remove from the area to fresh air. Seek medical attention if respiratory irritation develops or if breathing becomes difficult.

IF SWALLOWED: Give 3 to 4 glasses of water, but DO NOT induce vomiting. If vomiting occurs, give fluids again. Get immediate medical attention. Do not give anything by mouth to an unconscious or convulsing person.

KEEP OUT OF REACH OF CHILDREN

See the Material Safety Data Sheet for more information.

For medical or environmental emergencies, call CHEMTREC® at 1-800-424-9300.

Not for Resale

MADE IN THE U.S.A.
0609CLBA
0M905

QUALITY ISO 9001 ASSURANCE

TO REORDER, Call TOLL-FREE:
1-800-527-9929
FAX: 1-800-456-0121