HEADLINER™ PLUS

High-Speed Thermoplastic Floor Finish

Read the entire label before using this product.
Si usted no entiende esta etiqueta, pida a alguien que sepa inglés que se la explique completamente antes de usar este producto.

BEAUTIFIES WITH A HIGH-GLOSS FINISH

- **Low- or high-speed equipment compatible**
- **Withstands extreme temperatures**
- **Dries quickly**
- **Won't yellow or discolor surfaces**
- **Non-powdering**

Suitable for use as a floor coating in non-prcessing areas of U.S. Federally inspected meat and poultry plants.

NET CONTENTS: _____

DIRECTIONS FOR USE
KEEP FROM FREEZING
KEEP CONTAINER CLOSED WHEN NOT IN USE
NOTE: Do not pour unused floor finish back into the drum.

FLOOR PREPARATION: Thoroughly clean the floor surface first. Use a floor stripper to completely remove old wax or finish that could dull the shine. Allow to dry.

APPLICATION: Use a clean rayon mop to apply a thin, even coat of HEADLINER PLUS. Allow approximately 30 minutes of drying time, depending on atmospheric conditions. For best results, apply two or three thin coats. For optimum results, apply two or three additional thin coats after 24 hours. A single coat of HEADLINER PLUS may be applied to heavy traffic areas when loss of gloss occurs. The new coat blends invisibly with the original coat.

COVERAGE: The first coat will cover approximately 3,000 sq ft per gallon depending upon the porosity of the floor. Subsequent coats will be higher in coverage.

RESTORING TECHNIQUE

SPRAY BUFFING: Three days after initial application, HEADLINER PLUS High-Speed Thermoplastic Floor Finish can be spray buffed using HEADLINER PLUS at a 1 to 1 dilution with water. Spray in front of buffing pad during buffing. (Dry buffing is not recommended.)

MOP AND BUFF METHOD: Damp mop with HEADLINER PLUS at a 1 to 1 dilution with water. For maximum results, buff the floor with a high-speed buffer. When refinishing is necessary, HEADLINER PLUS may be easily removed from the floor with a floor stripper.

KEEP OUT OF REACH OF CHILDREN

See the Safety Data Sheet for more information.
For medical or environmental emergencies, call CHEMTREC® at 1-800-424-9300.

Not for Resale
MADE IN THE U.S.A.
0093MGBA
1M301

multiMIST™

CSPA Product Care®

MULTI-MIST Products
A Division of NCH Corporation
1618 Northgate, Irving, Texas 75062
©2013 NCH Corporation

QUALITY ISO 9001 ASSURANCE

TO REORDER, Call TOLL-FREE:
1-800-527-9919
FAX: 972-438-0634

12042220

SPECIMEN