Safety Data Sheet SURE FLOW II, MM

Supercedes Date 08/20/2013 **Issuing Date** 10/24/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name SURE FLOW II, MM
Recommended use Use in drains
Information on Manufacturer
CERTIFIED LABS, DIV. OF NCH CORP.
BOX 152170
IRVING, TEXAS 75015

Product Code 0269
Chemical nature Aqueous solution Alkaline
Emergency Telephone Number
CHEMTREC® 800-424-9300
Telephone inquiry
972-579-2477

2. HAZARD IDENTIFICATION

Color Blue **Physical state** Liquid **Odor** Odorless

GHS
Classification
Physical Hazards
Substances/mixtures corrosive to metal

Health Hazard

Acute Oral Toxicity	Category 3
Skin Corrosion/Irritation	Category 1
Serious Eye Damage/Eye Irritation	Category 1

Other hazards
None

Labeling
Signal Word
DANGER

Hazard statements
H314 - Causes severe skin burns and eye damage
H301 - Toxic if swallowed
H290 - May be corrosive to metals

Precautionary Statements
P280 - Wear protective gloves, protective clothing, eye protection and face protection.
P260 - Do not breathe mist.
P264 - Wash face, hands and any exposed skin thoroughly after handling
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P332 + P313 - If skin irritation occurs, get medical attention.
P363 - Wash contaminated clothing before reuse
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a physician
P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P342 + P311 - If experiencing respiratory symptoms, call a physician
P301+ P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.
P406 - Store in a corrosion-resistant container.
P390 - Absorb spillage to prevent damage
P501 - Dispose of contents and container in accordance with applicable local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight %
Potassium hydroxide	1310-58-3	10-30

Sodium hydroxide	1310-73-2	7-13

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice Do not get in eyes, on skin or on clothing. Do not breathe mist.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately.

Skin Contact Remove immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately.

Inhalation Move to fresh air. In case of shortness of breath, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

Ingestion Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person. Rinse mouth.

Notes to physician The product causes burns of eyes, skin and mucous membranes. Control of circulatory system, shock therapy if needed.

5. FIRE-FIGHTING MEASURES

Flash Point Does not flash **Method** No data available

Flammability Limits in Air %: Hydrogen, by reaction with metals. **Upper:** 75 **Lower:** 4

Suitable Extinguishing Media

Water spray. Foam. Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Material can create slippery conditions. Contact with metals liberates flammable hydrogen gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, NOHSC (approved or equivalent) and full protective gear.

NFPA	**Health** 3	**Flammability** 1	**Instability** 0
HMIS	**Health** 3	**Flammability** 1	**Instability** 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Ensure adequate ventilation. Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.

Environmental Precautions Do not flush into surface water or sanitary sewer system.

Methods for Containment Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Methods for Cleaning Up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Neutralizing Agent Acetic acid, diluted.

7. HANDLING AND STORAGE

Handling Do not get in eyes, on skin or on clothing. Do not breathe mist.

Storage Store in original container. Metal containers must be lined. Keep containers tightly closed in a dry, cool and well-ventilated place.

Storage Temperature **Minimum** 36 °F / 2 °C **Maximum** 120 °F / 49 °C

Storage Conditions **Indoor** X **Outdoor** **Heated** **Refrigerated**

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Potassium hydroxide	Ceiling: 2 mg/m^3	No data available	Ceiling: 2 mg/m^3
Sodium hydroxide	Ceiling: 2 mg/m^3	TWA: 2 mg/m^3	10 mg/m^3 Ceiling: 2 mg/m^3

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

- **Eye/Face Protection** Tightly fitting safety goggles. Face-shield.
- **Skin Protection** Wear suitable protective clothing, Impervious gloves.
- **Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations Wear protective gloves/clothing. Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	**Viscosity**	Viscous
Color	Blue	**Odor**	Odorless
Odor Threshold	Not applicable	**Appearance**	Hazy
pH	14	**Specific Gravity**	1.31
Evaporation Rate	0.43 (Butyl acetate=1)	**Percent Volatile (Volume)**	80.9
VOC Content (%)	0	**VOC Content (g/L)**	0
Vapor Pressure	11.4 mmHg @ 70°F	**Vapor Density**	0.6 (Air = 1.0)
Solubility	Completely soluble	**n-Octanol/Water Partition**	No data available
Melting Point/Range	No data available	**Decomposition Temperature**	No data available
Boiling Point/Range	230 °F / 110 °C	**Flammability (solid, gas)**	No data available
Flash Point	Does not flash	**Method**	No data available
Autoignition Temperature	No information available.		
Flammability Limits in Air %:	Hydrogen, by reaction with metals	**Upper:** 75 **Lower:** 4	

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	None known.
Incompatible Products	Strong oxidizing agents, Acids, Metals, Aldehydes, Highly halogenated compounds, Leather, Ammonia, Amines, Strong bases.
Decomposition Temperature	No data available
Hazardous Decomposition Products	Carbon oxides, Potassium oxides, Hydrogen, by reaction with metals.
Possibility of Hazardous Reactions	None under normal processing.

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50	No information available
Dermal LD50	No information available
Inhalation LC50	
Gas	No information available
Mist	No information available
Vapor	No information available

Principle Route of Exposure	Skin contact, Eye contact, Inhalation.
Primary Routes of Entry	None known.
Acute Effects:	
Eyes	Corrosive to the eyes and may cause severe damage including blindness.
Skin	Causes skin burns.
Inhalation	Harmful by inhalation. Causes burns.
Ingestion	If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.
Chronic Toxicity	Inhaled corrosive substances can lead to a toxic edema of the lungs.
Target Organ Effects	Respiratory system, Eyes, Skin.
Aggravated Medical Conditions	Skin disorders, Respiratory disorders.

Component Information

Acute Toxicity

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
Potassium hydroxide 1310-58-3	= 284 mg/kg (Rat)	no data available	No data available	No data available	No data available
Sodium hydroxide 1310-73-2	No data available	= 1350 mg/kg (Rabbit)	No data available	No data available	No data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Potassium hydroxide 1310-58-3	No data available	No data available	No data available	No data available	Skin; Eyes; Respiratory system
Sodium hydroxide 1310-73-2	No data available	No data available	No data available	No data available	Skin; Eyes; Respiratory system

Carcinogenicity There are no known carcinogenic chemicals in this product.

12. ECOLOGICAL INFORMATION

Product Information No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	Partition coefficien
Potassium hydroxide	No information available.	No information available.	No information available	No information available.	0.83
Sodium hydroxide	No information available.	LC50 = 45.4 mg/L Oncorhynchus mykiss 96 h	No information available	No information available.	N/A

Persistence and Degradability No information available.
Bioaccumulation No information available.
Mobility No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of in accordance with local regulations.
Container Disposal Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT
Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s.
Hazard Class 8
UN-No UN3266
Packing Group III
Reportable Quantity (RQ) Potassium hydroxide, RQ kg= 2049.30 Sodium hydroxide, RQ kg= 5044.47
Description UN3266, Corrosive liquid, basic, inorganic, n.o.s.(Potassium hydroxide,Sodium hydroxide), 8, PG III , RQ

TDG
Proper shipping name Corrosive liquid, basic, inorganic, n.o.s.
Hazard Class 8
UN-No UN3266
Packing Group III
Description UN3266, Corrosive liquid, basic, inorganic, n.o.s.(Potassium hydroxide,Sodium hydroxide), 8, PG III

ICAO
UN-No UN3266
Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s.
Hazard Class 8
Packing Group III
Shipping Description UN3266, Corrosive liquid, basic, inorganic, n.o.s.(Potassium hydroxide,Sodium hydroxide), 8, PG III

IATA
UN-No UN3266
Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s.
Hazard Class 8
Packing Group III
ERG-Code 8L
Shipping Description UN3266, Corrosive liquid, basic, inorganic, n.o.s.(Potassium hydroxide,Sodium hydroxide), 8, PG III

IMDG/IMO
Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s.
Hazard Class 8
UN-No UN3266
Packing Group III
EmS No. F-A, S-B
Description UN3266, Corrosive liquid, basic, inorganic, n.o.s.(Potassium hydroxide,Sodium hydroxide), 8, PG III

15. REGULATORY INFORMATION

Inventories
TSCA Complies
DSL Complies
U.S. Federal Regulations

SARA 313
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	No	No	No	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Potassium hydroxide	1000 lb	Not applicable
Sodium hydroxide	1000 lb	Not applicable

16. OTHER INFORMATION

Prepared By Adrienne McKee
Supercedes Date 08/20/2013
Issuing Date 10/24/2016
Reason for Revision No information available.
Glossary No information available.
List of References. No information available.

CERTIFIED LABS, DIV. OF NCH CORP.assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.