Husky®

706

BUTYL FREE LOW ODOR UHS FLOOR STRIPPER

This new low odor, specially designed UHS floor finish stripper emulsifies the heavily burnished floor finishes that have lost their captive solvent characteristics. Butyl free to help prevent contact with unwanted solvents and odors, while providing excellent removal and film break down.

Formula Features

- Emulsifies the Toughest Burnished Floor Finishes
- Butyl Free
- Increased Speed of Stripping Action
- Saves Time and Labor
- Low Odor Formula

Applications *Concentrated

(Dilute 12 oz. per gal. of water)

- Perfect for floor finishes that have been maintained with propane or high speed electric/battery burnishers.

Areas Of Utilization

- Schools
- Grocery Stores
- Retail Stores
- Shopping Malls
- Hospitals
- Office Buildings
- Nursing Homes
- Building Service Contractors

Other Liquid/Aerosol Formula Categories

- Restroom Care
- Industrial Care
- Skin Care
- Carpet Care
- Odor Control
- Specialty Products
- Health Care

CANBERRA CORPORATION ▸ 3610 N. Holland-Sylvania Rd. ▸ Toledo, Ohio 43615
(419) 841-6616 ▸ fax: (419) 841-7597 ▸ Visit Our Website: www.canberracorp.com

Husky® 706 BUTYL FREE LOW ODOR UHS FLOOR STRIPPER

DIRECTIONS

1. Always dilute product properly. For regular floor stripping, dilute 1:10 (12 oz. per gallon) with cold water. For heavy duty floor stripping, dilute 1:4 with cold water.

2. Apply liberally to small area of floor. Making sure surface remains wet until removed

3. Allow to remain approximately 10 minutes.

4. Agitate with single disc floor machine and black pad
5. Pick up with mop, vac, or automatic scrubber.
6. Clear water or neutralizer rinse.
7. Allow floor to completely dry.

PRODUCT DATA

	YES	NO
USDA A4 Equivalent	X	
Non-Butyl	X	
Low Odor	X	
Dot Regulated	X	

PERSONAL PROTECTIVE EQUIPMENT

GLOVES

SPLASH GOGGLES

HAZARD RATING
4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant

SECTION I - PRODUCT IDENTIFICATION

See reverse side for product identification.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous components %(Optional)	CAS#'s	OSHA PEL	ACGIH TLV	Other Limits	
Monoethanolamine	141-43-5	3 ppm	3 ppm	N/A	10-15
Potassium Hydroxide	1310-58-3	2mg/m³	2mg/m³	N/A	10-15
Sodium Xylene Sulfonate	1300-72-7	N/A	N/A	N/A	1-5

*This chemical is subject to the reporting requirements for section 313 of title III of the superfund amendments and reauthorization act of 1986 and 40 CFR part 372.

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point: ..... ≈212° F
Vapor Pressure (mm Hg.) .....N/A
pH (conc.).....N/A
Solubility in Water..... Complete
Appearance and Odor .....Clear Liquid/Mild Fragrance
Specific Gravity (H_2O=1) 1.070
Percent Volatile By Weight (%) .....>70%
Evaporation Rate (H_2O=1) .....N/A

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/E **Flammable Limits: LEL:** N/E **UEL: N/E**
Extinguishing Media: Water, CO_2, Foam or media suitable for surrounding fire
Special Fire Fighting Procedures: Standard fire fighting procedures may be followed, including full protective gear, NIOSH approved self-contained breathing apparatus.
Unusual Fire and Explosion Hazards: None Known

SECTION V - PHYSICAL HAZARDS

Stability ☐ Unstable ☒ Stable **Conditions to Avoid:** None Known
Incompatibility (Materials to Avoid): Do not mix with other chemicals.
Hazardous Decomposition Products or By-products: Thermal decomposition or burning may produce toxic vapors or gases.
Hazardous Polymerization ☐ May Occur ☒ Will Not Occur **Conditions to Avoid:** None Known

060512

N/A (Not applicable / Not available)
N/E (Not Established)

SECTION VI - HEALTH HAZARDS

Route(s) of Entry: Inhalation? Skin? **X** Ingestion? **X**
Health Hazards (1. Acute and 2. Chronic) **1. Acute:** Harmful if swallowed. Eye and skin irritant. May cause permanent damage to skin or eyes. **2. Chronic:** None Known
Chemical Listed as Carcinogen or Potential Carcinogen:
National Toxicology Program: ☒ No
I.A.R.C. Monographs: ☒ No
OSHA: ☒ No
Signs and Symptoms of Exposure: Irritation or burning sensation.
Medical Conditions Generally Aggravated by Exposure: May aggravate skin disorders or respiratory ailments. **Emergency and First Aid Procedures: Eye Contact:** Flush immediately with water for 15 minutes. Get medical attention. **Skin Contact:** Flush with water for 15 minutes. Remove and wash contaminated clothing. **Ingestion:** Rinse mouth with water. Then drink 1-2 glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Wear appropriate protective equipment. If possible, contain spill and collect in an approved container. Rinse affected area thoroughly with water. Keep product out of storm sewers or waterways. Hold for disposal.
Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. If possible, triple rinse container and recycle.
Precautions To Be Taken In Handling And Storing: Avoid contact with skin or eyes. Avoid breathing vapor, spray or mist. Store in original container, in cool dry place with adequate ventilation. Keep container tightly closed when not in use.
Other Precautions: Use only according to label directions. If unsure about safe use, contact your supervisor immediately.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): Not expected to be necessary under normal conditions of use. Where exposure cannot be adequately controlled by general or local ventilation, use appropriate respiratory protection to prevent over exposure, An approved dust/mist respirator would be recommended. **Ventilation: Local Exhaust:** As Necessary **Mechanical (General):** Adequate **Special:** N/A **Other:** N/A **Protection Gloves:** Water Impervious (Latex, Neoprene) **Eye Protection:** Chemical Resistant Goggles or Face Shield.
Other Protective Clothing Or Equipment: Not Required. Eye Wash Recommended.
Work/Hygiene Practices: Follow OSHA mandated procedures. Never eat or smoke while working with chemicals. Good housekeeping practices apply. Wash thoroughly after handling.