

Attachment B

Specification: Cab and Chassis Single Rear
Axle, 28,000 GVWR

28,000 GVWR Truck, Cab Forward and Chassis for Hydraulic Guardrail Post Driver/Puller (Re-Using Old Body)

28,000 GVWR truck, single rear axle, cab forward and chassis, for an existing MDOT-owned flat-bed-mounted hydraulic guard rail post driver/puller that is being re-used (to be mounted separately) new and of current model, equipped as advertised by the manufacturer, to meet or exceed the following **MINIMUM** specifications:

Truck Proposed: **Make:** _____ **Model:** _____

Non-Restrictive
Clause:

Any use of brand name or equal within this specification is to be considered a reference for the purpose of describing the standard of quality, performance, and characteristics desired. It is not intended to limit or restrict competition.

SPECIFICATIONS

GVWR: 28,000 lb. (minimum)

GVWR: _____

Comply Yes/No: _____

CA Dimension: 118"

CA dimension: _____

Comply Yes/No: _____

Wheel Base: 139"

Wheelbase: _____

Comply Yes/No: _____

BBC: 80"

BBC dimension: _____

Comply Yes/No: _____

Axle to Frame: 8"

Axle to frame: _____

Comply Yes/No: _____

Engine: 6-liter minimum, 225-horsepower minimum, water-cooled, diesel, minimum torque of 520 lb.-ft., meeting all current federal and EPA requirements

Make: _____ **Model:** _____

HP: _____ **Torque:** _____

Comply Yes/No: _____

Engine Protection: Unit shall have automatic shutdown system to include oil pressure, oil temperature, coolant temperature.

Comply Yes/No: _____

Transmission: Heavy-duty, fully automatic, 6-speed wide ratio with overdrive designed for on-road/off-road operations, geared for highway speeds up to 72 MPH with fully loaded truck; automated manual not acceptable

Make: _____ Model: _____

Type: _____ Speeds: _____

Comply Yes/No: _____

Brakes: Full air, disc, ABS with 4 channel/4 sensor/4 modulator configuration for front and rear axle compatibility, sized to meet all applicable state and federal safety standards for size, weight and application of truck

Brake system specified: _____

Rotor size: _____ Caliper size: _____

No. of caliper pistons: _____ Air tank capacity: _____

Air compressor size (GPM): _____ ABS system: _____

ABS configuration used: _____

Comply Yes/No: _____

Axle Rating and
Suspension:

Front – 10,000 lb. minimum, multi-leaf springs w/shock absorbers, disc brake compatible hubs

Rear – 18,000 lb. minimum, multi-leaf springs, full locking wheel differential (anti-spin device), disc brake compatible hubs

Axle rating:

Front: _____ Rear: _____

Axle description:

Front: _____ Rear: _____

Gear ratio: _____

Comply Yes/No: _____

Cooling System: Heavy-duty, high capacity radiator, silicone hoses

Comply Yes/No: _____

Electrical: 12-volt, 120-amp alternator. Two 12-volt maintenance-free batteries of the same size, 1250 CCA total

Alternator:

a. Manufacturer: _____

b. Amp rating: _____

Battery size and capacity: _____

Comply Yes/No: _____

Fuel System: 100-gallon (minimum) tank capacity (any configuration) dual stage fuel filters

Number of tanks: _____

Capacity per tank: _____

Comply Yes/No: _____

DEF Tank: 7-gallon frame-mounted, minimum

Comply Yes/No: _____

Steering: Power – integral

Comply Yes/No: _____

Driveline: Heavy-duty u-joint

Comply Yes/No: _____

Tires: Front (2) – 12R22.5 HSR2 16PR load range H

Rear (4) -- 11R22.5 HSR2 16PR load range H

Must be rated equal to or higher than axle and suspension weight specifications and rated for top governed speed of 72 MPH

Front:

Brand: _____

Size: _____

Load Rating: _____

Speed Rating: _____

Rear:

Brand: _____

Size: _____

Load Rating: _____

Speed Rating: _____

Comply Yes/No: _____

Wheels: Front: Pilot 22.5 x 9, 10-hole disc, steel, hub piloted

Rear: Pilot 22.5 x 8.25, 10-hole disc, steel, hub piloted

Must be rated equal to or higher than axle and suspension weight specifications and rated for top governed speed of 72 MPH, disc brake compatible

Front:

Brand: _____ Size: _____

Load Rating: _____ Speed Rating: _____

Rear:

Brand: _____ Size: _____

Load Rating: _____ Speed Rating: _____

Comply Yes/No: _____

Back-up Alarm: Smart alarm system which is activated upon backward movement of the vehicle; audible above normal outdoor and construction sounds

Comply Yes/No: _____

Cab and Equipment: Cab Forward-type, steel or aluminum construction, equipped with door pads and back of cab pads for sound deadening and insulation.

All standard equipment including, but not limited to: Five cab-mounted marker lights, Deluxe high-back air suspended driver and passenger seat, high-visibility orange safety belts, factory air conditioning and heater with defroster, outside assist handles both sides (if exhaust is in the way then an inside assist handle will be acceptable for the side affected), 12-volt dash-mounted accessory power outlet, all dash switches including spares shall be functional, direct reading gauges for oil pressure, water temperature and air pressure, tachometer, AM/FM Bluetooth stereo radio with hands-free option, dual air horns, warning lights and buzzers for air pressure, oil pressure and water temperature, RH and LH west coast mirrors, convex auxiliary mirrors (LH & RH), tinted glass all around, four-speed electric windshield wipers and washers with intermittent mode, tilt steering column, front tow hooks, heavy-duty front bumper,

Comply Yes/No: _____

Paint: Manufacturer's standard white

Comply Yes/No: _____

ADDITIONAL REQUIREMENTS

Service: Unit shall be delivered fully assembled ready to operate. Factory-trained dealer representative is to inspect equipment on delivery and provide receiving MDOT equipment manager with information on operational, service, and maintenance requirements.

Acknowledge Yes/No: _____

Warranty: Clearly stated terms and conditions of all manufacturer warranties shall be included with the Statement of Qualifications (SOQ). Any and all materials, specialty equipment, or accessories that prove defective in normal operation within the warranty period shall be replaced or repaired by the manufacturer free of any and all cost to MDOT, including all material, labor, and transportation costs. Warranty replacement and/or repairs shall be furnished promptly by the successful bidder within a time period not to exceed thirty days. **The bidder shall provide written assurance with the SOQ regarding warranty repairs.**

The delivering dealer will have sole warranty responsibility (**all components**) for the first ninety days after acceptance of vehicle.

The manufacturer shall provide, with SOQ, a list of warranty service locations within the State of Mississippi for all components of the vehicle (A/C, body, chassis, electrical, etc.) which may need warranty repair beyond the first ninety days.

Acknowledge Yes/No: _____

Workmanship: Workmanship throughout the vehicle shall conform to the highest standard of commercially accepted practice for the class of work and shall result in a neat and finished appearance. The design of the body and equipment which the manufacturer proposes to furnish must provide a vehicle of substantial and durable construction in all respects.

All parts shall be new. Used, reconditioned, or obsolete parts will not be accepted.

Acknowledge Yes/No: _____

Parts Availability: Dealer name and location within the State of Mississippi (if applicable):

Tests and Testing: The complete vehicle and all working and moving parts and operating devices shall be thoroughly tested and put in operating condition by the manufacturer.

Prior to acceptance of vehicle by MDOT, the manufacturer shall service and adjust vehicle for operation.

Acknowledge Yes/No: _____

Literature: Technical manuals: Operator's manual, service/maintenance manual, and parts book are to be made available in both hard copy and electronic (cd, flash drive, etc.) versions. One set of technical manuals shall be provided with each unit upon delivery. Additional manuals may be ordered at a later date.

Technical service bulletins: Successful bidder shall provide TSBs (technical service bulletins) for all equipment delivered to MDOT as they are published, regardless of the date of delivery. TSBs may be furnished in paper or electronic format, and shall be updated regularly.

The following additional information shall be provided by the vendor at time of delivery (electronically if possible):

Manufacturer's recommended service/preventive maintenance intervals
Recommended fluids, lubricants, and their SAE equivalents

Descriptive literature shall be furnished to substantiate the details specified in SOQ.

Acknowledge Yes/No: _____

Certification: The manufacturer(s) shall furnish certification that this machine meets or surpasses current U.S. Department of Labor Occupational Safety and Health Administration (OSHA) Regulations, U.S. Department of Transportation Federal Motor Vehicle Safety Standards (FMVSS), and any other applicable Federal regulations.

Acknowledge Yes/No: _____

=====

NOTE: Any company manufacturing, up-fitting, and/or selling a finished motor vehicle in the State of Mississippi must be in compliance with the rules and regulations of the Mississippi Motor Vehicle Commission prior to the bid opening. Any licensing will be verified prior to award.

A copy of licenses as required by the Mississippi Motor Vehicle Commission may be supplied with SOQ.

Dealers License Number: _____

Manufacturers License Number (where applicable): _____

Application and contact information may be attained through the internet at
<http://www.mmvc.ms.gov/>

Acknowledge Yes/No: _____

=====

Vehicle Title or Certificate of Origin:

Assignment: **State of Mississippi/DFA – 941**

Mailing address: Mississippi Department of Transportation, 9301
P.O. Box 1850
Jackson, MS 39215

Acknowledge Yes/No: _____

Lienholder: Upon award, if MDOT issues a **Notice to Proceed** instead of a **Purchase Order**, the vehicle is being purchased through the State's Master Lease Purchase Program, and the following shall be shown as the **1st Lienholder on the Title Application**:

U.S. Bank National Association
Attention: Jacqueline McNeil
6810 Crumpler Blvd., Suite 200
Olive Branch, MS 38654

Lienholder Number: 90018867500

Acknowledge Yes/No: _____