

# ARMTEX™ ATTACK

Lightweight All-Polyester Double Jacket Rubber Lined Fire Hose

## ARMTEX™ ATTACK

*High Tensile Strength Polyester Double Jacket & EPDM Rubber-Lined Fire Attack Hose*

**Construction** – Double-jacket polyester hose with a synthetic EPDM rubber ozone resistant lining. ARMTEX™ ATTACK is available in the sizes of 1-1/2", 1-3/4", and 2-1/2". Jacket color options include yellow, orange, red, blue, green and white.

**Service Temperature** – Remains flexible at temperatures as low as -40°F (-40°C).

**Abrasion Resistant Jacket** – Designed with superior abrasion resistance and kink resistance to resist damage from constant working conditions, even when using low pressure and straight bore nozzles. A smooth waterway surface for lower friction loss.

**Ultra-Lightweight** – ATI's lightest weight rubber-lined hose. An 1-3/4" 50'\* coil weighs just 17 lbs.

**Packs Tight** – ATI's best packing and easiest to fold double-jacket, rubber-lined hose.

**Maintenance Free** – Immune to mildew and rot.

10 Year Warranty

Meets and exceeds all NFPA requirements for Fire Hose, current editions.

### Applications –

- Municipal fire departments
- Industrial fire brigades
- Shipboard fire fighting

Series Number	Diameter (in.)	Working Pressure (P.S.I.)	Test Pressure (P.S.I.)	Burst Pressure (P.S.I.)	Standard Length (ft.)	Weight of 50 ft* (LB)	Coil Diameters (per 50 ft*)
42H15	1.5	400	800	1200	50/100	15	16
42H175	1.75	400	800	1200	50/100	17	16
42H25	2.5	400	800	1200	50/100	26	19

\*Weight does not include couplings



### COLOR CODES:



### LINER MATERIAL CODE:

**R** Rubber lined

### PART NUMBERS:

Part Number	Description
42H15RW	1 1/2 x ATTACK WHITE
42H15RO	1 1/2 X ATTACK ORANGE
42H15RB	1 1/2 X ATTACK BLUE
42H15RG	1 1/2 X ATTACK GREEN
42H15RR	1 1/2 X ATTACK RED
42H15RY	1 1/2 X ATTACK YELLOW
42H175RW	1 3/4 x ATTACK WHITE
42H175RY	1 3/4 X ATTACK YELLOW
42H175RR	1 3/4 X ATTACK RED
42H175RO	1 3/4 X ATTACK ORANGE
42H175RB	1 3/4 X ATTACK BLUE
42H175RG	1 3/4 X ATTACK GREEN
42H25RW	2 1/2 x ATTACK WHITE
42H25RY	2 1/2 X ATTACK YELLOW
42H25RO	2 1/2 X ATTACK ORANGE
42H25RR	2 1/2 X ATTACK RED
42H25RB	2 1/2 X ATTACK BLUE
42H25RG	2 1/2 X ATTACK GREEN



ARMORED TEXTILES INCORPORATED

[www.armtexinc.com](http://www.armtexinc.com)

ATIAAFL0318

# ARMTEX™ ATTACK LITE

Lightweight All-Polyester Double Jacket Polyurethane Lined Fire Hose



## COLOR CODES:



## LINER MATERIAL CODE:

**P** Polyurethane lined

## PART NUMBERS:

Part Number	Description
41H15PY	1 1/2 X ATTACK LITE YELLOW
41H15PO	1 1/2 X ATTACK LITE ORANGE
41H15PR	1 1/2 X ATTACK LITE RED
41H15PB	1 1/2 X ATTACK LITE BLUE
41H15PG	1 1/2 X ATTACK LITE GREEN
41H15PW	1 1/2 x ATTACK LITE WHITE
41H175PY	1 3/4 X ATTACK LITE YELLOW
41H175PO	1 3/4 X ATTACK LITE ORANGE
41H175PR	1 3/4 X ATTACK LITE RED
41H175PB	1 3/4 X ATTACK LITE BLUE
41H175PG	1 3/4 X ATTACK LITE GREEN
41H175PW	1 3/4 x ATTACK LITE WHITE
41H25PY	2 1/2 X ATTACK LITE YELLOW
41H25PO	2 1/2 X ATTACK LITE ORANGE
41H25PR	2 1/2 X ATTACK LITE RED
41H25PB	2 1/2 X ATTACK LITE BLUE
41H25PG	2 1/2 X ATTACK LITE GREEN
41H25PW	2 1/2 x ATTACK LITE WHITE

## ARMTEX™ ATTACK LITE

*High Tensile Strength Polyester Double Jacket & Polyurethane-Lined Fire Attack Hose*

**Construction** – Double-jacket polyester hose with a polyurethane lining. ARMTEX™ ATTACK LITE is available in the sizes of 1-1/2", 1-3/4", and 2-1/2". Jacket color options include yellow, orange, red, blue, green and white.

**Service Temperature** – Remains flexible at temperatures as low as -40°F (-40°C).

**Ultra-Lightweight** – ATI's lightest weight polyurethane-lined hose. An 1-3/4" 50'\* coil weighs 16 lbs.

**Packs Tight** – ATI's best packing and easiest to fold double-jacket hose.

**Maintenance Free** – Immune to mildew and rot.

10 Year Warranty

Meets and exceeds all NFPA requirements for Fire Hose, current editions.

## Applications –

- Municipal fire departments
- Industrial fire brigades
- High rise packs

Series Number	Diameter (in.)	Working Pressure (P.S.I.)	Test Pressure (P.S.I.)	Burst Pressure (P.S.I.)	Standard Length (ft.)	Weight of 50 ft* (LB)	Coil Diameters (per 50 ft*)
41H15	1.5	400	800	1200	50/100	14	15.5
41H175	1.75	400	800	1200	50/100	16	15.5
41H25	2.5	400	800	1200	50/100	23	18

\*Weight does not include couplings

ATIAAFL0318

[www.armtexinc.com](http://www.armtexinc.com)

ARMORED TEXTILES INCORPORATED

