

ARMTEX HP

NEW! ATI'S HIGHEST PRESSURE HOSE!



RESISTS BURN-THROUGH FOR A FULL MINUTE*

PERFECT FIT OF OUTER JACKET AND INNER TUBE

CONTINUOUS NYLON FILAMENT JACKET

OVERSIZED INNER JACKET FOR INCREASED WATER FLOW

LOWER FRICTION LOSS THAN OTHER DOUBLE JACKET HOSES

EXCEPTIONAL HEAT AND CUT RESISTANCE

OUTSTANDING KINK RESISTANCE

IDEAL FOR LOW PRESSURE COMBINATION STRAIGHT STREAM/FOG NOZZLES

TEN YEAR WARRANTY



ARMORED TEXTILES INCORPORATED
ARMTEXINC.COM

tipsa  **A KURIYAMA GROUP COMPANY**

ARMTEX HP IS ARMORED TEXTILES' MOST RUGGED FIRE HOSE FOR AGGRESSIVE INTERIOR STRUCTURAL FIREFIGHTING.



- ARMTEX HP IS COMPOSED OF AN OUTER JACKET WOVEN FROM 100% HIGH TENACITY SYNTHETIC YARN AND AN INNER LINER CONSISTING OF A ONE-PIECE EXTRUDED THROUGH THE WEAVE NBR RUBBER TUBE. THIS ALLOWS REDUCED FRICTION LOSS AND AMAZING KINK RESISTANCE.
- ARMTEX HP IS AVAILABLE AS 1 3/4" ATTACK LINE AND 2 1/2" MASTER FLOW LINE.
- ARMTEX HP BOASTS OUTSTANDING BURN-THROUGH RESISTANCE, BEING CAPABLE OF WITHSTANDING A SURFACE TEMPERATURE IN EXCESS OF 1100°F FOR A MINIMUM OF ONE MINUTE*, AT A STATIC PRESSURE OF 100 P.S.I., WITHOUT DAMAGE OR RUPTURE TO THE SYNTHETIC REINFORCEMENT.

- ARMTEX HP WILL NOT BURST CATASTROPHICALLY EVEN WITH A PUNCTURE THROUGH BOTH THE OUTER JACKET AND LINER.
- ARMTEX HP IS COLD RESISTANT TO -40°F.
- ARMTEX HP 1 3/4" IS AVAILABLE IN FLORESCENT YELLOW, ARMY GREEN, FIRE ENGINE RED, AND BLUE DEVIL BLUE. ARMTEX HP 2 1/2" IS AVAILABLE IN FLORESCENT YELLOW.
- STANDARD LENGTHS OF 50' AND 100'.
- NFPA 1961 COMPLIANT
- 10 YEAR WARRANTY



ARMTEX HP SPECIFICATIONS

DIAMETER (INCHES)	WORKING PRESSURE (P.S.I.)	TEST PRESSURE (P.S.I.)	BURST PRESSURE (P.S.I.)	WEIGHT LB/FT*	THICKNESS (INCH)
1.75	500	1000	1500	0.37	0.138
2.5	400	800	1200	0.55	0.146

*As per BS 6391, heat resistance test.



ARMORED TEXTILES INCORPORATED
ARMTEXINC.COM