



BARE BONES®

No-Rinse / No Scrub Liquifying Stripper

DESCRIPTION

A 55% active speed stripper that easily cuts through multi-layers of burnished floor finish. This "true" no-rinse stripper does not contain potassium hydroxide or sodium hydroxide yet is the fastest working liquifier on the market. Low foaming, no scrub and no rinse features make this product a must for all professional floor care systems.

PRODUCT FEATURES / BENEFITS

- Low foaming / Can be used through automatic scrubbers
- Contains no potassium or sodium hydroxide / Safe for personnel & flooring
- Requires no rinsing / Saves time by eliminating neutralizing and rinsing
- No scrubbing machine needed / Reduces equipment costs & can be used in hard to get to places
- 55% Active / High use dilution for greater economy

DIRECTIONS FOR USE

For the rapid removal of all floor finishes and waxes from resilient flooring including: vinyl, vinyl asbestos, vinyl composition, asphalt, linoleum, and rubber tiles. Also ideal for finished non-resilients such as: terrazzo, marble, ceramic, quarry tile, ceramic, quarry tile, concrete, and poured epoxy flooring. Although excellent for any type of equipment, greatest savings are realized when using automatic scrubbing equipment.

Dilute **BARE BONES®** following dilution recommendations below. Dilute using cold or mildly warm water only.

Light/Normal Buildup: 8 oz per gallon of water (1:16)

Heavy Buildup (Burnished): 21 oz per gallon of water (1:5)

Mop/Wet Vacuum Stripping System: Apply liberally with a mop to an area small enough so as not to allow the product to

dry and allow to stand for 3 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete stripping is not accomplished repeat the above procedure before re-application of recommended NCL Floor Finish.

Floor Machine Stripping System: Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

Note: As some asphalt tiles may be damaged by prolonged soaking in concentrated strippers, a spot test is recommended before general use.

SPECIFICATIONS

Color	Clear
Odor	Sassafras
pH	11.8 ± 0.3
Flash Point	None to Boiling
Upper Cloud Point	> 130°F
Lower Cloud Point	< 33°F
Viscosity (cps)	< 5

Water Solubility	Complete
Finish Removal.....	Excellent
Damage to Resilient Tiles	Minimal
Density (lbs/gal)	8.1 ± 0.1
Specific Gravity (g/cc).....	0.97 ± 0.01
Free Rinsing	Yes
Low Foaming.....	Yes
Shelf Life.....	1 year minimum in original unopened container

SAFETY INFORMATION

Danger: HARMFUL IF SWALLOWED. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. **KEEP OUT OF THE REACH OF CHILDREN**



Precautionary statement:

Prevention:

Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response:

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and

keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.

Storage:

Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional safety measures: Read the entire label and SDS before using this product, and for additional first aid measures. SDS for this product is available on the web at www.nclonline.com FOR COMMERCIAL AND INDUSTRIAL USE ONLY.



Stripper



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com

SAFETY DATA SHEET

Section 1 - Identification

Product Identifier	BARE BONES [®] No-Rinse/No-Scrub Liquifying Stripper
Other means of identification	1058
Recommended use	Floor finish remover.
Recommended restrictions	For commercial and industrial use only.
Manufacturer / Importer / Supplier / Distributor Information	
Company Name	National Chemical Laboratories of PA, Inc.
Address	401 N. 10th Street - Philadelphia, PA 19123
Telephone	1 (215) 922-1200
Supplier Email	info@nclonline.com
Contact	CHEM-TEL
Emergency Phone	1 (800) 255-3924

Section 2 - Hazard(s) Identification

SDS Hazards and Warnings are based on the undiluted product. Refer to diluted SDS for Ready-To-Use Hazards and Warnings.

	Classification	Category	
Physical Hazards	Not Classified		
Health Hazards	Acute toxicity, dermal	4	
	Acute toxicity, inhalation	4	
	Acute toxicity, oral	4	
	Serious eye damage/eye irritation	1	
	Skin corrosion/irritation	1	
	Specific target organ toxicity, single exposure	3	TARGET ORGAN: respiratory tract irritation
OSHA defined hazards	Not Classified.		
Label Elements			
Hazard Symbol			
Signal Word	Danger		
Hazard Statement	Causes severe skin burns and eye damage. Harmful if swallowed, in contact with skin or if inhaled. May cause respiratory irritation.		
Precautionary statement			
Prevention	Do not breathe the mist or vapor. Use only in well-ventilated areas. Wear protective gloves/clothing and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Keep out of reach of children.		
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
Storage	Store locked up. Store in a well-ventilated place. Keep cool.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) not otherwise classified (HNOC)	Not classified.		

Section 3 - Composition/Information on ingredients

Mixture			
Hazardous Components	Ingredient Name	CAS #	%
	2-Amino Ethanol	141-43-5	5 - 10
	2-Butoxyethanol	111-76-2	25 - 45

Section 4 - First-aid Measures

Inhalation	Move to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way
-------------------	---

SAFETY DATA SHEET

Skin contact	valve or other proper respiratory medical device. Get medical attention immediately. Remove contaminated clothing and shoes. Immediately flush skin with plenty of water. Get prompt medical attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Check and remove contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. DO NOT induce vomiting. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than the hips to help prevent aspiration. Call a physician or poison control center immediately.
Most Important symptoms /effects, acute and delayed	Causes skin and eye burns. May cause respiratory tract irritation. Symptoms may be delayed.
Indication of immediate medical attention and special treatment	Treat symptomatically.
General Information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Immediate medical attention is required. In case of shortness of breath, give oxygen. Keep victim warm.

Section 5 - Fire-fighting measures

Suitable extinguishing media	Carbon dioxide, alcohol-resistant foam, dry chemical, water spray, or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	None known.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment /instructions	Move containers from fire area if you can do it without risk. Use water spray to keep fire-exposed containers cool.

Section 6 - Accidental release measures

Personal precautions, protective equipment and emergency procedures.	Isolate area. Keep unnecessary personnel away. Use personal protection as recommended in Section 8 of the SDS.
Methods and materials for containment and cleaning up	Contain spill. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Flush area with water.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

Section 7 - Handling and storage

Precautions for safe handling	Do not get in eyes, on skin, or on clothing. Do not breathe mist or vapor. Keep container closed. Wash thoroughly after handling. Use Personal Protective Equipment recommended in section 8 of the SDS.
Conditions for safe storage, including any incompatibilities	Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials. Keep container closed. Keep out of reach of children.

Section 8 - Exposure control/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Amino Ethanol (CAS 141-43-5)	TWA	6 mg/m ³ , 3 ppm
2-Butoxyethanol (CAS 111-76-2)	TWA	240 mg/m ³ , 50 ppm

US. ACGIH Threshold Limit Values

Component	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
2-Amino Ethanol (CAS 141-43-5)	STEL	6 ppm
2-Amino Ethanol (CAS 141-43-5)	TWA	3 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2-Amino Ethanol (CAS 141-43-5)	STEL	15 mg/m ³ , 6 ppm
2-Amino Ethanol (CAS 141-43-5)	TWA	8 mg/m ³ , 3 ppm
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m ³ , 5 ppm

US. ACGIH. BEIs. Biological Exposure Indices

Components	Value	Determinate	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines Use personal protective equipment as required. Keep working clothes separately.

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components	Exposure
------------	----------

SAFETY DATA SHEET

2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.Minnesota Hazardous Substances List (Minn. Rules 5206.0400).

Components Exposure
2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

US.NIOSH: Pocket Guide to Chemical Hazards

Component Exposure
2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.100)

Components Exposure
2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.OSHA Table Z-1-A (29 CFR 1910.100)

Components Exposure
2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.Rhode Island Hazardous Substances Right-to-Know Act (R.I. Gen. Laws Section 28-21-1 et. seq.)

Components Exposure
2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.Tennessee. OELs Occupational Exposure Limkits, Table Z1A

Components Exposure
2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

Appropriate engineering controls Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved chemical safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin protection

Hand protection Wear chemical-resistant, impervious gloves. Suitable gloves can be recommended by the glove supplier.

Other Not available.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

Section 9 - Physical and chemical properties

Appearance	Clear.
Physical state	Liquid.
Form	Liquid.
Color	Pale Straw.
Odor	Sassafras.
Odor threshold	Not available.
pH	11.7
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C)
Flash point	>201°F (94°C) TCC
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Similar to water.
Vapor density	Similar to water.
Relative density	0.97 ± 0.01
Relative density temperature	75 °F (23.89 °C)
Solubilities	100 % Soluble.
Partition Coefficient n-octanol/water	Not available

SAFETY DATA SHEET

Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Viscosity	< 10 cP
Viscosity Temperature	75 °F (23.89 °C)

Section 10 - Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to Avoid	Keep away from heat and direct sunlight. Contact with incompatible materials.
Incompatible materials	Oxidizing agents.
Hazardous Decomposition Products	Carbon monoxide. Carbon dioxide. Nitrogen oxides.

Section 11 - Toxicological information

Information on likely routes of exposure

Ingestion	May cause burns of the gastrointestinal tract if swallowed.
Inhalation	Irritating to respiratory system. May cause burns in mucous membranes, throat, esophagus and stomach.
Skin contact	Causes skin burns.
Eye contact	Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics
Causes skin and eye burns. May cause respiratory tract irritation. Symptoms may be delayed.

Information on toxicological effects.

Acute toxicity Harmful if inhaled, absorbed through skin, or swallowed.

Components	Level	Type	Code	Species	Results
2-Butoxyethanol (CAS 111-76-2)	Acute	Dermal	LD50	Rabbit	400 mg/kg
	Acute	Inhalation	LC50	Rat	450 mg/l, 4 hrs
	Acute	Oral	LD50	Rat	560 mg/kg
2-Amino Ethanol (CAS 141-43-5)	Acute	Dermal	LD50	Rabbit	1025 mg/kg
	Acute	Oral	LD50	Rat	1715 mg/kg

Skin corrosion/irritation	Causes skin burns.
Serious eye damage/ eye irritation	Causes serious eye damage.
Respiratory sensitization	Not classified.
Skin sensitization	Not classified.
Germ cell mutagenicity	Not classified.

IARC Monographs. Overall Evaluation of Carcinogenicity

Component	Result	Comment
2-Butoxyethanol (CAS 111-76-2)	3	Not classifiable as to carcinogenicity to humans.

Reproductive toxicity	Not classified.
Specific target organ toxicity - single exposure	Irritating to respiratory system.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not classified.
Chronic effects	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Section 12 - Ecological Information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	The product is expected to be biodegradable.
Bioaccumulative potential	Not known.
Partition coefficient n-octanol / water log (Kow)	
Components	Results
2-Butoxyethanol (CAS 111-76-2)	0.83
2-Amino Ethanol (CAS 141-43-5)	-1.31
Mobility in soil	Not available.
Mobility in general	The product is water soluble and may spread in water systems.
Other adverse effects	None known.

SAFETY DATA SHEET

Section 13 - Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	Waste codes should be assigned by the user based on the application for which the product was used.
Waste from residues / unused products	Dispose in accordance with all applicable regulations.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Section 14 - Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transportation in bulk according to Annex II of MARPOL 73/78 and IBC Code	This substance/mixture is not intended to be transported in bulk.

Section 15 - Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR707, Subpt. D)	Not regulated.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not on regulatory list.
CERCLA Hazardous Substance List (40 CFR 302.4)	

Components	Result
2-Butoxyethanol (CAS 111-76-2)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories	Immediate Hazard	Yes
	Delayed Hazard	No
	Fire Hazard	No
	Pressure Hazard	No
	Reactivity Hazard	No

SARA 302 Extremely hazardous substance	No
SARA 311/312 Hazardous chemical	Yes

SARA 313 (TRI reporting)

Chemical name	CAS #	% by wt.
2-Butoxyethanol	111-76-2	25 - 45

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HSPs) List	Not regulated.
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)	Not regulated.
Safe Drinking Water Act (SDWA)	Not regulated.
Food and Drug Administration (FDA)	Not regulated.

US state regulations

US.Massachusetts RTK - Substance List	Components 2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)
US.New Jersey Worker and Community Right-to-Know Act	Components 2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)
US.Pennsylvania RTK - Hazardous Substances	Components 2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)
US.Rhode Island RTK	Components 2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)
US - California Proposition 65	California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory Name	On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

SAFETY DATA SHEET

Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
Unites States Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

*A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 - Other information, including date of preparation or last version

Issue date 1/18/2015

Version # 01

Disclaimer The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS. Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this SDS. The user should review these regulations to ensure full compliance.

A true caustic free, no rinse stripper that penetrates and solubilizes floor finish with unbeatable speed!

Directions:

Dilute BARE BONES® following dilution recommendations below. Dilute using cold or mildly warm water only.

Light/Normal Buildup:8 oz per gallon of water (1:16)

Heavy Buildup (Burnished):20 oz per gallon of water (1:5)

Mop/Wet Vacuum Stripping System: Apply liberally with a mop to an area small enough so as not to allow the product to dry and allow to stand for 3 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete stripping is not accomplished repeat the above procedure before re-application of recommended NCL Floor Finish.

Floor Machine Stripping System: Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

Note: Asphalt tile, Linoleum, and other sensitive floor surfaces may be damaged by contact with stripping solution. We recommend that a spot test be conducted before general use.

Instrucciones para Uso:

Diluir BARE BONES® siguientes recomendaciones de dilución a continuación. Diluir con agua fría o ligeramente tibia solamente.

Leve/Medio Acumulación8 oz por galón de agua (1:16)

Pesado Acumulación:20 oz por galón de agua (1:5)

Sistema Que pela De Vacío De Mop/Wet: Aplíquese liberalmente con un aljofifar a un área bastante pequeña para no permitir que el producto se seque y permita para estar parado por 3 a 5 minutos. Agite con un aljofifar y quite la solución y el viejo final con un vacío mojado. Permita que el piso se seque a fondo y que aplique nuevo final según lo dirigido por el fabricante. Si es completo el pelar no es repetición lograda el procedimiento antedicho antes de que re-uso del final recomendado del piso de NCL.

Sistema Que pela De la Máquina Del Piso: Permita para estar parado por 3 a 5 minutos, friegue con una máquina rotatoria del piso o un depurador automático equipado de los cojines que pelan. Quite la solución y el viejo final con un vacío mojado y permita que el piso se seque totalmente. Si está deseado, un paso que aclara puede ser agregado. Aplíquese recomendó final del piso de NCL según instrucciones.

Nota: Las baldosas de asfalto, el linóleo y otras superficies sensibles del piso pueden resultar dañadas por contacto con la solución de decapado. Recomendamos que se realice una prueba puntual antes del uso general.

NCL®

World Class Cleaning Solutions®



DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

See side panel for additional precautionary statements.

PELIGRO: CAUSAS DE LA PIEL Y QUEMADURAS GRAVES DAÑOS A LOS OJOS.


Ver panel lateral para las medidas preventivas adicionales.

NET CONTENTS: 1 GALLON / 3.79 LITERS

National Chemical Laboratories, Inc.

Philadelphia, PA 19123 USA • www.nclonline.com

Product No.: 1058



Strippers



DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF SWALLOWED, IN CONTACT WITH SKIN OR

IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF REACH OF CHILDREN.

Precautionary statement

Prevention: Do not breathe mist or vapor. Use only in well-ventilated areas. Wear protective gloves/clothing and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first aid measures. SDS for this product is available on the web at www.nclonline.com

PELIGRO: CAUSAS DE LA PIEL Y QUEMADURAS GRAVES DAÑOS A LOS OJOS. NOCIVO EN CASO DE INGESTIÓN, CONTACTO CON LA PIEL O SI SE INHALA. PUEDE CAUSAR IRRITACIÓN RESPIRATORIA. MANTENER FUERA DEL ALCANCE DE LOS NIÑOS.

Palabra de advertencia

Prevención: No respirar vapores o niebla. Utilizar solamente en áreas bien ventiladas. Uso de guantes de protección y ropa y protección para los ojos/la cara. No comer, beber o fumar cuando se utiliza este producto. Lávese cuidadosamente después de la manipulación.

Respuesta: En caso de ingestión: Enjuagar la boca. NO provocar el vómito. En caso de contacto con la piel (o el pelo): Quitarse inmediatamente toda la ropa contaminada. Enjuagar la piel con agua o tomar un baño. Lave la ropa contaminada antes de volver a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar inmediatamente a un centro de toxicología o a un médico. En caso de contacto con los ojos: Enjuague cuidadosamente con agua durante varios minutos. Quitese los lentes de contacto, si los usa y si puede hacerse con facilidad. Continúe enjuagando.

Almacenamiento: Guardar bajo llave. Almacenar en lugar bien ventilado. Mantener fresco.

Eliminación: Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales / internacionales pertinentes.

Este producto es calificado como "químicamente peligroso" según el Estándar de Comunicación de Riesgos de la OSHA Hazard Communication Standard, 29 CFR 1910.1200. Todos los componentes están en la Lista de inventario de la EPA TSCA.

Medidas additional de primeros auxilios:

Lea toda la etiqueta y SDS antes de usar este producto, así como medidas adicionales de primeros auxilios. SDS para el artículo está disponible en la web en www.nclonline.com

CONTAINS: 2-Amino Ethanol CAS# 141-43-5, 2-Butoxy Ethanol CAS# 111-76-2

NCL®

World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123
1-800-MAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail: info@nclonline.com

★★ MADE IN USA ★★

LG-0001-1058-04 ©

FOR COMMERCIAL AND INDUSTRIAL USE ONLY
QUESTIONS?
Call (800) 628-2436



To learn more about this product, scan this QR code to visit our website.

