



## PRODUCT DATA SHEET

### RLT 4222 - STEAM AND CONDENSATE TREATMENT

#### GENERAL DESCRIPTION:

RLT 4222 is a blend of volatile neutralizing amines used for control of corrosion in steam and condensate systems. RLT 4222 helps control corrosion by neutralizing carbonic acid formed in steam/condensate systems. RLT 4222 is authorized by the United States Department of Agriculture for use in federally inspected facilities.

#### PRODUCT CHARACTERISTICS:

Form.....Clear Liquid  
pH.....Approximately 11.5  
Density.....8.35 lbs./gallon

#### FEEDING:

RLT 4222 should be fed on a continuous basis directly to the boiler, steam line or the feedwater line. RLT 4222 may be mixed with other boiler water treatments and there are no restrictions as to materials of construction for feed equipment.

#### PRECAUTIONS AND HANDLING:

Product contains volatile amines. Avoid contact with skin and eyes. Do not take internally. Protective gloves and chemical splash goggles are recommended. Wear impervious apron and boots to minimize potential contact. Localized ventilation is suggested. A NIOSH approved organic vapor respirator should be used for exposures above OSHA permissible TLV(S). Consult material safety data sheet for more information.

#### PACKAGING:

55 GALLON DRUMS  
30 GALLON DRUMS  
5 GALLON PAILS