



CHEETAH

48" & 52" models

**Fast. Maneuverable.
Comfortable.**

Specifications

Engine Options:

- 22hp Kawasaki FX, air-cooled, V-Twin, vertical shaft
- 23hp Kohler Command, air-cooled, V-Twin, Electronic Fuel Injection (EFI)
- 23hp Kawasaki FX, air-cooled, V-Twin, vertical shaft
- 25hp Kohler Command, air-cooled, V-Twin, Electronic Fuel Injection (EFI)

Fuel Capacity/Design:

10 gallons, dual fuel tanks. Extra-large fuel neck for easy filling.

Travel Control:

Twin lever steering controls with gas dampers for smooth, precise maneuverability. Adjustable damper positions.

Ground Speed:

10.5 mph forward, 5 mph reverse

Main Frame Construction:

Single tube, steel frame, full-length, fully-welded

Drive Tires:

23 x 9.5 - 12, 4 ply

Caster Tires:

13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic

Caster Wheel Bearings:

Tapered roller bearings

Front Caster Arm Design:

Bolt-on for easy replacement if necessary

Drive System:

Dual Hydro-Gear ZT-3400 integrated transaxles (2 separate units) with charge pumps spin-on oil filters and cooling fans

Hydraulic Oil Filter:

25 micron spin-on filter

Electrical System:

12 Volt battery, "maintenance-free" battery, accessory charging outlet and Solenoid shift starter.

WWW.SCAG.COM



(Continued)

SCAG
POWER EQUIPMENT

Belts:	Kevlar cord. Self-adjusting, spring-loaded, self-tightening
Drive/Load Pulleys:	Split-steel design -- stronger and lighter weight than cast-iron
Instrument Panel :	Tiger Eye Advanced Monitoring System, key switch, throttle, manual choke, PTO switch, digital hour meter

Tiger Eye Advanced Monitoring System:

Depending on engine selection following systems are monitored: hour meter, volt meter, air filter condition, control lever circuit, PTO circuit, parking brake circuit, seat switch circuit and safety interlock module.

Operator Suspension System:	<ul style="list-style-type: none"> Isolates the entire operator station from the effects of rough terrain. <u>Coil-over shock</u> provides effective suspension action right where it's needed, and only where it's needed for a smooth ride. <u>Thick-cushioned, bolstered seat</u>, fully adjustable, with adjustable, folding arm rests. <u>3-Position adjustable deck lift foot pedal</u> allows for easy deck lift for all operators
PTO - Electric Clutch:	<ul style="list-style-type: none"> Ogura GT3.5 - 250 ft lb; adjustable air-gap
Cutter Decks:	48" & 52" Velocity Plus decks. Floating, adjustable, anti-scalping design.
Cutter Deck Construction:	Tri-Plate, welded: 10-gauge top, 7 gauge skirts, 10 gauge & 11 gauge reinforcement plates.
Cutter Deck Drive:	Belt-driven -- straight alignment for increased reliability & longevity
Number of Anti-Scalp Wheels:	<ul style="list-style-type: none"> 48": 3 wheels in 3 positions, 1 rear anti-scalp roller 52": 3 wheels in 3 positions, 1 rear anti-scalp roller
Cutter Deck Spindles:	Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
Cutter Deck Height Adjustment:	Foot pedal lift (3-position adjustable) with self-locking mechanism at transport position
Cutting Range:	1" to 5.5" in .25" increments
Number of Cutter Blades:	3 Marbain blades
Total Length:	81.75"
Total Width (with discharge chute in mowing position):	<ul style="list-style-type: none"> 48" models: 61.25" 52" models: 65.25"
Total Width (with discharge chute in transport position):	<ul style="list-style-type: none"> 48" models: 49.75" 52" models: 53.75"
Height (with ROPS):	67"
Height (with ROPS folded):	48"
Weight (with ROPS):	<ul style="list-style-type: none"> 48" models: 1075 lbs. 52" models: 1080 lbs.
Warranty:	<ul style="list-style-type: none"> 2 Yr. Commercial Mower Warranty—Parts & labor. 3 Yr. / 500 Hour Non-Commercial Mower Warranty—Parts & labor. 3 Yr. Deck Warranty—First & second years parts & labor; third year parts. 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts. 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice. Actual ground speeds may vary.
September 2017

