



CHEETAH

61" & 72" models

The Fastest Cat on Earth.

Specifications

Engine Options:

- 27hp Kawasaki FX, air-cooled, V-Twin, vertical shaft
- 29hp Kohler Command EFI, air-cooled, V-Twin, vertical shaft
- 31hp Kohler Command EFI, air-cooled, V-Twin, vertical shaft
- 31hp Kawasaki FX, air-cooled, V-Twin, vertical shaft
- 35hp Kohler Command EFI, air-cooled, V-Twin, vertical shaft

Fuel Capacity/Design:

15 gallons, dual fuel tanks mounted low on the mower to lower the center-of-gravity and improve hillside stability and traction.

Travel Control:

Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes. Adjustable damper positions.

Ground Speed:

- 16mph forward, 8 mph reverse in high-range
- 12mph forward, 5 mph reverse in low-range

Main Frame Construction:

Double tube, steel frame, full-length, fully-welded

Drive Tires:

24 x 12 - 12, 4 ply

Caster Tires:

13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic

Caster Wheel Bearings:

Tapered roller bearings

Front Caster Arm Design:

Bolt-on for easy replacement if necessary

Drive System:

Dual Hydro-Gear ZT-5400, 2-speed, integrated transaxles (2 separate units); 16cc displacement pump; 21cc displacement wheel motor; 9" cooling fan on each unit

Hydraulic Oil Cooling:

Yes - 9" fan on each unit

Hydraulic Oil Filter:

25 micron spin-on filter

Electrical System:

12 Volt battery, "maintenance-free" battery, accessory charging outlet and Solenoid shift starter.

WWW.SCAG.COM



(Continued)

SCAG
POWER EQUIPMENT

Belts:	Kevlar cord. Self-adjusting, spring-loaded, self-tightening
Drive/Load Pulleys:	Split-steel design -- stronger and lighter weight than cast-iron
Instrument Panel :	Tiger Eye Advanced Monitoring System, key switch, throttle, manual choke (non-EFI models), PTO switch

Tiger Eye Advanced Monitoring System:

Depending on engine selection following systems are monitored: hour meter, volt meter, air filter condition, control lever circuit, PTO circuit, parking brake circuit, seat switch circuit and safety interlock module.

Operator Suspension System:	<ul style="list-style-type: none"> Isolates the entire operator station from the effects of rough terrain. <u>Coil-over shock</u> provides effective suspension action right where it's needed, and only where it's needed, for a smooth ride. <u>High-back seat</u>, fully adjustable, with adjustable, folding arm rests. <u>"Quick-Fit" steering control levers</u> feature incredible range of adjustment for optimal comfort and control <u>3-Position adjustable deck lift foot pedal</u> allows for easy deck lift for all operators
PTO - Electric Clutch:	<ul style="list-style-type: none"> Ogura GT3.5 - 250 ft lb; adjustable air-gap (61" models) Ogura GT5 - 350 ft lb; adjustable air-gap (31FX, 35CV-EFI & All 72" models)
Cutter Decks:	61" & 72" Velocity Plus side-discharge decks; 61" rear-discharge (RD) deck. Floating, adjustable, anti-scalping design.
Cutter Deck Construction:	Tri-Plate, welded: 10 gauge top, 7 gauge skirts, 7 gauge & 11 gauge reinforcement plates.
Cutter Deck Drive:	Belt-driven -- straight alignment for increased reliability & longevity
Number of Anti-Scalp Wheels:	<ul style="list-style-type: none"> 61" side-discharge: 7 wheels in 5 positions, 2 rear anti-scalp rollers 61" rear-discharge: 5 wheels in 3 positions 72" side-discharge: 7 wheels in 5 positions, 2 rear anti-scalp rollers
Cutter Deck Spindles:	Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
Cutter Deck Height Adjustment:	Foot pedal lift (3-position adjustable) with self-locking mechanism at transport position
Cutting Range:	1.25" to 5" in .25" increments
Number of Cutter Blades:	3 Marbain blades
Total Length:	<ul style="list-style-type: none"> 61" models: 85.5" 72" models: 91"
Total Width (with discharge chute in mowing position):	<ul style="list-style-type: none"> 61" models: 73.5" 61" RD models: 63.5" 72" models: 83"
Total Width (with discharge chute in transport position):	<ul style="list-style-type: none"> 61" models: 62.75" 72" models: 73"
Height (with ROPS):	67"
Height (with ROPS folded):	49.5"
Weight (with ROPS):	<ul style="list-style-type: none"> 61" models: 1350-1365 lbs. 72" models: 1385-1400 lbs.
Warranty:	<ul style="list-style-type: none"> 2 Yr. Commercial Mower Warranty—Parts & labor. 3 Yr. / 500 Hour Non-Commercial Mower Warranty—Parts & labor. 3 Yr. Deck Warranty—First & second years parts & labor; third year parts. 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts. 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice. Actual ground speeds may vary.
September 2017

