



**SERIES**  
REMOTE-OPERATED  
ROBOTIC MOWER

**RC MOWERS**

# REMOTE-OPERATED ROBOTIC MOWERS THAT CREATE OPPORTUNITIES

**R SERIES MOWERS FOR MAINTAINING STEEP SLOPES & EXTREME LANDSCAPES**

## IDEAL FOR:

- Hillside & steep-incline maintenance
- Wetland & swamp preservation
- Dam & levee embankments
- Landfill slope preservation
- Retention or water treatment ponds
- Roadside mowing



**R-60**



**R-52**



**R-44**





**SERIES**  
REMOTE-OPERATED  
ROBOTIC MOWER



## COMPARISON CHART



ENGINE	Kawasaki® FX1000V EFI	Kawasaki® FX850V	Kawasaki® FR651V
HORSEPOWER	38.5	27	21.5
DISPLACEMENT	999 cc	852 cc	726 cc
DRIVE SYSTEM	Hydro-Gear® ZT-4400 Transaxles	Hydro-Gear® ZT-4400 Transaxles	Hydro-Gear® ZT-3100 Transaxles
FUEL CAPACITY	13.4 Gallons	13.4 Gallons	5 Gallons
GROUND SPEED	6.7 mph (Transport) / 5.7 mph (Mowing)	6.7 mph (Transport) / 5.7 mph (Mowing)	4.5 mph (Transport) / 4.2 mph (Mowing)
CUTTING WIDTH	60 Inches	52 Inches	44 Inches
ACRES PER HOUR	3.1	2.7	1.7
SLOPE CLIMB ABILITY	50 Degrees	50 Degrees	45 Degrees
DECK CONSTRUCTION	3/8" Thick Deck Across Spindles	3/8" Thick Deck Across Spindles	Fabricated 10 Ga. Steel
DECK ENGAGEMENT	Ogura® Soft Start Electric Clutch	Ogura® Soft Start Electric Clutch	Ogura® Electric Clutch
CUTTING HEIGHTS	2.5 - 7 Inches	2.5 - 7 Inches	2.5 - 6.0 Inches
TRACK CONSTRUCTION	Rubber Molded Over Steel Links	Rubber Molded Over Steel Links	Rubber Molded Over Steel Links
TRACK SIZE / STYLE	9 Inches / Tread Style 'J'	9 Inches / Tread Style 'J'	7 Inches / Tread Style 'Wave'
WEIGHT	1,900 Pounds	1,850 Pounds	1,220 Pounds
LENGTH	90 Inches	90 Inches	82 Inches
WIDTH	82 Inches	74 Inches	63 Inches
HEIGHT	49.5 Inches	49.5 Inches	34 Inches
WARRANTY	2 Years / 400 Hours	2 Years / 400 Hours	1 Year / 200 Hours

Customer Support: 920-634-2227 • [www.rcmowersusa.com](http://www.rcmowersusa.com)