



SHUTTLE™ 4

HARD WORK MEETS SUPERIOR EFFICIENCY.

Designed for multi-taskers, the Shuttle 4 showcases four forward-facing seats and a spacious cargo bed, making it the perfect vehicle to transport people and equipment through your facility. Available as an ELiTE lithium vehicle activated by Samsung SDI battery technology or with an efficient 13.5 hp EFI gas engine, the Shuttle 4 will help you get your daily operations done.

ELiTE
LITHIUM

ELiTE LITHIUM

OR
13.5 HP
EFI GAS

4 PASSENGER
SEATING

1200LB
VEHICLE LOAD CAPACITY

9 CU FT
CARGO DECK CAPACITY



OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Turn Signal with Four-Way Flashers
- Brake Lights
- LED Headlights
- LED Taillights/Brake Lights
- Wheel Covers
- Limited Slip Differential
- Additional Body Colors
- Rapid On-Board Charger (ELiTE Only)
- ELiTE World Charger (ELiTE Only)
- CE Kit (Gas Only)

CUSHMAN.COM

SHUTTLE™ 4

SHUTTLE 4 ELiTE

SHUTTLE 4 GAS

BODY & CHASSIS

| | |
|----------------|--|
| FRAME | Welded Steel with E-Coat & DuraShield™ Powder Coat |
| BODY & FINISH | Injection Molded TPO |
| STANDARD COLOR | Patriot Blue |

DIMENSIONS

| | |
|---------------------|---|
| OVERALL LENGTH | 134 in (343 cm) |
| OVERALL WIDTH | 48.5 in (123 cm) |
| OVERALL HEIGHT | 48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof) |
| WHEEL BASE | 93.5 in (237 cm) |
| WHEEL TRACK | 34.2 in (87 cm) Front / 38.0 in (97 cm) Rear |
| GROUND CLEARANCE | 3.9 in (9.8 cm) |
| CARGO DECK CAPACITY | 9 cu ft (.25 m3) |
| CARGO DECK MATERIAL | Wood Stake Sides |

POWER

| | | |
|--------------------|---|---|
| POWER SOURCE | 56.7V Li-Ion Battery | 4-Cycle, 24.5 ci (401cc) |
| VALVE TRAIN | N/A | Single Cylinder OHV |
| HORSEPOWER (KW) | 14.9 HP (11.1 kW) | 13.5 hp (10.1 kW) |
| ELECTRICAL SYSTEM | 48V Primary, 12V Auxiliary | Starter/Generator. Solid State Reg. |
| BATTERY (QTY/TYPE) | 56.7V Li-Ion Composite Module + Cell Model | One, 12V Maintenance Free |
| BATTERY CHARGER | 56.7V, 811W World Charger, 3M Charging Cord | N/A |
| KEY OR PEDAL START | | Pedal |
| AIR CLEANER | N/A | Replaceable Industrial Rated Dry Cartridge |
| LUBRICATION | N/A | Pressurized Oil System |
| OIL FILTER | N/A | Spin-On |
| COOLING SYSTEM | N/A | Air Cooled |
| FUEL CAPACITY | N/A | 5.96 Gallon (22.6 L) tank |
| DRIVE TRAIN | Motor Shaft Direct Drive | Continuously Variable Transmission |
| TRANSAXLE | | Differential w/ Helical Gears |
| GEAR SELECTION | Dash Mount Forward-Neutral- Reverse / Key Switch | Forward - Reverse |
| REAR AXLE RATIO | 16.99:1 | 11.47: 1 (Forward) / 14.35:1 (Reverse) |

PERFORMANCE

| | | |
|--------------------------|--|--|
| SEATING CAPACITY | | 4-Person |
| WEIGHT W/O BATTERIES | 907 lb | 896 lb (406 kg) |
| CURB WEIGHT | 988 lb | 936 lb (425 kg) |
| VEHICLE LOAD CAPACITY | 1200 lb (544 kg) | |
| BED LOAD CAPACITY | 400 lb (181 kg) | |
| OUTSIDE CLEARANCE CIRCLE | 25.5 ft (7.8 m) | |
| SPEED | 14.9 mph ± 0.5 mph (24.0 kph ± 0.8 kph) (High Speed) / 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed) / 16.5 mph | 14 mph ± 0.5 mph (22.5 kph ± 0.8 kph) |

STEERING & SUSPENSION

| | |
|----------------------|--|
| STEERING | Self-Compensating Rack and Pinion |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers |
| SERVICE BRAKE | Rear Wheel Mechanical Self-Adjusting Drum |
| PARKING BRAKE | Self-Compensating, Single-Point Engagement |
| TIRES (FRONT & REAR) | 18 x 8.50 - 8 (4 Ply Rated) |



SHUTTLE™ 6

ACCELERATE GROUP TRANSPORTATION.

Comfortably and effectively move up to six people with the use of the four forward-facing seats and two rear-facing seats in the Shuttle 6. Available as an ELiTE lithium vehicle activated by Samsung SDI battery technology or with an efficient 13.5 hp EFI gas engine, the Shuttle 6 gives you the ability to take care of every task across your facility.

ELiTE
LITHIUM

ELiTE LITHIUM
OR
13.5 HP
EFI GAS

6 PASSENGER
SEATING

1200LB
VEHICLE LOAD CAPACITY



OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Turn Signal with Four-Way Flashers
- LED Headlights
- LED Taillights/Brake Lights
- Wheel Covers
- Limited Slip Differential
- Additional Body Colors
- Rapid On-Board Charger (ELiTE Only)
- ELiTE World Charger (ELiTE Only)
- CE Kit (Gas Only)

SHUTTLE™ 6

BODY & CHASSIS

| | SHUTTLE 6 ELiTE | SHUTTLE 6 GAS |
|----------------|--|---------------|
| FRAME | Welded Steel with E-Coat & DuraShield™ Powder Coat | |
| BODY & FINISH | Injection Molded TPO | |
| STANDARD COLOR | Patriot Blue | |

DIMENSIONS

| | | |
|------------------|---|----------------|
| OVERALL LENGTH | 134 in (343 cm) | |
| OVERALL WIDTH | 48.5 in (123 cm) | |
| OVERALL HEIGHT | 48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof) | |
| WHEEL BASE | 93.5 in (237 cm) | |
| WHEEL TRACK | 34.2 in (87 cm) Front / 38.0 in (97 cm) Rear | |
| GROUND CLEARANCE | 3.9 in (9.8 cm) | 4.3 in (11 cm) |

POWER

| | | |
|--------------------|---|---|
| POWER SOURCE | 56.7V Li-Ion Battery | 4-Cycle, 24.5 ci (401cc) |
| VALVE TRAIN | N/A | Single Cylinder OHV |
| HORSEPOWER (KW) | 14.9 HP (11.1 kW) | 13.5 hp (10.1 kW) |
| ELECTRICAL SYSTEM | 48V Primary, 12V Auxiliary | Starter/Generator. Solid State Reg. |
| BATTERY (QTY/TYPE) | 56.7V Li-Ion Composite Module + Cell Model | One, 12V Maintenance Free |
| BATTERY CHARGER | 56VDC, 120/230 VAC, UL/ CSA, CE | N/A |
| KEY OR PEDAL START | Pedal | |
| AIR CLEANER | N/A | Replaceable Industrial Rated Dry Cartridge |
| LUBRICATION | N/A | Pressurized Oil System |
| OIL FILTER | N/A | Spin-On |
| COOLING SYSTEM | N/A | Air Cooled |
| FUEL CAPACITY | N/A | 5.96 Gallon (22.6 L) tank |
| DRIVE TRAIN | Motor Shaft Direct Drive | Continuously Variable Transmission |
| TRANSAXLE | Differential w/ Helical Gears | |
| GEAR SELECTION | Dash Mount Forward-Neutral- Reverse / Key Switch | Forward - Reverse |
| REAR AXLE RATIO | 16.99:1 | 11.47: 1 (Forward) / 14.35:1 (Reverse) |

PERFORMANCE

| | | |
|--------------------------|--|--|
| SEATING CAPACITY | 6-Person | |
| WEIGHT W/O BATTERIES | 945 lb | 1124 lb (510 kg) |
| CURB WEIGHT | 1026 lb | 1164 lb (528 kg) |
| VEHICLE LOAD CAPACITY | 1200 lb (544 kg) | |
| OUTSIDE CLEARANCE CIRCLE | 25.5 ft (7.8 m) | |
| SPEED | 14.9 mph ± 0.5 mph (24.0 kph ± 0.8 kph) (High Speed) / 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed) / 16.5 mph | 14 mph ± 0.5 mph (22.5 kph ± 0.8 kph) |

STEERING & SUSPENSION

| | | |
|----------------------|--|--|
| STEERING | Self-Compensating Rack and Pinion | |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers | |
| SERVICE BRAKE | Rear Wheel Mechanical Self-Adjusting Drum | |
| PARKING BRAKE | Self-Compensating, Single-Point Engagement | |
| TIRES (FRONT & REAR) | 18 x 8.50 - 8 (4 Ply Rated) | |

CUSHMAN.COM



SHUTTLE™ 8

ELEVATE HIGH VOLUME TRANSPORTATION.

The Shuttle 8 is the ideal vehicle for transporting large groups of people throughout your facility with its six forward-facing seats and two rear-facing seats. With the option of a maintenance-free ELiTE lithium powertrain activated by Samsung SDI battery technology or a fuel-efficient 13.5 hp EFI gas engine, the Shuttle 8 keeps guests and workers alike going.

ELiTE
LITHIUM

ELiTE LITHIUM
OR
13.5 HP
EFI GAS

8 PASSENGER
SEATING

1600LB
VEHICLE LOAD CAPACITY



OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Additional Body Colors
- Turn Signal with Four-Way Flashers
- LED Headlights
- LED Taillights/Brake Lights
- Additional Body Colors
- CE Kit (Gas Only)
- Rapid On-Board Charger (ELITE Only)
- Upgrade to 6.2 Triple Pack for Extended Range (ELITE Only)

SHUTTLE™ 8

BODY & CHASSIS

SHUTTLE 8 ELITE

SHUTTLE 8 GAS

| | |
|----------------|--|
| FRAME | Welded Steel with E-Coat & DuraShield™ Powder Coat |
| BODY & FINISH | Injection Molded TPO |
| STANDARD COLOR | Patriot Blue |

DIMENSIONS

| | |
|---------------------|---|
| OVERALL LENGTH | 171.3 in (435 cm) |
| OVERALL WIDTH | 49.6 in (126 cm) |
| OVERALL HEIGHT | 48.6 in (123 cm) (w/o Roof) / 76.0 in (193 cm) (w/ Struts & Roof) |
| WHEEL BASE | 125.0 in (318 cm) |
| WHEEL TRACK | 35.2 in (90 cm) Front / 36.7 in (93 cm) Rear |
| GROUND CLEARANCE | 4.4 in (11 cm) 3.0 in (8 cm) |
| CARGO DECK CAPACITY | 400 lb (181 kg) |

POWER

| | | |
|--------------------|---|---|
| POWER SOURCE | 56.7V Li-Ion Battery | 4-Cycle, 24.5 ci (401cc) |
| VALVE TRAIN | N/A | Single Cylinder OHV |
| HORSEPOWER (KW) | 14.9 hp (11.1 kW) Peak | 13.5 hp (10.1 kW) |
| ELECTRICAL SYSTEM | 48V Primary, 12V Auxiliary | Starter/Generator. Solid State Reg. |
| BATTERY (QTY/TYPE) | Single, 56.7V max Li-Ion Composite Module and Cell Module ("Twin Pack") | One, 12V Maintenance Free |
| BATTERY CHARGER | 56.7V, 811W World Charger, 3M Charging Cord | N/A |
| KEY OR PEDAL START | | Pedal |
| AIR CLEANER | N/A | Replaceable Industrial Rated Dry Cartridge |
| LUBRICATION | N/A | Pressurized Oil System |
| OIL FILTER | N/A | Spin-On |
| COOLING SYSTEM | N/A | Air Cooled |
| FUEL CAPACITY | N/A | 5.96 Gallon (22.6 L) Tank |
| DRIVE TRAIN | Motor Shaft Direct Drive | Continuously Variable Transmission |
| TRANSAXLE | | Differential w/ Helical Gears |
| GEAR SELECTION | Dash Mount Forward-Neutral- Reverse / Key Switch | Forward - Reverse |
| REAR AXLE RATIO | 16.99:1 | 11.47: 1 (Forward) / 14.35:1 (Reverse) |

PERFORMANCE

| | |
|--------------------------|---|
| SEATING CAPACITY | 8-Person |
| WEIGHT W/O BATTERIES | 1215 lb (551 kg) 1225 lb (556 kg) |
| CURB WEIGHT | 1289 lb (585 kg) 1265 lb (574 kg) |
| VEHICLE LOAD CAPACITY | 1600 lb (726 kg) |
| BED LOAD CAPACITY | 400 lb (181 kg) |
| OUTSIDE CLEARANCE CIRCLE | 35 ft (10.7 m) |
| SPEED | 16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) 16 mph ± 0.5 mph (26 kph ± 0.8 kph) |

STEERING & SUSPENSION

| | |
|----------------------|--|
| STEERING | Self-Compensating Rack and Pinion |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers |
| SERVICE BRAKE | Rear Wheel Mechanical Self-Adjusting Drum |
| PARKING BRAKE | Self-Compensating, Single-Point Engagement |
| TIRES (FRONT & REAR) | 215 / 60 - 8 (8 Ply Rated) Tires |

CUSHMAN.COM



CUSHMAN®

MINUTE MISER™



ALL WORK. ALL THE TIME.

With the Cushman® Minute Miser™, you won't waste a second of your day. This versatile, energy efficient vehicle features a flip-down seat for an additional passenger or a small cargo deck for moving equipment and materials. It's equipped with a zero-emissions, 24V electric drivetrain and has a load capacity of 550 pounds to move you around your facility in moments. Trust the Minute Miser to get you to the next job quickly and efficiently.

LET'S WORK.®

550^{LB}
TOTAL LOAD
CAPACITY

2
PERSON
SEATING

24v
ELECTRIC
DRIVETRAIN



CUSHMAN® MINUTE MISER™



FLIP-DOWN SEAT



300-LB CARGO DECK

HANDLEBAR STEERING

OPTIONS & ACCESSORIES

- Portable Charger
- Certification Module EE
- Hour Meter
- Headlight
- Horn
- CE Certification

BODY & CHASSIS

| | |
|----------------|---|
| FRAME | Welded Steel w/ DuraShield™ Powder Coat |
| BODY & FINISH | Diamond Plate Poly Primer and Acrylic |
| STANDARD COLOR | Safety Yellow |

DIMENSIONS

| | |
|-----------------------|----------------------------------|
| OVERALL LENGTH | 85.0 in (216 cm) |
| OVERALL WIDTH | 30.0 in (76 cm) |
| OVERALL HEIGHT | 39.0 in (99 cm) |
| WHEEL BASE | 48.0 in (122 cm) |
| WHEEL TRACK | N/A Front / 25.5 in (65 cm) Rear |
| GROUND CLEARANCE | 4.0 in (10 cm) |
| GARGO DECK DIMENSIONS | 23 in X 29 in (58 cm X 73 cm) |
| CARGO DECK CAPACITY | 300 lb (136 kg) |
| CARGO DECK MATERIAL | Plywood |

POWER

| | |
|---------------------|---------------------------------------|
| POWER SOURCE | 24V DC Series Wound |
| HORSEPOWER (KW) | 8.25 hp (6.15 kW) @ 1570 rpm |
| ELECTRICAL SYSTEM | 24V DC |
| BATTERY (QTY/TYPER) | Four, 6V Deep Cycle |
| BATTERY CHARGER | 24V DC, 100-240V AC On-Board, UL & CE |
| KEY OR PEDAL START | Pedal |
| SPEED CONTROLLER | Solid State 250 Amp Rated |
| DRIVE TRAIN | Motor Shaft Direct Drive |
| TRANSAXLE | Differential w/ Helical Gears |
| GEAR SELECTION | Forward-Neutral-Reverse |
| REAR AXLE RATIO | 14.78:1 |

PERFORMANCE

| | |
|--------------------------|-------------------------------------|
| SEATING CAPACITY | 2-Person |
| WEIGHT W/O BATTERIES | 440 lb (200 kg) |
| CURB WEIGHT | 690 lb (313 kg) |
| VEHICLE LOAD CAPACITY | 550 lb (250 kg) |
| BED LOAD CAPACITY | 300 lb (136 kg) |
| OUTSIDE CLEARANCE CIRCLE | 10.8 ft (3.3 m) |
| SPEED | 10 mph ± 0.5 mph (14 kph ± 0.8 kph) |

STEERING & SUSPENSION

| | |
|----------------------|--|
| STEERING | Direct Handlebar to Front Fork |
| SUSPENSION | Torque Block (Front) / Coil Springs & Single Shock Absorber (Rear) |
| SERVICE BRAKE | Rear Wheel Mechanical Drum |
| PARKING BRAKE | Single-Point Latch |
| TIRES (FRONT & REAR) | 4.80 x 8 (Load Range B) |

www.cushman.com

©2021 Textron Specialized Vehicles Inc. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82326-G7 (Rev. 11/2021)



ALL-NEW

SHUTTLE™ 2+2

VERSATILITY COMMANDS THE DAY.

The newly redesigned Shuttle 2+2 is the ideal choice for transporting personnel and visitors. Comfortably seating up to four passengers with bench seats, the rear seat will also convert to a cargo deck. The Shuttle 2+2 is offered in your choice of a fuel-efficient 13.5-hp EFI gas engine or with an ELiTE lithium powertrain activated by Samsung SDI lithium technology.

ELiTE
LITHIUM

ALL-NEW
IMPROVED STYLING

**NOW AVAILABLE
WITH**
ELiTE LITHIUM
POWERTRAIN

18" OR 20"
TIRE OPTIONS

2 OR 4-WHEEL
MECHANICAL BRAKE
OPTIONS



STANDARD FEATURES

- RFS Pro Rear-Facing Seat
- Halogen Headlights
- 18" or 20" Tires
- 2-Wheel Mechanical Brakes
- E-Shield™ Frame
- Modular Canopy
- Premium Steering Wheel
- Side Body Color
- Multifunction Gauge (ELiTE only)
- Fuel and Oil Gauge (Gas only)

OPTIONS & ACCESSORIES

- 4-Wheel Mechanical Brakes
- Contoured Seats
- Limited Slip Differential
- LED Headlights, Taillights and Brake Lights
- Brush Guard
- Lockable Glove Box with Shelf and Molded Rubber Mats
- Fold-Down Windshield
- Flat Windshield
- Weather Enclosure
- USB Outlet
- Rearview Mirror
- ELiTE Lithium 2.2, 4.2, or 6.2 Pack (ELiTE only)
- Rapid On-Board Charger (ELiTE only)

CUSHMAN.COM

ALL-NEW

SHUTTLE™ 2+2

SHUTTLE 2+2 ELiTE

18" TIRES

20" TIRES

SHUTTLE 2+2 GAS

18" TIRES

20" TIRES

BODY & CHASSIS

FRAME Welded Steel with E-Coat & DuraShield™ Powder Coat

BODY & FINISH Injection Molded TPO

STANDARD COLOR Patriot Blue

DIMENSIONS

OVERALL LENGTH 113 in (287 cm)

OVERALL WIDTH 47 in (119 cm)

OVERALL HEIGHT (W/ CANOPY) 76 in (193 cm) 80 in (203 cm) 76 in (193 cm) 80 in (203 cm)

OVERALL HEIGHT (W/O CANOPY) 48 in (122 cm) 52 in (132 cm) 48 in (122 cm) 52 in (132 cm)

WHEEL BASE 65.5 in (166 cm)

WHEEL TRACK 37 in (94 cm) Front / 38 in (97 cm) Rear

GROUND CLEARANCE 4.3 in (11 cm) 5.5 in (14 cm) 4.3 in (11 cm) 5.5 in (14 cm)

POWER

POWER SOURCE 56.7V Li-Ion Battery 4-Cycle, 24.5 ci (401cc)

VALVE TRAIN N/A Single Cylinder OHV

HORSEPOWER (KW) 11.7 HP (8.7 kW) 13.5 hp (10.1 kW)

ELECTRICAL SYSTEM 48V Primary, 12V Auxiliary Starter/Generator, Solid State Regulator

BATTERY (QTY/TYPE) 2.2 Single, 56.7V Li-Ion Composite Module One, 12V Maintenance Free

BATTERY CHARGER 56.7V, 350W Domestic Charger, 3M Charging Cord N/A

KEY OR PEDAL START Pedal

AIR CLEANER N/A Industrial Rated Dry Filter

LUBRICATION N/A Pressurized Oil System

OIL FILTER N/A Spin-On

COOLING SYSTEM N/A Air Cooled

FUEL CAPACITY N/A 5.96 Gallon (22.6 L) tank

DRIVE TRAIN Motor Shaft Direct Drive Continuously Variable Transmission (CVT)

TRANSAXLE Differential w/ Helical Gears

GEAR SELECTION Dash Mount Forward-Neutral-Reverse / Key Switch Forward - Reverse

REAR AXLE RATIO 16.99:1 11.47:1 (Forward) / 14.35:1 (Reverse)

PERFORMANCE

SEATING CAPACITY 4-Person

WEIGHT W/O BATTERIES 743 lb (342 kg) 782 lb (351 kg) 872 lb (396 kg) 913 lb (414 kg)

CURB WEIGHT 790 lb (363 kg) 829 lb (372 kg) 902 (409 kg) 963 lb (437 kg)

VEHICLE LOAD CAPACITY 800 lb (363 kg)

OUTSIDE CLEARANCE CIRCLE 18.9 ft (5.76 m)

SPEED 16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)

STEERING & SUSPENSION

STEERING Self-Compensating Rack and Pinion

SUSPENSION Leaf Springs w/ Hydraulic Shock Absorbers

SERVICE BRAKE Dual Rear Wheel Mechanical Self-adjusting Drum

PARKING BRAKE Self-Compensating, Single-Point Engagement

TIRES (FRONT & REAR) Hole-N-One Tires K399, 205/65-10, 6 PLY Hole-N-One Tires K399, 205/65-10, 6 PLY