Delta Chemical Corp.
The Difference in Water Treatment
P.O. Box 7430
Metairie, LA 70010

Product Data Sheet

PRODUCT:	**DWT 6035**	
NAME:	Polyphosphate	
GENERAL DESCRIPTION:	DWT 6035 is a liquid Polyphosphate scale and corrosion inhibitor used primarily in the protection of potable water distribution systems. DWT 6035 has been specifically formulated to provide excellent sequestering capabilities and for a wide range of general corrosion inhibition needs. When added to the water flow, DWT 6035 forms a stable, evenly distributed protective film on distribution piping and all surfaces.	
PRODUCT CHARACTERISTICS:	Appearance: % P-PO4: Density: pH: Solubility: Crystallization Point: NSF/ANSI/CAN Std 60 MUL:	Clear Colorless Liquid 34-36 1.64-1.74 10-12 100% < 20 °F 26.0 mg/L
PRINCIPAL USES:	• Controls General Corrosion • Sequesters Calcium, Iron, & Manganese • Prevents Scale Deposits	
PRECAUTIONS AND HANDLING:	DWT 6035 is a non-hazardous material. However, caution should be taken to prevent ingestion, contact with skin and eyes. It is recommended that safety eye protection, gloves and other personal protection be worn when handling all chemicals. DWT 6035 is not DOT regulated. Consult material safety data sheet for specific information regarding safety and handling of this product. • Store in a cool, dry, well ventilated area away from incompatible materials. • Keep containers closed when not in use. Refer to the SDS for additional information.	
PACKAGING:	Bulk, 55 Gallon Drums, 30 Gallon Drums, 275 Gallon Tote DO NOT REUSE CONTAINERS	