Delta Chemical Corp.
The Difference in Water Treatment
P.O. Box 7430
Metaire, LA 70010

PRODUCT DATA SHEET

DBT 4800-L BOILER WATER DISPERSANT

GENERAL DESCRIPTION:

DBT 4800 contains a blend of synthetic terpolymers, co-polymers, and natural organic dispersants for suspension of sludge in boiler systems. The suspended sludge is readily removed by means of continuous and/or bottom blowdown. DBT 4800 is especially effective in boiler systems which contain an appreciable amount of iron. The product contains a trace element to facilitate product testing in the boiler.

PRODUCT CHARACTERISTICS:

Form.....Light Amber Liquid
pH.....Approximately 13.50
Density.....9.82 lbs./gallon

FEEDING:

DBT 4800 may be mixed with other boiler treatment compounds and there are no restrictions on this product relative to point of feed. Consult your service representative for specific recommendations.

PRECAUTIONS AND HANDLING:

Product is an alkaline material. Avoid contact with skin and eyes. Do not take internally. Protective gloves and chemical splash goggles are recommended. Wear impervious apron and boots to minimize potential contact. General ventilation is adequate, however, a NIOSH approved breathing apparatus should be used for exposures above OSHA threshold limit values. Consult material safety data sheet for more information.

PACKAGING:

BULK
55 GALLON DRUMS
30 GALLON DRUMS