# Earth Sense\*

#### **ENVIRONMENTALLY RESPONSIBLE**

## GREEN IMPACT™

Speed Stripper

#### **DESCRIPTION**

GREEN IMPACT™ Stripper is a fast-acting speed stripper. This environmentally responsible formulation meets the Green Seal™ Standard for Industrial and Institutional Floor -Care Products (GS-40) and has been certified along with companion Green Seal™ Certified floor finishes.

GREEN IMPACT™ Stripper and companion Green Seal™ Certified Earth Sense® Floor Finishes are recommended for use in Federal, State and Local Government Offices, Military Bases, Municipal Facilities, Day Care Centers, Hospitals, Nursing Homes, Office Buildings, Parks and Recreation Centers, Schools, Universities, Hotels, Lodging and any facility sensitive to environmental and human health characteristics.

#### **PRODUCT BENEFITS**

- Non-toxic, non-flammable, non-caustic, environmentally responsible formula.
- No phosphates, no butyl (2-Butoxyethanol\*), no NPE or APE surfactants, no free alkali, no added fragrances.
- Powerful, yet low odor formulation is excellent for use in health care facilities, nursing homes, any area where objectionable odors present a problem.
- · Concentrated formula for economical in-use-dilution costs.

#### **DIRECTIONS FOR USE**

Mop/Wet Vacuum Stripping System: Dilute GREEN IMPACT™ using cold water according to the dilution chart below. Apply liberally with a mop to small area and allow to stand for 3 to 5 minutes. Add water to the floor as necessary to keep the floor from drying. Agitate with a mop and pick-up solution and old finish with a wet vacuum. Rinse as necessary. Allow floor to dry completely.

Floor Machine Stripping System: Dilute GREEN IMPACT™ using cold water according to the dilution chart below. GREEN IMPACT™ may be applied with a mop or Automatic Scrubber. Allow to stand for 3

to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Pick-up solution and old finish with a wet vacuum. Rinse as necessary. Allow floor to dry completely.

APPLICATION	OZ./GAL	DILUTION	
Mop/Wet Vac			Marie Land
Heavy Build-up	64	1:2	
Normal Build-up	25	1:5	
Floor Machine Stripping			
Normal Build-up	8	1:16	
Heavy Build-up	25	1:5	

#### **SPECIFICATIONS**

Color	Clear Green
Odor	. Very Low, Neutral
pH (as is)	10.0 ± 0.3
pH (In dilution 1:5)	9.8 ± 0.3
pH (In dilution 1:16)	9.7 ± 0.3
Specific Gravity (g/cc)	1.00 ± 0.01
Lower Cloud Point	< 33°F

Upper Cloud Point	> 130°F
Viscosity (cps)	< 5
Water Solubility	Complete
Stripping	Outstanding
Free Rinsing	Yes
Low Odor	Yes
Shelf Life 1 year minimum in origin	nal unopened container.

#### **ENVIRONMENTAL RECOGNITIONS**



The EARTH SENSE® Seal of Assurance is self-certified by NCL, and identifies our products that are formulated to promote human health and worker safety with a preferred environmental profile.



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

DISPOSE OF UNUSED PRODUCT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS - PLEASE RECYCLE CONTAINER

**PPE Information**: Respiratory protection is generally not required. Use with adequate ventillation. The use of safety glasses and gloves is recommended. No other protective equipment is required.

### **ENVIRONMENTAL PROFILE**

Chemical ingredients:		
Phosphates:	None	
Ammonia:	None	
2-Butoxyethanol*:	None	
APE / NPE:	None	
Added Fragrances:	None	
Free Alkali:	None	

Human Toxicity\*:
Skin Corrosive:....

\* Human toxicity profile is based on ready-to-use product.



World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123 1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517 www.nclonline.com • e-mail:info@nclonline.com



## NATIONAL CHEMICAL LABORATORIES, INC.

2

#### **SAFETY DATA SHEET**

#### **Section 1 - Identification**

Product Identifier Earth Sense® GREEN IMPACT Speed Stripper

Other means of identification 1053

Recommended use Floor stripper.

**Recommended restrictions** For commercial and industrial use only.

Manufacturer / Importer / Supplier / Distributor Information

Company NameNational Chemical Laboratories of PA, Inc.Address401 N. 10th Street - Philadelphia, PA 19123

 Telephone
 1 (215) 922-1200

 Supplier Email
 info@nclonline.com

 Contact
 CHEM-TEL

 Emergency Phone
 1 (800) 255-3924

#### Section 2 - Hazard(s) Identification

SDS Hazards and Warnings are based on the undiluted product. Refer to diluted SDS for Ready-To-Use Hazards and Warnings.

Classification Category

Physical Hazards Not Classified

Health Hazards Serious eye damage/eye irritation

OSHA defined hazards Not Classified.

Label Elements

**Hazard Symbol** 



Signal Word Warning

Hazard Statement Causes serious eye irritation.

**Precautionary statement** 

**Prevention** Wash thoroughly after handling. Wear eye/face protection.

**Response** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. If eye irritation persists: Get medical advice/attention.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

#### Section 3 - Composition/Information on ingredients

Mixture

 Hazardous Components
 Ingredient Name
 CAS #
 %

 Benzyl Alcohol
 100-51-6
 10 - 20

 2-Amino Ethanol
 141-43-5
 1 - 5

 Alcohols, C12-13 Ethoxylated
 66455-14-9
 1 - 5

#### **Section 4 - First-aid Measures**

**Inhalation** Move to fresh air. Get medical attention if irritation persists.

**Skin contact** Wash off with soap and water. Get medical attention if irritation persists.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do.

 $\label{lem:continue} \textbf{Continue rinsing. Get medical attention if irritation persists.}$ 

**Ingestion** Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Call a physician or poison

control center.

Most Important symptoms /effects, acute and delayed

Serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General Information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### **Section 5 - Fire-fighting measures**

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment

/instructions

Move containers from fire area if you can do it without risk.

General fire hazards No unusual fire or explosion hazards noted.

Specific Methods Use standard firefighting procedures and consider the hazards of other involved materials.

#### **Section 6 - Accidental release measures**

Personal precautions, protective equipment and emergency procedures.

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Isolate area.

Methods and materials for containment and cleaning up This product is miscible in water.

SMALL SPILLAGE: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual

contamination.

LARGE SPILLS: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product

recovery, flush area with water.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Absorb spillage with suitable absorbent

material. After removal flush contaminated area thoroughly with water.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

#### **Section 7 - Handling and storage**

Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

#### Section 8 - Exposure control/personal protection

#### Occupational exposure limits

US. Workplace environmental Exposure Level (WEEL) Guides

Type

Benzyl Alcohol (CAS 100-51-6) TWA 44.2 mg/m<sup>3</sup>, 10 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components Value Form Tvpe

2-Amino Ethanol (CAS 141-43-5) 6 mg/m<sup>3</sup>, 3 ppm TWA

**US. ACGIH Threshold Limit Values** 

Component Type Value Form

2-Amino Ethanol (CAS 141-43-5) STEL 6 ppm 2-Amino Ethanol (CAS 141-43-5) TWA 3 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards** 

Components Type Value

2-Amino Ethanol (CAS 141-43-5) STFI 15 mg/m<sup>3</sup>, 6 ppm 2-Amino Ethanol (CAS 141-43-5) TWA  $8 \text{ mg/m}^3$ , 3 ppm

**Biological limit values** No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Provide adequate ventilation and minimize the risk of inhalation of vapors and mists. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

1053

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Use a respirator when local exhaust or ventilation is

not adequate to keep exposures below the OEL. In a confined space a supplied respirator may be required.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking,

considerations and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### **Section 9 - Physical and chemical properties**

Clear. **Appearance** Physical state Liquid. Form Liquid Colo Green.

Odor Mild aromatic. Odor threshold Not available 10.0 ± 0.3 (Conc) рΗ 9.8 ± 0.4 (1:2 to 1:16)

Melting point/freezing point Not available. 212 °F (100 °C)

Initial boinging point and

boiling range

Flash point None to boiling. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits Flammability limit - lower (%) Not available Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Similar to water. Vapor density Similar to water. Relative density 1.01 + 0.01Relative density temperature 75 °F (23.89 °C) **Solubilities** 100 % Soluble.

Partition Coefficient n-

octanol/water

Not available

Auto-ignition temperature Not Available **Decomposition temperature** Not Available Viscosity < 10 cP

75 °F (23.89 °C) **Viscosity Temperature** 

#### Section 10 - Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Stable at normal conditions.

Possiblity of hazardous reactions No dangerous reaction known under conditions of normal use.

**Conditions to Avoid** Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous Decomposition** No hazardous decomposition products are known.

**Products** 

#### **Section 11 - Toxicological information**

Information on likely routes of exposure

Ingestion May be harmful if swallowed. Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Eve contact Causes serious eye irritation.

Serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Symptoms related to the

physical, chemical and Prolonged or repeated exposure may cause liver and kidney damage, these effects have not been observed in humans.

toxicological characteristics

Information on toxicological effects.

Acute toxicity

Components Level Type Code **Species** Results 2-Amino Ethanol (CAS 141-43-5) Acute Dermal LD50 Rabbit 1025 mg/kg Acute Oral LD50 Rat 1715 mg/kg

Alcohols, C12-13 Ethoxylated (CAS 66455-14-9) Acute Dermal LD50 Rabbit 3300 mg/kg, 24 Hours Acute LD50 > 2000 mg/kg, 24 Hours Dermal

1053

	Acute	Inhalation	LC50	Rat	> 100 mg/m³, 6 Hours > 1.6 mg/l, 4 Hours
Benzyl Alcohol (CAS 100-51-6)	Acute	Dermal	LD50	Rabbit	2000 mg/kg
	Acute	Inhalation	LC100	Rat	200 - 300 mg/l, 8 Hours
	Acute	Inhalation	LC50	Rat	8.8 mg/l, 4 Hours
	Acute	Oral	LD50	Mouse	1150 mg/kg
	Acute	Oral	LD50	Rat	1230 - 3100 mg/kg
	Acute	Other	LD50	Mouse	480 mg/kg
	Acute	Other	LD50	Rat	400 mg/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/ eye

irritation

Causes serious eye irritation.

**Respiratory sensitization**This product is not expected to cause respiratory sensitization. **Skin sensitization**This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not classified.

**Chronic effects** May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

#### **Section 12 - Ecological Information**

Ecotoxicity The product contains a substance which is very toxic to aquatic organisms.

Component(s)

2-Amino Ethanol, 141-43-5

Aquatic

Acute Algae EC50 Selenastrum capricornutum (new name 2.5 mg/l, 48 hours

Pseudokirchnerella subca

CrustaceaEC50Daphnia magna65 mg/l, 48 hoursFishLC50Goldfish (Carassius auratus)170 mg/l, 96 hoursFishLC50Cyprinus carpio349 mg/l, 96 hours

Alcohols, C12-13 Ethoxylated, 66455-14-9

Aquatic

Acute Crustacea EC50 Water flea (Daphnia magna) 0.39 -0.56 mg/l, 48 hours
Fish LC50 Flathead minnow (Pimephales promelas) 0.72 -2.7 mg/l, 96 hours

Benzyl Alcohol, 100-51-6

Aquatic

Acute Fish LC50 Bluegill (Lepomis macrochirus) 10 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coeficient n-octanol / water log (Kow)

 Components
 Results

 2-Amino Ethanol (CAS 141-43-5)
 -1.31

 Benzyl Alcohol (CAS 100-51-6)
 1.1

Mobility in soil No data available.

**Mobility in general** The product is water soluble and may spread in water systems.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine

disruption, global warming potential) are expected from this component.

#### **Section 13 - Disposal considerations**

**Disposal instructions** Dispose in accordance with applicable federal, state, and local regulations.

**Local disposal regulations** Dispose of in accordance with local regulations.

**Hazardous waste code**Waste codes should be assigned by the user based on the application for which the product was used.

Waste from residues / unused

products

Dispose in accordance with all applicable regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

1053

#### **Section 14 - Transport information**

DOT Not regulated as dangerous goods. IATA Not regulated as dangerous goods. **IMDG** Not regulated as dangerous goods.

Transportation in bulk This substance/mixture is not intended to be transported in bulk.

according to Annex II of MARPOL 73/78 and IBC Code

#### **Section 15 - Regulatory Information**

**US** federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR707, Subpt. D) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not on regulatory list.

CERCLA Hazardous Substance List (40 CFR 302.4

Not listed.

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard Categories** Immediate Hazard

Delayed Hazard Fire Hazard No Pressure Hazard No Reactivity Hazard No

SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HSPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated.

Safe Drinking Water Act (SDWA) Not regulated. Food and Drug Administration (FDA) Not regulated.

**US state regulations** 

**US.Massachusetts RTK - Substance List** Components

> 2-Amino Ethanol (CAS 141-43-5) Benzyl Alcohol (CAS 100-51-6)

US.New Jersey Worker and Community Right-to-Know Act Components

2-Amino Ethanol (CAS 141-43-5)

**US.Pennsylvania RTK - Hazardous Substances** Components

> 2-Amino Ethanol (CAS 141-43-5) Benzyl Alcohol (CAS 100-51-6)

US Rhode Island RTK Components

2-Amino Ethanol (CAS 141-43-5)

**US - California Propsition 65** California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This

material is not known to contain any chemicals currently listed as carcinogens or

reproductive toxins.

International Inventories

Country(s) or region	Inventory Name	On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notifed Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
Unites States Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

#### Section 16 - Other information, including date of preparation or last version

Issue date 2/5/2015 **Revision date** 1/15/2015 Version # 02

<sup>\*</sup>A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### Disclaimer

The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS. Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this SDS. The user should review these regulations to ensure full compliance.

#### Directions:

Mop/Wet Vacuum Stripping System: Dilute GREEN IMPACT™ using cold water according to the dilution chart below. Apply liberally with a mop to small area and allow to stand for 3 to 5 minutes. Add water to the floor as necessary to keep the floor from drying. Agitate with a mop and pick-up solution and old finish with a wet vacuum. Rinse as necessary. Allow floor to dry completely.

Floor Machine Stripping System: Dilute GREEN IMPACT™ using cold water according to the dilution chart below. GREEN IMPACT<sup>™</sup> may be applied with a mop or Automatic Scrubber. Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Pick-up solution and old finish with a wet vacuum. Rinse as necessary. Allow floor to dry completely.

Finish Application: When applying finish use a compatible Green Seal™ Certified NCL Earth Sense® Floor Finish following directions of the product label.

DILUTION	OZ./GAL.	APPLICATION	DI
Mop / Wet Vac:			Mop/\
1:2	64	Heavy Build-Up	-
1:5	25	Moderate Grease & Soils	
Floor Machine Strip	oping:		El pela
1:5	25	Heavy Build-Up	
1:16	8	Normal Build-Up	

## DISPOSE OF UNUSED PRODUCT IN ACCORDANCE WITH LOCAL

PPE Information: Respiratory protection is generally not required. Use with adequate ventilation. The use of safety glasses and gloves is recommended. No other protective equipment is required.

#### Instrucciones para Uso:

Mop/sistema que pela mojado de vacío: GREEN IMPACT™ diluído usando la agua fría según carta de la dilusión abaio. Aplicarte liberalmente con un mop al área pequeña y permitir para estar parado por 3 a 5 minutos. Agregar el agua al piso cuanto sea necesario para quardar el piso de la seguedad. Agitar con una solución del mop y de la recogida v vieio final con un vacío moiado. Aclaración cuanto sea necesario. Permitir que el piso se segue totalmente.

Máquina del piso Sistema que pela: GREEN IMPACT™ diluído usando la aqua fría según carta de la dilusión abaio. El GREEN IMPACT™ se puede aplicar con un mop o un depurador automático. Permitir para estar parado por 3 a 5 minutos, fregar con una máquina rotatoria del piso o un depurador automático equipado de los coines que pelan. Tomar la solución y el vieio final con un vacío moiado. Aclaración cuanto sea necesario. Permitir que el piso se segue totalmente.

Aplicación Acabado: Cuando acabado aplicando utilizar un compatibles Green Seal™ Certified NCL Earth Sense® Floor Finish siguientes direcciones de la etiqueta del producto.

APPLICATION	DILUSIÓN	ONZA./GAL.	US0
	Mop/Vac mojado:		
Heavy Build-Up	1:2	64	Acumulación pesada
Moderate Grease & Soils	1:5	25	Moderar la grasa y los suelos
	El pelar de la máquin	na del piso:	
Heavy Build-Up	1:5	25	Acumulación pesada
Normal Build-Up	1:16	8	Acumulación normal
	Heavy Build-Up Moderate Grease & Soils Heavy Build-Up	Heavy Build-Up 1:2 Moderate Grease & Soils 1:5  El pelar de la máquir Heavy Build-Up 1:5	Heavy Build-Up Moderate Grease & Soils         1:2         64 to 25           Heavy Build-Up Moderate Grease & Soils         1:5         25           El pelar de la máquina del piso:           Heavy Build-Up         1:5         25

#### ELIMINE EL PRODUCTO SIN UTILIZAR DE ACUERDO CON LAS NORMAS STATE AND FEDERAL REGULATIONS - PLEASE RECYCLE CONTAINER LOCALES, ESTATALES Y FEDERALES, FAVOR DE RECICLAR EL CONTENEDOR.

Información PPE: Generalmente no se requiere protección respiratoria. Utilizar con una ventilación adecuada. Se recomienda el uso de gafas de seguridad y quantes. No se requiere ningún otro equipo de protección.









**Strippers** 

ENVIRONMENTAULY RESPONSIBLE



## **Green Impact**™

Speed Stripper

A concentrated, odorless speed stripper. Rapidly penetrates and removes multiple coats of finish!

#### **WARNING:** CAUSES SERIOUS EYE IRRITATION.

See side panel for additional precautionary statements.

#### **ATENCIÓN:** PROVOCA IRRITACION OCULARES GRAVES.

Ver panel lateral para las medidas preventivas adicionales.

**NET CONTENTS: 1 GALLON / 3.79 LITERS** 

**National Chemical Laboratories, Inc.** Philadelphia, PA 19123 USA • (800) 628-2436 www.nclonline.com



Product No.: 1053



#### WARNING: CAUSES SERIOUS EYE IRRITATION. KEEP OUT OF THE REACH OF CHILDREN.

#### Precautionary statement **Prevention:** Wash thoroughly after handling.

Wear eye/face protection.

Response: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eve irritation persists: Get medical advice/

Storage: Store away from incompatible materials.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910,1200, All components are on the U.S. EPA TSCA Inventory List.

#### Additional safety measures:

Read the entire label and SDS before using this product, and for additional first aid measures. SDS for this product is available on the web at www.nclonline.com

#### ATENCIÓN: PROVOCA IRRITACION OCULARES GRAVES. MANTENER FUERA DEL ALCANCE DE LOS NIÑOS.

#### Conseios de prudencia

Prevención: Lávese cuidadosamente después de la manipulación. Use protección para los ojos/la cara.

Respuesta: Si en los ojos: Aclarar cuidadosamente con agua durante varios minutos. Quitar las lentes de contacto, si lleva y resulta fácil de hacer. Proseguir con el lavado. Si persiste la irritación ocular: Consultar a un médico / atención.

Almacenamiento: Almacene leios de materiales incompatibles.

Eliminación: Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales / internacionales pertinentes.

Este producto es calificado como "químicamente peligroso" según el Estándar de Comunicación de Riesgos de la OSHA Hazard Communication Standard, 29 CFR 1910,1200, Todos los componentes están en la Lista de inventario de la EPA TSCA.

#### Medidas additional de primeros auxilios:

Lea toda la etiqueta y SDS antes de usar este producto, así como medidas adicionales de primeros auxilios. SDS para el artículo está disponible en la web en www.nclonline.com

#### KEEP FROM FREEZING

CONTAINS: 2-Amino Ethanol CAS# 141-43-5, Benzyl Alcohol CAS# 100-51-6, Alcohols, C12-13 Ethoxylated CAS# 66455-14-9



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOC's and human & environmental toxicity. GreenSeal.org.



The EARTH SENSE® Seal of Assurance is self-certified by NCL, and identifies our products that are formulated to promote human health and worker safety with a preferred environmental profile.



401 N. 10th Street • Philadelphia, PA 19123 1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517 www.nclonline.com • e-mail: info@nclonline.com