Carpet Pre-Spray

Carpet Pre-Spray is designed to maximize cleaning efficiency while minimizing harmful residue. Residue causes resoiling, which increases cleaning frequency, costing time and money.

- Penetrates to loosen oil and water based soils
- Removes soil without damaging carpet.
- Green Seal certified.

Technical Specifications

Appearance	Clear
Dilution Rate	1:20
Color	Colorless
Scent	Non-Objectionable
Non Volatile Matter	13.00-14.00%
pH @ 25 deg. C	9.00 - 10.00
5th Gen Carpet	5th Generation Carpet Safe

Safety

See material safety data sheet and product for safety information, handling and proper use.

HMIS (Concentrate/RTU)

Flammability = 0/0 Health = 1/0 Reactivity = 0/0

Availability

HIL0081404	12 - 1 Quart Bottles
HIL0081425	4 - 2.5 Liter Containers

Certifications, Registrations & Notes

Green Seal™ Certified

This product meets Green Seal™ Standard GS-37 based on effective performance, concentrated volume, minimized/recycled packaging, and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

CRI Certified

The CRI Seal of Approval program tests cleaning effectiveness. Solutions are tested on overall cleaning effectiveness and the following criteria: rate of resoiling, pH level, surface texture change, optical brighteners and colorfastness.

Directions

Arsenal II
Use of hot water is recommended.
1. For use with Hillyard Arsenal Push Button Dispensers. Remove shipping cap and attach adapter cap to the one gallon of concentrate. Place into either a wire rack or cabinet. 2. Dispense diluted product into a pump-up pressure sprayer. 3. Vacuum the floor thoroughly. 4. Pre- spray carpet with diluted product from a pump-up pressure sprayer or trigger sprayer. Light agitation of carpet with a carpet brush will increase cleaning efficiency. Let product dwell for 5 minutes before extracting. 5. Wait overnight for the carpet to dry before walking on it. To dry thoroughly, open windows and use fans. 6. Once the carpet is completely dry, vacuum the carpet thoroughly. 7. This product is diluted at 6 oz. per gallon.

Arsenal Junior & Mobile
Use of hot water is recommended.
1. For use with Hillyard Arsenal Push Button Dispensers. Remove shipping cap and insert container into bottom of dispenser until it locks into place. 2. Dispense diluted product into a pump-up pressure sprayer. 3. Vacuum the floor thoroughly. 4. Pre-spray carpet with diluted product from a pump- up pressure sprayer or trigger sprayer. Light agitation of carpet with a carpet brush will increase cleaning efficiency. Let product dwell for 5 minutes before extracting. 5. Wait overnight for the carpet to dry before walking on it. To dry thoroughly, open windows and use fans. 6. Once the carpet is completely dry, vacuum the carpet thoroughly. 7. This product is diluted at 6 oz. per gallon.

Arsenal Jug System
Use of hot water is recommended.
1. Empty contents of quart container into 5 gallons of water in a 5 gallon dispensing jug. 2. Dispense diluted product into a pump-up pressure sprayer. 3. Vacuum the floor thoroughly. 4. Pre-spray carpet with diluted product from a pump-up pressure sprayer or trigger sprayer. Light agitation of carpet with a carpet brush will increase cleaning efficiency. Let product dwell for 5 minutes before extracting. 5. Wait overnight for the carpet to dry before walking on it. To dry thoroughly, open windows and use fans. 6. Once the carpet is completely dry, vacuum the carpet thoroughly. 7. This product is diluted at 6 oz. per gallon.

NOTICE: Over-wetting of carpet may cause shrinkage and browning.