Top Shape®

A quality, acrylic copolymer floor polish formulated to provide a clear, wet-look, protective shine on your floors. Top Shape's advanced formula is perfect for resilient tile, terrazzo, unglazed ceramic, quarry tile, paver brick, natural stone, sealed wood, or concrete flooring.

- 18% solids clear acrylic copolymer for enhanced appearance.
- Self-leveling for easy application.
- Minimum maintenance required.

Technical Specifications

Appearance	Milky Emulsion
Dilution Rate	RTU
Color	Milky White
Scent	Non-Objectionable
Non Volatile Matter	18.00%
pH @ 25 deg. C	8.00 - 9.00

Safety

See material safety data sheet and product for safety information, handling and proper use.

HMIS (Concentrate/RTU)

Flammability = 0 Health = 0 Reactivity = 0

Availability

HIL0052206	4 - 1 Gallon Containers
HIL0052207	1 - 5 Gallon Bag-In-Box
HIL0052209	1 - 55 Gallon Drum
HIL0052272	1 - 5 Gallon Pail

Certifications, Registrations & Notes

UL Approved

Classified by Underwriters Laboratories, Inc. as to slip resistance. (186S).

Directions

Preparation: New floors: After resilient flooring has been installed and the adhesive has cured for at least 2 weeks, scrub with a solution of Hillyard Recoat Prep or Assurance, following label directions, and a blue pad to remove factory finish. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour. **Scrub and recoat:** Scrub the existing floor polish with a solution of Hillyard Recoat Prep or Assurance, following label directions, and a blue pad. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour. **Stripping:** Strip Top Shape or other polishes from the floor with a solution of Hillyard Arsenal Stripper, Devastator, or Power-Strip, following label directions. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour.

Application: When using a sealer, apply a minimum of 5 coats of Top Shape at a rate of 1500-2000 ft²/gallon with a microfiber flat finish mop or Multi-Flo XP. Allow each coat to dry a minimum of 30 minutes before applying the next. When a sealer is not used, apply a minimum of 7 coats of Top Shape.

NOTE: Allow for longer dry time between coats of finish if the humidity is above 80% or the floor temperature is below 60°F (16°C). For best results, do not apply more than 3-4 coats per day.

Maintenance: Use a cotton dust mop, treated with Hillyard Super Hil-Tone, daily to remove loose dirt and grit. Damp mop or autoscrub, as scheduled, with Hillyard Super Shine-All®, Top Clean®, or Arsenal® Heavy Duty Floor Cleaner. After the floor has been cleaned, gloss may be restored by spray buffing with Hillyard Hil-Glo®, according to label directions. Scrub and recoat, as scheduled, with a minimum of 2 coats of Top Shape.

FLOOR PAD RECOMMENDATIONS: Stripping: black; **Scrub and Recoat:** blue; **Autoscrubbing:** red.

NOTICE: Do not use an ammoniated cleaner for daily care. If the floor is very porous, seal with Hillyard Hil-Tex+® or Seal 341® before applying Top Shape. If stains are a problem, seal with Strong Guard®. Do not pour unused finish or seal back into the original container.