ENVIRO-BROM® TABS
SLOW RELEASE TABLETS

A MICROBIOCIDE, BACTERICIDE, FUNGICIDE, ALGAECIDE AND SLIMICIDE, USED IN TREATING WATER FOR INDUSTRIAL RECIRCULATING and EVAPORATIVE COOLERS, BASEMENT SUMPS, AIR CONDITIONING PANS, COOLING PONDS, LINED RESERVOIRS, DECORATIVE FOUNTAINS, AIR WASHING SYSTEMS, RO MEMBRANES AND METAL WORKING FLUIDS

ACTIVE INGREDIENT:
2,2-dibromo-3-nitrilopropionamide. 95.6%
INERT INGREDIENTS. 4.4%
TOTAL. 100.0%

KEEP OUT OF REACH OF CHILDREN
DANGER

See side panels for additional precautionary statements

FIRST AID	
If in eyes	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
If inhaled	• Move person to fresh air • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible • Call a poison control center or doctor for further treatment advice
If on skin or clothing	• Take off contaminated clothing • Rinse skin immediately with plenty of water for 15-20 minutes • Call a poison control center or doctor for treatment advice
If swallowed	• Call poison control center or doctor immediately for treatment advice • Have person sip a glass of water if able to swallow • Do not induce vomiting unless told to do so by the poison control center or doctor • Do not give anything by mouth to an unconscious person
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. **YOU MAY ALSO CONTACT 1-800-420-9736 FOR EMERGENCY MEDICAL TREATMENT INFORMATION**	
NOTE TO PHYSICIAN "Probable mucosal damage may contraindicate the use of gastric lavage."	

MANUFACTURED BY:
Enviro Tech Chemical Services, Inc.
500 Winmoore Way, Modesto, CA 95358
(209) 581-9576

EPA Reg. No. 63838-~~RA~~ 16 EPA Est. No.

NET CONTENTS: _____. (LBS.)

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. CAUSES SKIN BURNS. PROLONGED OR FREQUENTLY REPEATED SKIN CONTACT MAY CAUSE ALLERGIC REACTIONS IN SOME INDIVIDUALS.

PERSONAL PROTECTIVE EQUIPMENT

Applicators and other handlers must wear:

- Coveralls worn over long sleeved shirt and long pants
- Chemical resistant footwear plus socks
- Goggles (required) with or without face shield
- Chemical resistant gloves (such as barrier laminate, neoprene rubber, nitrile rubber, or PVC)
- Chemical resistant apron (for mixing/loading)

APPLICATION RESTRICTIONS: Do not apply this product in a way that will contact workers or other persons, either directly or through drift. Only protected handlers may be in the area during application.
ENGINEERING CONTROLS: When handlers are using closed metering systems the handler requirements may be reduced or modified to long-sleeved shirt, long pants, shoes and socks.

USER SAFETY REQUIREMENTS: Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

USER SAFETY INSTRUCTIONS: Users must wash hands before eating, drinking, chewing gum, using tobacco, or using toilet. User must remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of waste. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
NOV 21 2011

043 EB Tabs V1

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 63838-16

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.
STORAGE: To maintain product quality, store at temperatures below 95°F (35°C). Keep container tightly closed when not in use. Do not remove tablet(s) from container except for immediate use. Do not store with foods, feeds, drugs, or clothing.
DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use, according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
CONTAINER DISPOSAL: Nonrefillable container. Do not use this container to hold materials other than pesticides or dilute pesticides (rinsate). After emptying and cleaning, it may be allowable to temporarily hold rinsate or other pesticide-related materials in the container. Contact your state regulatory agency to determine allowable practices in your state. Clean container promptly after emptying. Offer for recycling if available.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

DIRECTIONS: FOR RECIRCULATING COOLING:
NOTE: Badly fouled systems must be pre-cleaned by following manufacturer's product instructions before treatment is begun. Direct contact of Enviro-Brom Tabs with a metal surface in the cooling system will cause local corrosion. To prevent corrosion, place the Enviro-Brom Tab(s) in the holder provided or equivalent. Suspend / float it in the water so the tablet is completely submerged. Enviro-Brom Tabs are best used in the basin of the cooling system in an area with little turbulence. Avoid placing Enviro-Brom Tabs in direct sunlight. Tablets may be placed in a flow-through feeder through which cooling water or make-up water is directed.
To control bacteria, fungi, and algae in clean to moderately contaminated systems, add 100 g of tablet(s) per 500-1,000 gallons of water in the system. Heavily contaminated systems may require 200 g of tablet(s) per 500-1,000 gallons of water in the system.

DIRECTIONS: FOR EVAPORATIVE COOLERS (e.g. SWAMP COOLERS), BASEMENT SUMPS & AIR CONDITIONING PANS:
NOTE: Badly fouled systems must be pre-cleaned by following manufacturer's product instructions before treatment is begun. Direct contact of Enviro-Brom Tabs with a metal surface in the cooling system will cause local corrosion. To prevent corrosion, place the Enviro-Brom Tab(s) in the holder provided or equivalent. Suspend / float it in the water so the tablet is completely submerged.
To control bacteria, fungi, and algae add one 20 g tablet per 5 gallons of contained water.

DIRECTIONS: COOLING PONDS, LINED RESERVOIRS AND DECORATIVE FOUNTAINS:
To prevent corrosion, place the Enviro-Brom Tab(s) in the holder provided or equivalent. Suspend / float it in the water so the tablet is completely submerged. This product may be applied at the lined reservoir, pond, or fountain inlet or at a location that permits complete diffusion into the water at maximum retention time before reaching the outlet. To control bacteria, fungi, and algae in clean to moderately contaminated systems, add 100 g of tablet(s) per 500-1,000 gallons of water in the system. Heavily contaminated systems may require 200 g of tablet(s) per 500-1,000 gallons of water in the system.

DIRECTIONS: AIR WASHER SYSTEMS:
Badly fouled systems must be cleaned before treatment is begun. Only use this product in industrial air washer systems that maintain effective mist eliminating components. To control slime forming bacteria and fungi add 100 g of tablet(s) per 500-1,000 gallons of water in the system. When the system is noticeably fouled, add 200 g of tablet(s) per 500-1,000 gallons of water in the system.

DIRECTIONS: NON-POTABLE WATER REVERSE OSMOSIS SYSTEMS
This product may be used to control bacteria and reduce biofouling in industrial membrane systems, including UF and NF systems. Acceptable applications include boiler feedwater, wastewater, electronics and industrial membrane systems. Add 100 g of tablet(s) per 500-1,000 gallons of water. When the system is noticeably fouled, add 200 g of tablet(s) per 500-1,000 gallons of water in the system.

DIRECTIONS: TREATING METAL WORKING FLUIDS
This product is an effective antimicrobial treatment for metal working and lubricating fluids that are water soluble. The point of addition of this product is recommended at the fluid collection tank. Add 100 g of tablet(s) per 500-1,000 gallons of water. When the system is noticeably fouled, add 200 g of tablet(s) per 500-1,000 gallons of water in the system.