E-100™

Sewer and Drain Cleaning Compound

Read entire label • Si no entiende esta etiqueta, pida a alguien que sepa ingles que se la explique antes de usar.

FORMULATED FOR SEWER LINES, INDUSTRIAL DRAINS, GREASE TRAPS, AND LIFT STATIONS

E-100™ compound is an exceptional formulation that quickly cleans sewer lines, lift stations, and industrial drains of grease and oil. Contains chemicals and metallic chips to saponify and remove grease. Contains a trace dye to simplify effectiveness checking. If color traces appear downstream in the system, lines are free-flowing.

Produces even heat over a long period of time and attacks stoppages further down the line. When used regularly, E-100™ will aid in preventing problems caused by grease, oil, fiber, sludge, and organic matter; yet it will not injure pipes or plumbing lines. It requires no mixing.

Suitable for use as a sewer and drain cleaner in U.S. Federally inspected meat and poultry plants.

DIRECTIONS FOR USE

KEEP THE CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

DANGER: THIS PRODUCT MAY REACT WITH MATERIALS IN THE SEWER TO FORM POTENTIALLY HAZARDOUS GASES. VIOLENT ERUPTIONS, HARMFUL GASES OR CORROSIVE SPLASHBACK COULD RESULT!

1. **KEEP YOUR FACE AWAY WHEN APPLYING THIS PRODUCT.** Do NOT stand over or look into the drain or opening immediately after applying this product as corrosive splashback can result in severe burns.
2. To avoid splattering, excessive heat, and pressure, add the product slowly to cold water in the line. Do NOT add to hot water.
3. Do NOT use the product in drain lines where acid cleaners have recently been used or where acid waste products have accumulated.
4. Store in a well-ventilated area. Avoid contact with combustible materials. Drying of undiluted product on clothing or combustible materials may cause fire. Never return unused product to the original container. Storage and transfer equipment should be made only of glass or plastic. Do not use brass, copper, nickel, iron, bronze, synthetic rubber or polypropylene. Store this product away from other chemicals.

LIFT STATIONS: Aids in the removal of grease from floats, walls and pump inlets. Apply at a time of low flow in order to give maximum time for the product to work. Wait until the water is at its lowest level. Shovel or pour approximately 25 pounds of the product in such a way that it contacts the areas that are blocked or coated with grease. If a larger amount is needed, a 50-pound application may be used.

MUNICIPALITIES: Shovel or pour approximately 25 pounds of the product into strategically located manholes. If a larger amount should be needed, a 50-pound application may be used.

INDUSTRY: In food processing or meat packing facilities, pour or shovel 10 to 20 pounds of the product into grease traps and drains. In other industrial drains, only 1 to 2 pounds is necessary.

For drain pipes or clean-outs, use approximately 1 pound per inch of drain diameter. Example: For a 2-inch pipe, use 2 pounds of product. For a 4-inch pipe, use 4 pounds, etc.

NOTE: 1 pound of product is approximately 2 cups (1 pint).

STORAGE: Store in a cool, dry place. Keep the container tightly closed when not in use. Avoid exposure to areas of moisture and high humidity as product activation can occur. Store in a corrosion-resistant container. Absorb spillage to prevent damage.

DANGER: MAY INTENSIFY FIRE; OXIDIZER • CAUSES SEVERE SKIN BURNS AND EYE DAMAGE • HARMFUL IN CONTACT WITH SKIN • HARMFUL IF SWALLOWED • MAY BE CORROSIVE TO METALS

Contains Sodium hydroxide, Aluminum powder and Sodium nitrate. Keep away from heat. Take any precaution to avoid mixing with combustibles. Wear protective gloves, protective clothing, eye protection and face protection. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust. Do not eat, drink or smoke when using this product. 5 % of the mixture consists of ingredient(s) of unknown toxicity.

FIRST AID

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation occurs, get medical attention. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a physician.

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a physician if unwell.

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.

KEEP OUT OF REACH OF CHILDREN

See the Safety Data Sheet for more information.

For medical or environmental emergencies, call CHEMTREC® at 1-800-424-9300.

Not for Resale

MADE IN THE U.S.A.

4416FGBA

1M706

CHEMSEARCH FE A Division of NCH Corporation
2727 Chemsearch Blvd., Irving, Texas 75062
www.chemsearchfe.com • ©2017 NCH Corporation

NET WEIGHT: _____

CSPA Product Care®

CHEMSEARCH® FE™

QUALITY ISO 9001 ASSURANCE

TO REORDER, Call TOLL-FREE:
1-800-527-9921
FAX: 1-800-456-0010

DISPOSAL
Dispose of contents and container in accordance with applicable regulations.

12044195

SPECIMEN