CRC

HYDRO FORCE®

Drain Re-Nu™

Quickly Unclogs Drains
Easy to Measure Spout

No. 14125

1 gal. (3.78 L)

For professional use only. This product is not packaged for retail sale or household use.

CRC Drain Re-Nu™

DIRECTIONS: ***Read entire label before using this product.***

1. For use on clogged or slow-running drains, measure 4-8 oz. and pour slowly over the drain. (8 oz. for clog, 4 oz. for slow running drains.)
2. Allow to work for 15 minutes. For tough problems, allow 30 minutes.
3. Flush with hot water. Repeat steps one, two, and three if clog persists.
4. For garbage disposal drains, follow steps two through four. If drain does not clear, do not turn on disposal since HydroForce® Drain Re-Nu™ may splash back. Consult plumber.

Danger
May be corrosive to metals. Causes severe skin burns and eye damage.

Precautionary Statements
Do not breathe mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Absorb spillage to prevent material damage. Store locked up. Keep and store only in original container. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid
If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor.

Contains Sodium hydroxide (1310-73-2), Sodium hypochlorite (7681-52-9) and Water (7732-18-5). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

©2014 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in U.S.A. 14A

800-521-3168 (Technical Information)
800-272-4620 (Customer Service)
215-442-6260 (SDS)

0
2 1
B

0 78254 14125 1