## DIRECTIONS

The dosage is dependent upon the make-up of the water, the system and the cycle of concentration being used. Each system should be considered a special application. In most areas, for a system up to 300 tons, 1/2 to 1 gallon of product per 12 hours of operations. If water hardness is moderate or soft, less product is needed. Adjust bleed-off to operate between 4 to 8 cycles of concentration.

Regular sampling of water and recommendations from technician are necessary to maintain proper operation.

# ALL TOWER TREAT

**03-8963-5**

Manufactured for
Liquid Solutions LLC
PO Box 677
Magee, MS 39111

**Concentrated liquid formulated to remove scale and corrosion in open recirculating cooling towers**

**FOR COMMERCIAL,INSTITUTIONAL AND INDUSTRIAL USE ONLY**

**KEEP OUT OF REACH OF CHILDREN**

**DANGER: CAN CAUSE EYE AND SKIN BURNS.**

**PRECAUTIONARY MEASURES:**
Contains Potassium Hydroxide. Do Not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.
FIRST AID: In case of contact, flush eyes or skin with water for 15 minutes. Remove contaminated clothing. Seek medical attention immediately. If ingested, DO NOT induce vomiting. Drink a glass of water. Do not give anything by mouth to an unconscious person. Seek medical attention
IN CASE OF SPILL: Absorb and properly dispose of waste.

See Material Safety Data Sheet (MSDS)

## DIRECTIONS

The dosage is dependent upon the make-up of the water, the system and the cycle of concentration being used. Each system should be considered a special application. In most areas, for a system up to 300 tons, 1/2 to 1 gallon of product per 12 hours of operations. If water hardness is moderate or soft, less product is needed. Adjust bleed-off to operate between 4 to 8 cycles of concentration.

Regular sampling of water and recommendations from technician are necessary to maintain proper operation.

# ALL TOWER TREAT

**03-8963-5**

Manufactured for
Liquid Solutions LLC
PO Box 677
Magee, MS 39111

**Concentrated liquid formulated to remove scale and corrosion in open recirculating cooling towers**

**FOR COMMERCIAL,INSTITUTIONAL AND INDUSTRIAL USE ONLY**

**KEEP OUT OF REACH OF CHILDREN**

**DANGER: CAN CAUSE EYE AND SKIN BURNS.**

**PRECAUTIONARY MEASURES:**
Contains Potassium Hydroxide. Do Not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.
FIRST AID: In case of contact, flush eyes or skin with water for 15 minutes. Remove contaminated clothing. Seek medical attention immediately. If ingested, DO NOT induce vomiting. Drink a glass of water. Do not give anything by mouth to an unconscious person. Seek medical attention
IN CASE OF SPILL: Absorb and properly dispose of waste.

See Material Safety Data Sheet (MSDS)