DESCRIPTION: STONE is a sealer finish formulated specifically for marble, natural stone and other nonresiliant floors. This product provides the ultimate in gloss and protection to worn or dull floors while protecting against chemical spills and traffic. Excellent adhesion allows burnishing with both conventional and high speed equipment. Easy to apply and maintain, this formulation actually enhances the natural grain and appearance of the stone or non-resilient surface. Its extended durability and extra protection are particularly recommended for high traffic areas such as lobbies, malls, corridors, and supermarkets. This product is non-yellowing, nonflammable and VOC compliant.

QC SUPPLY, LLC
574 Road 11
Schuyler, NE 68661
PHONE (800) 433.6340

CASCO

C-STONE

SAFETY: CAUTION: PRODUCTS CONTAINS EMULSIFIERS WHICH MAY CAUSE EYE IRRITATION. AVOID CONTACT WITH EYES

FIRST AID: Skin: Flush with water. Seek medical attention if irritation persists. Eyes: Flush with large quantities of water. Seek medical attention if irritation persists.
Ingestion: Dilute with two glasses of water. Seek medical attenlion if symptoms persist.

INGREDIENTS: Water: Acrylic Copolymer: Polyethylene wax emulsion; Tribuloxyelhyl phosphate; Diethylene glycol methyl ether.

NPCA HAZARDOUS MATERIALS I.D. SYSTEM
HEALTH 1 FLAMMABILITY 0 REACTIVITY 0 PERSONAL PROTECTION A

DIRECTIONS FOR USE: Read the entire label before using this product.

1. Remove all old wax and floor finish using recommended stripper. Be sure to follow directions. This step is very important for new, highly polished marble where residue of the factory polishing process may be present. NOTE: Use the least aggressive pad possible to maintain the marble's original polished appearance. A red pad should be sufficient. Do not use a black pad on polished marble.
2. Detail mop to assure no alkaline residue is left on floor.
3. Apply sealer/finish in thin to medium uniform coats and allow to dry (approximately 30-45 minutes depending on the humidity and temperature of the facility). Apply additional coats in the same manner.
   - For marble, quarry tile, and ceramic tile; 3-4 thin coats are recommended.
   - For terrazo and concrete type floors: 4-6 coats are recommended.
4. Maintain floor by damp mopping with a neutral cleaner. When burnishing, a compatible restorer is recommended for lubrication.