Easy to use - Economical
Highly Concentrated - Safe

CS-590 should be used when normal mechanical and chemical adjustments fail to control foam. This product is designed to rapidly dissipate and control foam in chemical and detergent washing applications, agitation operations, high pressure and hot solution applications, automatic wash machine operations, and chemical extraction operations. Excellent for controlling foam in wet vacuum tanks and tray wash tanks. Also recommended in all industrial cleaning where dissipation of foam is required.

QC Supply, LLC
574 Road 11
Schuyler, NE 68661
Phone (800) 433.6340

All responsibility for the proper use, storage, and handling of this product is the responsibility of the buyer. Casco Products Company, Inc. makes no other claims or warrantees, expressed or implied.

CASCO

CS-590

DE-FOAM COMPOUND

CONTROLS FOAM

SAFE TO USE

CAUTION:

KEEP OUT OF REACH OF CHILDREN

DIRECTIONS:

Start with adding 1 oz. CS-590 per 120 gal. solution. Depending on type of foaming problem, increase rate of foam dissipation by continuously adding increments of 1 oz. CS-590 until desired results are achieved. The exact amount of this product necessary to dissipate foam depends on amounts and types of foaming agents in the solution.

Automatic Tray Wash Machine:
A low foaming detergent should be used in accordance with machine manufacturer's recommendations. As foam levels approach unacceptable levels CS-590 should be added at the rate of 1 oz. increments until desired results are obtained. CS-590 should be added through the inlet side of the machine.

Net Contents:

CS-590 Defoam

CS-590
Product Code

Precautions:

QC SUPPLY, LLC
574 Road 11, Schuyler, NE 68661
Phone (800) 433.6340