DIRECTIONS FOR USE: ***Read the entire label before using this product.*** Remove soil and dust mop the floor. Spray a light mist of product on the floor in front of the floor machine. DO NOT OVERWET. Using a nylon or polyester spray buff pad, buff the floor where the fine mist of spray buff has been applied. Flip or change pad as necessary. After spray buffing the floor is completed, dust mop the floor if dust is still present. ***NOTE: In order for spray buff to work correctly, three or four base coats of floor finish must be applied before using spray buff in order to achieve maximum gloss and wear properties.*** Heavy traffic areas may require dust mopping, followed by damp mopping, followed by spray buffing. Use of this spray buff will eliminate powdering and will never yellow the floor. ***NOTE: Slip resistance meets or exceeds standard, (ASTM D 2047-11) James Machine 0.5 minimum.***

Caution: May cause eye irritation. Contains Ethylene glycol. Avoid contact with eyes. Wash thoroughly after handling. Do not ingest.
FIRST AID: If splashed in eyes, flush with large quantities of water. Call a physician if irritation persists. If swallowed, do not induce vomiting. Rinse out mouth with water. Call a physician.

INGREDIENTS (CAS No.): Water (7732-18-5); Ethylene Glycol (107-21-1); Nonionic Surfactant (68439-46-3); Acrylic Copolymer Dispersion (N/A); Tetrasodium EDTA (64-02-8).

KEEP FROM FREEZING

Sold by: Jackson Newell PAPER COMPANIES

www.newellpaper.com

Made in USA

RLB4343

JACKSON, MS	COLUMBUS, MS	1212 GRAND AVENUE MERIDIAN, MS 39301	HATTIESBURG, MS	DEMOPOLIS, AL
800-844-5449	800-844-1467	800-844-8894	800-530-7537	800-652-2768

0560815

New-Jax

SHINE ON

Thermoplastic Spray Buff

See Cautions and First Aid on side panel.
KEEP OUT OF REACH OF CHILDREN.
FOR INSTITUTIONAL AND COMMERCIAL USE.

1 US gal (3.78 L)