New-Jax

PRIME KOTE

Metal Interlocked Acrylic Polymer Floor Sealer

See Cautions and First Aid on back panel.
KEEP OUT OF REACH OF CHILDREN.
FOR INSTITUTIONAL AND COMMERCIAL USE.

5 US gal (18.9 L)

RLB4341 0560715

⚠ WARNING
ATENCIÓN

Children can fall into bucket and drown.

Keep children away from buckets with even a small amount of liquid.

Los niños pueden caerse en el balde y ahogarse.

Mantenga los niños alejados de baldes, incluso los que solo contienen una pequeña cantidad de liquido.

RLB4342

New-Jax

PRIME KOTE
Metal Interlocked Acrylic Polymer Floor Sealer

DIRECTIONS FOR USE: ***Read the entire label before using this product.*** Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces. This product is of specific benefit in preparing old, worn or porous tile floors for finishing. RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply sealer in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. A minimum of 2 coats of sealer is recommended. This sealer can be used as a finish coat, however, for a better shine, increased protection and easier maintenance, we recommended the application of 2 - 4 coats of a floor finish that best fits your maintenance program. Please recycle empty containers. ***Note: Slip resistance meets or exceeds standard, (ASTM D 2047-11) James Machine 0.5 minimum.***

Caution: May cause eye irritation. Contains Glycol Ether. Avoid contact with eyes. Wash thoroughly after handling. Do not ingest.

FIRST AID: EYES: Flush with large quantities of water. Call a physician if irritation persists. INGESTION: Do not induce vomiting. Rinse out mouth with water. Call a physician.

INGREDIENTS (CAS No.): Water (7732-18-5); Acrylic Polymer (N/A); Diethylene Glycol Ethyl Ether (111-90-0); Tributoxyethyl Phosphate (78-51-3); Polyethylene Wax Emulsion (N/A).

KEEP FROM FREEZING

Sold by: Jackson Newell PAPER COMPANIES

www.newellpaper.com

JACKSON, MS 800-844-5449

COLUMBUS, MS 800-844-1467

1212 GRAND AVENUE MERIDIAN, MS 39301 800-844-8894

HATTIESBURG, MS 800-530-7537

DEMOPOLIS, AL 800-652-2768

Made in USA

0560715