Buckeye®

R.P.M.™

FINISH ENHANCER

Buckeye R.P.M. is a Buffable Floor Finish Enhancer, for use on resilient and non-resilient floors. **R.P.M.** is used with floor machines 1000 rpms or greater.

CLASSIFIED UL

FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE

DIRECTIONS FOR USE

FLOOR PREPARATION

1. Remove gum, tape or other foreign material from floor.
2. Dust mop floor.
3. Damp mop or lightly scrub floor.

☐ Concentrated Product Sample ☐ Diluted Product

•NOT FOR SALE• _____ DILUTION

APPLICATION:

MOP ON METHOD:

1. Dilute one quart **R.P.M.**/gallon of cold water, (250 ml/l), (1:4) in a mop bucket.
2. Damp mop solution onto floor. When floor is dry, buff.
3. To increase gloss, periodically spray a fine mist of water onto buffing pad.

AUTOSCRUBBER METHOD:

1. Dilute 12 fluid ounces of **R.P.M.**/gallon of cold water (100 ml/l), (1:10) in the autoscrubber.
2. Scrub floor. When floor is dry, buff.

NOTE: See catalog sheet for other applications and directions.

HAZARD & PRECAUTIONARY STATEMENTS: May cause slight eye and skin irritation. Avoid contact with eyes and skin. Store locked up.

FIRST AID: *For eyes:* Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician if irritation persists. *For skin:* Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician. *For inhalation:* Remove to fresh air. *For ingestion:* Give two large glasses of water. Do NOT induce vomiting. Call physician. For medical emergencies only, call 800-303-0441. Outside North America call 651-632-8956.

CONTAINS: Water, Acrylic emulsion CAS# Blend, Polyethylene emulsion CAS#67892-91-5,and Linear primary alcohol ethoxylate CAS# 34398-01-1.

SEE SAFETY DATA SHEET
KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY
KEEP FROM FREEZING

Mfg. by **Buckeye International, Inc.**
2700 Wagner Place • Maryland Heights • MO 63043 • USA
314.291.1900 • www.buckeyeinternational.com

1792 (7/15)