Buckeye®

PROCLAIM®

CONCRETE FLOOR COATING

Buckeye PROCLAIM is a water-based urethane fortified floor coating, designed to protect hard surface areas, while providing a slip resistant surface. It also improves the appearance and cleanability of the floor surface. May be used on concrete, terrazzo, quarry, ceramic, natural stone, resilient tile and marble.

DIRECTIONS FOR USE

FLOOR PREPARATION:

FOR FRESHLY-POURED CONCRETE FLOORS: 1. Allow new floor to set-up 30 days, to ensure proper cure. 2. Scrub floor using Buckeye **Blue** at 2 oz. per gallon of cold water (16 ml/l), (1:64). 3. Rinse well. Be sure to scrub the floor with your rinse water. Pick up residue and allow floor to dry. 4. Apply a coat of **Cirene** using a traditional floor finish mop. Be sure to move slowly and deliberately with the mop head in order to achieve a good uniform look. Due to the alkalinity of concrete, any remaining finish in the bucket after the first coat should be discarded. The mop head itself should be thoroughly rinsed or a fresh mop head should be used for the second coat. Allow the first coat to dry to tack free and apply a second coat of **Cirene**. 5. When the **Cirene** has dried to tack free, using a fresh mop head, begin applying **Proclaim**.

CLASSIFIED UL

FLOOR COATING AND FINISHING MATERIAL, AS TO SLIP RESISTANCE ONLY. 169S

☐ Concentrated Product Sample

☐ Diluted Product

•NOT FOR SALE•

_____ DILUTION

The dry time for both products will be affected by temperature and humidity Be certain the floor is tack free before applying additional coats.

FOR PREVIOUSLY WATER-BASED SEAL COATED FLOORS: 1. Strip floor using Buckeye **Juggernaut®**, following label directions. 2. Be sure to scrub the floor well with your rinse water. Pick up residue and allow floor to dry. 3. Apply **Cirene** and **Proclaim** as indicated above.

APPLICATION: 1. Use a clean mop and bucket or applicator. 2. Saturate mop and press firmly into wringer to remove excess **Proclaim**. Do not wring mop. 3. Apply **Proclaim** using an overlapping figure-eight motion. NOTE: The first coat on porous floors should be applied medium to heavy. 4. Allow to dry (usually 30 to 40 minutes). Temperature, humidity and air movement affect dry time. 5. Apply additional coats until desired gloss is achieved. Apply no more than four (4) coats in a 24-hour period. 6. Allow **Proclaim** to properly cure for 48 hours before scrubbing.

MAINTENANCE: 1. Dust mop floor. 2. Damp mop or autoscrub floor as needed, using Buckeye **Crossbow®**, **Straight-Up®**, **Blue**, or **Two-O-One™**, following label directions. 3. Top scrub and recoat, as needed. **Note:** Do not put used product back into its original container! **Note:** Not recommended for kitchen floors or on floors that remain wet for long periods of time.

DANGER

HAZARD & PRECAUTIONARY STATEMENTS: May damage fertility or the unborn child. Use personal protective equipment as required. If exposed or concerned: Get medical attention. Store locked up.

FIRST AID: *For eyes:* Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician if irritation persists. *For skin:* Wash with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse. *For inhalation:* Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician if you feel unwell. *For ingestion:* Give two large glasses of water. Do NOT induce vomiting. Call physician. For medical emergencies only, call 800-303-0441. Outside North America call 651-632-8956.

CONTAINS: Diethylene glycol ethyl ether CAS# 111-90-0, Water, Acrylic emulsion CAS# 25987-66-0, Polyethylene copolymer emulsion CAS# 67892-91-5 and Polyurethane aqueous dispersion CAS# Blend.

SEE SAFETY DATA SHEET • KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

KEEP FROM FREEZING

Mfg. by **Buckeye International, Inc.**
2700 Wagner Place • Maryland Heights • MO 63043 • USA
314.291.1900 • www.buckeyeinternational.com

1984 (11/16)