Buckeye®

Contains LIQUESCENT® Patented

RiPSAW™

floor stripper

Water based stripper for floor finishes and sealers.

DIRECTIONS FOR USE

FOR USE IN COLD OR HOT WATER

For Removing Floor Finishes and sealers:

Using ***ADI***® (Automatic Dilution Indicator) add **RipSaw** to water in mop bucket until it turns cloudy, which is approximately 32 fl. oz./gallon water (250 ml/l), (1:4).

1. Wet floor. Allow to stand 10 minutes. Do not allow to dry on floor. 2. Machine scrub. 3. Pick up solution. 4. Rinse floor at least twice with cold water. 5. After floor is dry, apply finish.

Product produced under one or more of the following U.S. Patents: 5,080,822; 5,080,831; 5,158,710; 5,419,848; 5,585,341; 5,849,682. Canada Patents: 2,056,425; 2,080,352; 2,057,027.

☐ Concentrated Product Sample ☐ Diluted Product

•NOT FOR SALE• _____ DILUTION

DANGER

HAZARD & PRECAUTIONARY STATEMENTS: May be harmful if swallowed. Causes severe skin burns and eye damage. Do not breathe mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/ eye protection/~~face protection.~~ Store locked up.

FIRST AID: *For eyes:* Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention. *For skin:* Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and wash before reuse. Get medical attention if irritation develops and persists. *For Inhalation:* Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or physician. *For ingestion:* Rinse mouth. Give two large glasses of water. Do NOT induce vomiting. Call physician immediately. For medical emergencies only, call 800-303-0441. Outside North America call 651-632-8956.

CONTAINS: Ethanolamine CAS #141-43-5, Sodium Metasilicate CA # 6834-92-0, Sodium Hydroxide CAS # 1310-73-2, Water, Benzyl alcohol CAS# 100-51-6 and Ethylene Glycol Phenyl Ether CAS# 122-99-6.

SEE SAFETY DATA SHEET • KEEP OUT OF REACH OF CHILDREN FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

~~NOTE: PRODUCT IS WHMS CLASS E.~~

RISQUES & PRÉCAUCION STATEMENTS: Peut etre nocif si avalé. Cause des brûlures graves à la peau et des dommages aux yeux. Ne pas respire brume/vapeurs/pulvériser. Se laver à fond le visage, les mains et toute peau exposée après la manipulation. Porter des gants/vêtements/lunettes de protection/~~un écran facial.~~ Ranger sous verrou.

PREMIERS SOINS: *Contact avec les yeux :* Rincer soigneusement à l'eau pendant plusieurs minutes. Enlever les lentilles cornéennes, si elles sont présentes et faciles à enlever. Continuer à rincer. Obtenir une attention médicale immédiate. *Contact avec la peau:* Laver immédiatement à grande eau pendant au moins 15 minutes. Enlever les vêtements contaminés et les laver avant de les réutiliser. Obtenir de l'aide médicale si dévellope et persiste. *En cas d'inhalacion:* Déplacer la victime à l'air frais et la garder dans une position qui lui permet de respirer confortablement. Obentir une attention médicale immédiate. *En cas d'ingestion:* Rincer la bouche. Faire boire deux grands verres d'eau. NE PAS faire vomir. Appeler un médecin immédiatement. Pour urgences médicales seulement, appeler au 800-303-0441. À l'extérieur de l'Amérique du Nord, appeler au 651-632-8956.

CONTIENT: Éthanolamine no CAS 141-43-5, Métasilicate de sodium pentahydraté n° CAS 6834-92-0, Hydroxyde de sodium n° CAS 1310-73-2, eau, Alcool benzylique no CAS 100-51-6 et Éther de phényle de l'éthyléneglycol n° CAS 122-99-6.

VOIR LA FICHE SANTÉ SÉCURITÉ • GARDER HORS DE PORTÉE DES ENFANTS DESTINÉ UNIQUEMENT À L'USAGE INDUSTRIEL ET INSTITUTIONNEL.

~~REMARQUE: LE PRODUIT APPARTIENT À LA CLASSE E DU SIMDUT.~~

Mfg. by

Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • MO 63043 • USA

800.321.2583 • www.buckeyeinternational.com

2236 (7/15)