03-8563-5

NO FLOAT 40

DESCRIPTION

NO FLOAT 40 is formulated from distilled organic plant and vegetable materials and petroleum distillates. It is designed to keep all drains, lift stations, grease traps, and garbage disposal units clean, deodorized and free flowing. The regular use of this product will eliminate manual cleaning of drains and disposals.

NO FLOAT 40 is also extremely effective product for controlling odors is sewage treatment plants and dumpsters, garbage receptacles and refuse dumps.

It is readily water emulsifiable and has extremely high solvency characteristics.

CAUTION: COMBUSTIBLE MATERIAL

Should be stored in a cool place away from exposure to extreme heat & open flames. Avoid contact with skin & eyes.

FIRST AID: EYES- Flush with cool water. If irritation develops get medical attention.

SKIN- Contact can de-fat skin. Wash with soap and water.

DRAIN, DISPOSAL, DEODORANT & SEWER PLANT MAINTAINER

- **Degreases & Deodorizes**
- **Non-Acid, Non-Caustic, Non-Corrosive**

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

LIQUID SOLUTIONS LLC
P.O. BOX 677
MAGEE, MS 39111

DIRECTIONS

DRAINS: Used in a weekly drain maintenance program. **NO FLOAT 40** will keep drains free flowing & sanitary. Weekly, add 3 to 4 ounces to each drain. Let stand for 5 to 10 minutes. If the drain is slow, repeat the regular maintenance dose every 2 to 3 days until unit is flowing freely.

GARBAGE DISPOSALS: Add 3 to 4 ounces plus 2 cups of water. Let stand 15 to 20 minutes, and then operate the disposal thru a cycle.

SEWAGE PLANTS: Effectively controls odors in dilution as low as 0.5 PPM or ½ ounce per 800 gallons of water. Dispensed thru Driptol Dispenser directly into effluent, it reduces build-up of grease & slime without effecting bacterial activity.

CLEANING & DEGREASING: Use straight. Soak, spray, or wipe on. Allow time to penetrate, depending on degree of soil and flush off with water, under pressure, if available.