TECHNICAL DATA SHEET

CLR PRO® CALCIUM, LIME, RUST REMOVER

DESCRIPTION:
CLR PRO® Calcium, Lime & Rust Remover is a fast and effective way to clean away calcium, lime, and rust deposits.

FEATURES & BENEFITS:

- Powerful formula removes calcium and lime buildup, rust, mineral deposits, hard water stains, soap scum and oxidation
- EPA's Safer Choice is the U.S. government's third-party certification for environmentally responsible products
- Non-toxic, non-abrasive, non-corrosive formula
- Biodegradable—safe on all plumbing including copper and plastic PVC
- Complies with LEED Green building and environmentally preferable product purchasing requirements
- Made of materials derived from plants. Contains no bleach, ammonia, or phosphorous
- Safe on surrounding vegetation
- NSF Non-Foods Certified—approved for use in food processing, food storage, and food service facilities
- Certified Kosher

USE ON THESE SURFACES:

PORCELAIN	BRICK	BRASS
STAINLESS STEEL	GLASS	PVC/PLASTIC
CHROME	FIBERGLASS	COPPER
CONCRETE	VINYL	

DIRECTIONS FOR USE:

- Spot test on an inconspicuous area before applying. Dilution and dwell time may vary by soil load. Use in a well-ventilated area
- Apply product directly to the stain with a brush, cloth, or sponge. After 2 minutes, rinse promptly with cold water. Repeat application as needed

For light soils: mix 1 part CLR and 8 parts warm water

For medium soils: Mix equal parts (1:1) CLR and warm water

For heavy soils: Use full strength CLR

Product	Size	Stock #
CLR PRO® Calcium, Lime, Rust Remover	1 Gal.	CL-4PRO
CLR PRO® Calcium, Lime, Rust Remover	5 Gal.	CL-5PRO
CLR PRO® Calcium, Lime, Rust Remover	55 Gal.	CL-55PRO

Safety: See label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application, handling, and disposing. SDS is available online at ***www.clrpro.com.***

PHYSICAL & CHEMICAL PROPERTIES

Appearance	Crystal clear, lime green liquid
Odor	Slightly acidic
Odor Threshold	N.D.
pH @20°C	2.05-2.30
Melting Point	N.D.
Freezing Point	N.D.
Boiling Point	99°C / 210°F
Boiling Point Range	N.A.
Flash Point	None
Evaporation Rate	N.D.
Flammability	Not Flammable
Upper/Lower Flammability	N.A.
Vapor Pressure @20°C	N.D.
Vapor Density (mm Hg)	N.D.
Relative Density	1.040 – 1.060
Solubility in Water	100%
Partition Coefficient; n-octanol/water	N.D.
Auto Ignition Temperature	N.A.
Decomposition Temperature	N.A.
Viscosity	N.D.

SAFER CHOICE Meets U.S. EPA Safer Product Standards

NSF

CLR PRO® jelmar

5550 West Touhy Avenue, Suite 200, Skokie, IL 60077
1-800-323-5497 • sales@jelmar.com