



Slip Resistant Floor Cleaner + Treatment

Anti-Slip for use on unsealed porous concrete, ceramic, brick, diamond plate and porcelain surfaces

- Reduces Potential for Slips & Falls
- Increases Slip Resistance
- Self-Applied
- Non-Hazardous
- Two-in-One; Safety & Cleaning at the Same Time
- Reduces Costs



Nonfood Compounds
Program Listed A4
123398



FLOOR COATING AND
FINISHING MATERIAL
AS TO SLIP RESISTANCE ONLY
8L30



4800 SW Meadows Suite 300
Lake Oswego, OR 97035
(800) 876-2232 • (503) 699-1335
www.saf-t-step.com

FOR ADDITIONAL INFORMATION:



SAF-T-STEP®
PRODUCTS

SAF-T-STEP®

SAF-T-STEP® Slip Resistant Cleaner and Treatment

Restoration “Shock” Slip Treatment Procedure (As Needed)

Use SAF-T-STEP® Slip Resistant Treatment full strength whenever floor surface is out of control with heavy stains or grease buildups. Pretest glazed tile floors before using. NOTE: On new floors or lightly soiled floors, SHOCK cleaning procedure is not recommended; use DAILY slip treatment.

Maintenance Slip Treatment and Cleaning Procedures

Daily Cleaning: Dilute 2 to 4 ounces SAF-T-STEP® per gallon of water.

Weekly Heavy Scrub: Dilute 12 ounces SAF-T-STEP® per gallon of water.

Monthly Heavy Scrub: Dilute 48 ounces SAF-T-STEP® per gallon of water.

If using an auto tank scrubber, add defoamer to recovery tank. If using a foam gun, SAF-T-STEP® will self-foam at 4 ounces of water dilution.

Directions

1. Apply product liberally, evenly and directly to floor. Leave product on floor for 5 minutes
2. Scrub floor with stiff bristle brush; pay special attention to grout lines and heavily soiled areas.
3. Rinse thoroughly with clean water
4. Squeegee remaining water and residue to floor drains. If drains are not available, use wet/dry vacuum or mop up with mop, bucket and clean water.

