ELKINS
Since 1956
WHOLESALE INC.

FINISH COAT 25

EXTREME PERFORMANCE FLOOR FINISH

FEATURES

- Incorporates high molecular weight cross-linked acrylic polymers
- Cross-linked acrylic polymers provides superior:
  - Lay-down gloss
  - Durability
  - Soil resistance
  - Gloss build
  - Mark resistance
  - Dry and recoat times
- Ammonia-free for dramatically reduced odor
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired
- Low emissions formula - meets California's new 1% VOC Regulation
- Fast-drying - 30-35 minutes under optimal conditions (50% humidity and 70°F) between coats
- Meets ASTM D2047 method for slip resistance

PROPERTIES

Type	Acrylic Emulsion
Form	Opaque Liquid
Odor	Bland
Color	Milky White
Film Clarity	Clear
Weight Per Gallon	8.73 Lbs.
pH	7.8
Floor Solids	25%
Storage Stability	Minimum 1 Year
Freeze/Thaw	Protect From Freezing
V.O.C.	1%

* Properties are typical and subject to usual manufacturing tolerances

Scan QR code for access to the Safety Data Sheet.

Scanner le code QR pour accéder à la Fiche de Données de Sécurité.

Escanee el código QR para acceder a la Hoja de Datos de Seguridad.

803 South Magnolia St.
Laurel, MS 39440

3880 Bullard St.
Jackson, MS 39209

www.elkinswholesale.com

PRODUCT NUMBER:
ELKINS97-5GP