HI POWER DEGREASER

Powerful Alkaline Soil Eliminator

FEATURES

- Industrial strength degreaser floats away grease, oil, dirt, soap scum, light carbon, and other grime
- Variable dilution rate – from 1-12 ounces per gallon
- All-purpose, all-surface – use wherever heavy soil is found
- Classified non-hazardous by DOT
- USDA A1 authorized – ideal for use in federally inspected meat and poultry plants
- NSF A1 listed

PROPERTIES*

Type	Butyl Degreaser
Form	Clear Liquid
Odor	Pine Detergent
Color	Purple
Weight per Gallon	8.73 lbs.
pH	12.3 - 13.0
pH 1%	9.4
Storage Stability	Min. 1 Year
Freeze/Thaw	Passes 3 Cycles
Foam Height	Medium High
Flash Point (c.c.)	None
Actives	>15%
Phosphate (%P)	0.9

* Properties are typical and subject to usual manufacturing tolerances

ESSENTIAL® INDUSTRIES

Merton, Wisconsin 53056-0012 USA
Phone: (262) 538-1122
www.essind.com

354DG

© 2010 Essential Industries, Inc. L1510
LT-90000S0354DG

354GC

HI POWER DEGREASER

With Iodine Stain Remover

PRODUCT SAFETY AND TRAINING

DIRECTIONS

Effectively strips, grease, grime, soap scum, oil, dirt, sludge and other films from a variety of surfaces. Chemically penetrates, reacts with and suspends soil in solution for easy rinsing. Spray, brush or mop on and RINSE THOROUGHLY. High concentrations may be used for extreme soil, less for light soil.

Heavy Cleaning ..... dilute 1 to 20 water **General Cleaning** ..... dilute 1 to 40 water **Light Cleaning** ..... dilute 1 to 60 water

SPECIFIC DILUTIONS

Air Filters	1 to 4 water	Whitewall Tires	1 to 1 water
Conveyors	1 to 10 water	Concrete Floors	1 to 20 water
Engines, Machinery	1 to 2 water	Damp Mopping	1 to 60 water
Kitchens (ovens)	1 to 4 water	Walls, ceilings	1 to 20 water
Metal Surfaces	1 to 10 water	Machine Sumps	1 to 10 water
Printing Plants	1 to 10 water	Plastics	1 to 40 water
Scrubbing Machines	1 to 20 water	Shower stalls	1 to 10 water
Stainless & Aluminum	1 to 20 water	Swimming Pools	1 to 10 water
Terrazzo	1 to 30 water	Air Conditioning (ducts, grills)	1 to 20 water
Exhausts, Flues	1 to 2 water		

For Food Plant Use: Food contact surfaces are to be rinsed with potable water before reuse.

NOTE: For stripping and maintaining asbestos containing tile, follow OSHA guidelines or EPA guidelines.

DISPOSAL - CAUTION - FIRST AID

DISPOSAL: PRODUCT: Dispose of excess product in accordance with local, state and federal regulations. CONTAINER: Please recycle HDPE container.

CAUTION: May cause severe eye, skin and gastrointestinal irritation or burns. May be absorbed through skin with prolonged or repeated contact. Use in poorly ventilated area may cause respiratory irritation. **PRECAUTION:** Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Keep out of the reach of children.

FIRST AID: EYES & SKIN: Flush with water (eyes 15 minutes). **INGESTION:** If swallowed, give 2-3 large glasses of water. DO NOT induce vomiting. Seek medical attention. **INHALATION:** Remove to fresh air and rest. In all cases if symptoms persist, seek medical attention.

ESSENTIAL® INDUSTRIES
Merton, Wisconsin 53056-0012 USA
Phone: (262) 538-1122
www.essind.com

NSF 134742

© 2010 Essential Industries, Inc. L1510
LT-90000S0354DG3