TYR TACTICAL® MALE EPIC-LOC MOLLE ASSAULTER'S PLATE CARRIER

















ENHANCED DESIGN FEATURES:

BREATHABILITY & MOISTURE PROTECTION

Antimicrobial/FR treated padded spacer mesh system

SCALABLE SYSTEM

- · Removable front flap
- QASM buckle system
- PALS webbing for MOLLE attachment
- Semi-rigid exterior MOLLE cummerbund

PATENTED INTEGRATED BALLISTIC FRAMEWORK

Increases structural integrity & reduces back face deformation

ELONGATED MATERIAL LIFE & ABRASION RESISTANCE

• Engineered utilizing patented PV® material



PLATE POCKET STYLE

 Internal plate pocket retention straps accommodate several different plate styles & thicknesses

ADDITIONAL FEATURES

- Patented Ballistic Vein®
- EPIC® low profile shoulder pads
- Hydration/Communication tabs for routing
- · Reinforced drag handle
- · Repair buckle kit

NIJ 0101.06 Certified Level IIIA NIJ 0101.06 Certified Level II TYR-M-EPIC-LOC-MOL-TXP3A

TYR-M-EPIC-LOC-MOL-NFA2/10

NIJ 0101.06 Certified Level IIIA TYR-M-EPIC-LOC-MOL-NFA3/10

TYR TACTICAL® FEMALE EPIC-LOC MOLLE ASSAULTER'S PLATE CARRIER

















ENHANCED DESIGN FEATURES:

BREATHABILITY & MOISTURE PROTECTION

• Antimicrobial/FR treated padded spacer mesh system

SCALABLE SYSTEM

- Removable front flap
- QASM buckle system
- PALS webbing for MOLLE attachment
- Semi-rigid exterior MOLLE cummerbund

PATENTED INTEGRATED BALLISTIC FRAMEWORK

Increases structural integrity & reduces back face deformation

ELONGATED MATERIAL LIFE & ABRASION RESISTANCE

Engineered utilizing patented PV® material



PLATE POCKET STYLE

 Internal plate pocket retention straps accommodate several different plate styles & thicknesses

ADDITIONAL FEATURES

- Patented female shape
- Patented Ballistic Vein[®]
- EPIC[®] low profile shoulder pads
- Hydration/Communication tabs for routing
- · Reinforced drag handle
- · Repair buckle kit

NIJ 0101.06 Certified Level IIIA NIJ 0101.06 Certified Level II TYR-F-EPIC-LOC-MOL-TXP3A

TYR-F-EPIC-LOC-MOL-NFA2/10F

NIJ 0101.06 Certified Level IIIA

TYR-F-EPIC-LOC-MOL-NFA3/10F

TYR TACTICAL® BODY ARMOR





BALLISTIC PANELS

Removable ballistic panels should be cleaned in the following method:

- · Do not immerse in liquid
- Gently wipe-down ballistic panels with a damp sponge or wash cloth using mild detergent. Remove any excess detergent with a damp sponge or wash cloth using clean water.
- Allow to thoroughly air dry before inserting panels into carrier.
- · Do not dry clean, machine wash or bleach
- . Do not dry outdoors in the sun

























OUTER CARRIER


The nylon carrier is treated with chemicals to reduce your IR signature. Therefore you should never use a phosphorus based detergent to clean your vest, doing so will breakdown its IR treatment causing it to glow under IR light.

- · Remove ballistic panels from the front and back of the carrier.
- · Brush off as much surface dust as possible.
- Scrub set-in stains with a nylon brush using a mild non-phosphorus detergent such as Dawn dish soap.
- · Air-dry indoors at room temperature.

Additional Instructions:

- Do Not Bleach
- Carrier Must Be Completely Dry Before Inserting The Ballistic Panels













TYR TACTICAL SOFT ARMOR SPECIFICATIONS



SOFT ARMOR PACKAGES	NFA3/10*
THICKNESS	.24"
WEIGHT/ Areal Density	1.09 lbs psf
TESTING STANDARD	NIJ 0101.06 FBI Testing Standards
PROTECTION Level	Certified Level IIIA FBI & DEA Requirements
V 50	.357 Sig / 1865 fps .44 Mag / 1690 fps
BACK-FACE Deformation	.357 Sig / 30.3mm .44 Mag / 35.4mm
IDEAL USE	Tactical

*Available in Gender Neutral and Female Version



TYR TACTICAL® HARD ARMOR TYR-XHA3/7









DI ATE DADT	TVD VIIA9/7
PLATE PART#	TYR-XHA3/7
WEIGHTS	XSmall: 2.74 lbs.
	Small: 3.34 lbs.
	Medium: 3.85 lbs.
	Large: 4.37 lbs. XLarge: 4.95 lbs.
	ALaige: 4.55 lbs.
DIMENSIONS	XSmall: 6.87" x 11.12"
	Small: 8.5" x 11.5"
	Medium: 9.3" x 12.3"
	Large: 10" x 13"
	XLarge: 10.9" x 13.8"
TESTING STANDARD	NU 0101.06
STANDARD	
PROTECTION	Level III &
LEVEL	Special Threats
CONFIGURATION	In-Conjunction with
	NIJ Level II or above
PLATE	
THICKNESS	.62 in. / 15.75 mm
BUOYANCY	N/A
	IVA
CURVATURE	Multi Curve
MATERIALS	Ceramic Composite HAP
COVER	Black Polyurea
	E 45 v 20 mm E2 avain MCC 7NC
	5.45 x 39-mm, 53-grain MSC 7N6 5.56 x 45-mm, 62-grain M855 Ball, SS109
THREATS	7.62 v 20 mm 122 grain MCC

7.62 x 39-mm, 123-grain MSC

7.62 x 51-mm, 149-grain M80 FMJ 7.62 x 54R-mm, 148-grain LPS

THREATS



HURON CARRY BAGS





HURON ARMOR CARRY BAG

ENHANCED DESIGN FEATURES:

- 500 Denier Cordura®
- Clear Plastic I.D. Window
- 2" Nylon Webbing Reinforcement Handles
- Heavy Duty Zippers & Ribbed 550 Cord Zipper Pulls
- Wt.: 1.75 lbs.
- Dim: 23"L x 23"W x10"D

HRN-ACB













TYR TACTICAL® PICO-DSX ASSAULTER'S PLATE CARRIER

















ENHANCED DESIGN FEATURES:

QUICK RELEASE

• Taktic buckle system provides a quick connect for users to don & doff the plate carrier utilizing one hand in less than two seconds

BREATHABILITY & MOISTURE PROTECTION

- Antimicrobial/FR treated padded spacer mesh system
- Slotted poly mesh base cummerbund for increased ventilation

LOAD CARRIAGE

- Flush admin chest pocket with internal elastic keepers
- Rear internal pocket for storage
- Seam tape straps for radio & magazine pouch attachment
- Elastic webbing straps for cable management
- PALS webbing for MOLLE attachment

SCALABLE SYSTEM

- · Removable front flap
- Zippers for DS Assaulter's Zip-On Back Panels
- QASM buckle system

ELONGATED MATERIAL LIFE & ABRASION RESISTANCE

Engineered utilizing patented PV® material



PLATE POCKET STYLE

- Incorporates a Gusseted Plate Pocket which relieves tension and pressure normally placed on the body from hard plates in classic plate pocket configurations
- The front & back plate pocket incorporate 4-way stretch Tweave on the perimeter. This allows the plate pocket to expand & accommodate multiple plate thicknesses.

ADDITIONAL FEATURES

- · Reinforced drag handle
- · Repair buckle kit
- · Low profile wrap shoulder pads

Carrier Only
TYR-PICO-DSX-CR

NIJ 0101.06 Certified Level II TYR-PICO-DSX-NFA2/10

Exceeds Level II & USSOCOM Frag Spec TYR-PICO-DSX-NFA2/DK

NIJ 0101.06 Certified Level IIIA TYR-PICO-DSX-NFA3/10

NIJ 0101.06 Certified Level IIIA TYR-PICO-DSX-TXP3A

TYR TACTICAL® PATENTED BALLISTIC SHIELD DOLLY







Telescoping frame & Shield Clamps accommodate up to two shields (sold separately)

TYR TACTICAL® PATENTED BALLISTIC SHIELD DOLLY - LEVEL III

ARMOR SPECIFICATIONS:

Weight 40.0 lbs.

Testing Standard: NIJ 0108.01

Protection Level: Level III & Special Threats **Plate Thickness:** .56 in. / 14.22 mm

Materials: UHMWPE & Hybrid Ceramics

Cover: Black Polyurea

Threats: 5.56 x 45-mm, 55-grain M193 Ball

7.62 x 39-mm, 123-grain PS Ball

7.62 x 51-mm, 149-grain M80 FMJ

7.62 x 54R-mm, 148-grain LPS

TYR-RBS/BSD2-LV3

FEATURES & SPECIFICATIONS:

CONSTRUCTION

- Constructed out of high-strength, lightweight aluminum
- Two rubberized dolly handles
- · Padded shield rest
- Center armor panel reinforces the connection area where the upper & lower shields meet
- Matte black powder coat finish

BALLISTIC COVERAGE

- Center armor panel covers the ballistic gap on both sides of the dolly
- Bolt holes on the armor panel are offset from the ballistic gap to reduce the possibility of penetration

FRAME ADJUSTABILITY

- Telescoping frame to accommodate up to two shields
- Telescoping, pull pin, shield handle bracket for multiple shield sizes

WHEEL CONFIGURATION

- Removable rear wheel
- Two-wheel configuration allows for 360° movement
- Dolly is self-supported in the two-wheel configuration by resting on the lower shield
- Three removable heavy duty wheels



TYR TACTICAL® PATENTED BALLISTIC SHIELD DOLLY







DOUBLE SHIELD:

The two-wheel configuration allows you to run the system as a ballistic barricade with 360° movement. Two handle heights allow the user to push the dolly in a standing or bowed position. The system can also tilt forward transforming it into a free-standing ballistic barricade.

M PROVIDES BOTH LOAD
CARRIAGE & UNMATCHED
BALLISTIC PROTECTION. 17

SYSTEM DEPLOYS
IN 90 SECONDS
OR LESS 17

SINGLE SHIELD:

Provides a ballistic barricade in the tilt forward position. It also functions as a load carriage dolly for Broco 0^2 Cylinders as well as mission specific MOLLE panels (sold separately).





TYR TACTICAL® 24" X 36" MT NON-VIEWPORT LEVEL III PROTECTION RAPID RESPONSE BALLISTIC SHIELD







FEATURES:

- Forearm pad
- Carry bag
- Fixed shield handle
- Patented Ballistic Ridge[®]

LEVEL III

The TYR Tactical® 24"x36" MT3 Rapid Response Ballistic Shield is built to work as a stand-alone Level III shield

SPECIFICATIONS:

Weight: 21.6 lbs.

Dimension: 24" x 36"

Testing Standard: NIJ 0108.01

Protection Level: Level III & Special Threats

Configuration: Stand Alone

Plate Thickness: .56 in. / 14.22 mm

Buoyancy: N/A

Curvature: Single Curve

Materials: UHMWPE

Cover: Black Polyurea

Threats: 5.56 x 45-mm, 55-grain M193 Ball 7.62 x 39-mm, 123-grain PS Ball

7.62 x 51-mm, 149-grain M80 FMJ 7.62 x 54R-mm, 148-grain LPS

TYR-RBS/MT3-NV

TYR TACTICAL® 18" X 32" CQB NON-VIEWPORT LEVEL IIIA PROTECTION RAPID RESPONSE BALLISTIC SHIELD







FEATURES:

- Forearm pad
- Carry bag
- Fixed shield handle
- Patented Ballistic Ridge[®]

LEVEL IIIA

The TYR Tactical® 18" x 32" CQB3A Rapid Response Ballistic Shield is built to work as a stand-alone Level IIIA shield

SPECIFICATIONS:

Weight: 8.3 lbs

Dimension: 18" x 32" Testing Standard: NIJ 0108.01

Protection Level: Level IIIA & Special Threats

Configuration: Stand Alone Plate Thickness: .28 in. / 7.11 mm

Buoyancy: N/A

Curvature: Single Curve Materials: UHMWPE Cover: Black Polyurea

TYR-RBS/CQB3A-NV

Threats: 9-mm, 127-grain SXT

9-mm Fiocchi, 115-grain FMJ

9-mm, 124-grain FMJ

5.7 X 28-mm, 27-grain SS195 LFHP

5.7 x 28-mm, 28-grain SS192

5.7 x 28-mm, 40-grain SS197SR

.40-cal., 95-grain S&W HP

.357 SIG, 115-grain JHP

.357-cal, 125-grain SIG FMJ FN

.357-cal, 125-grain SIG GDHP

7.62 x 25-mm, 85-grain TOKAREV FMJ

.44-mag, 240-grain SWCGC

TYR TACTICAL® 18" X 32" CQB VIEWPORT LEVEL IIIA PROTECTION RAPID RESPONSE BALLISTIC SHIELD







FEATURES:

- Forearm pad
- Carry bag
- · Fixed shield handle
- Patented Ballistic Ridge[®]

LEVEL IIIA

The TYR Tactical® 18" x 32" CQB3A Rapid Response Ballistic Shield with Viewport is built to work as a stand-alone Level IIIA shield

SPECIFICATIONS:

Weight: 12.3 lbs

Dimension: 18" x 32" (Viewport: 9.75" x 3.75")

Testing Standard: NIJ 0108.01

Protection Level: Level IIIA & Special Threats

Configuration: Stand Alone **Plate Thickness:** .28 in. / 7.11 mm

Buoyancy: N/A

Curvature: Single Curve
Materials: UHMWPE
Cover: Black Polyurea

TYR-RBS/CQB3A-VP

Threats: 9-mm, 127-grain SXT

9-mm Fiocchi, 115-grain FMJ

9-mm, 124-grain FMJ

5.7 X 28-mm, 27-grain SS195 LFHP

5.7 x 28-mm, 28-grain SS192

5.7 x 28-mm, 40-grain SS197SR

.40-cal., 95-grain S&W HP

.357 SIG, 115-grain JHP

.357-cal, 125-grain SIG FMJ FN

.357-cal, 125-grain SIG GDHP

7.62 x 25-mm, 85-grain TOKAREV FMJ

.44-mag, 240-grain SWCGC

TYR TACTICAL® 18" X 32" CQB NON-VIEWPORT LEVEL III PROTECTION RAPID RESPONSE BALLISTIC SHIELD







FEATURES:

- Forearm pad
- · Carry bag
- · Fixed shield handle
- Patented Ballistic Ridge[®]

LEVEL III

The TYR Tactical® 18" x 32" CQB3 Rapid Response Ballistic Shield is built to work as a stand-alone Level III shield

SPECIFICATIONS:

Weight: 16.3 lbs Dimension: 18" x 32"

Testing Standard: NIJ 0108.01

Protection Level: Level III & Special Threats

Configuration: Stand Alone **Plate Thickness:** .56 in. / 14.22 mm

Buoyancy: N/A

Curvature: Single Curve
Materials: UHMWPE
Cover: Black Polyurea

Threats: 5.56 x 45-mm, 55-grain M193 Ball 7.62 x 39-mm, 123-grain PS Ball 7.62 x 51-mm, 149-grain M80 FMJ

7.62 x 54R-mm, 148-grain LPS

TYR-RBS/CQB3-NV

TYR TACTICAL® 18" X 32" CQB VIEWPORT LEVEL III PROTECTION RAPID RESPONSE BALLISTIC SHIELD







FEATURES:

- Forearm pad
- · Carry bag
- · Fixed shield handle
- Patented Ballistic Ridge[®]

LEVEL III

The TYR Tactical® 18" x 32" CQB3 Rapid Response Ballistic Shield with Viewport is built to work as a stand-alone Level III shield

SPECIFICATIONS:

Weight: 24.8 lbs.

Dimension: 18" x 32" (Viewport: 9.75" x 3.75")

Testing Standard: NIJ 0108.01

Protection Level: Level III & Special Threats

Configuration: Stand Alone
Plate Thickness: .56 in. / 14.22 mm

Buoyancy: N/A

Curvature: Single Curve Materials: UHMWPE Cover: Black Polyurea **Threats:** 5.56 x 45-mm, 55-grain M193 Ball 7.62 x 39-mm, 123-grain PS Ball 7.62 x 51-mm, 149-grain M80 FMJ

7.62 x 54R-mm, 148-grain LPS

TYR-RBS/CQB3-VP