

MELL



32"

MODEL - 994157

18.5 HP / 603 CC Kawasaki® FS600 V-TWIN

36"

MODEL - 994149

18.5 HP / 603 CC Kawasaki® FX600 V-TWIN

48"

MODEL - 99/1/1

23.5 HP / 726 CC Kawasaki® FX730 V-TWIN

52"

MODEL - 994162

23.5 HP / 726 CC Kawasaki $^{\circ}$ FX730 V-TWIN

MODEL - 994163

26 HP / 726 CC Kawasaki® FT730 EFI

60"

MODEL - 994164

23.5 HP / 726 CC Kawasaki® FX730 V-TWIN

MODEL - 994165

26 HP / 726 CC Kawasaki® FT730 EFI

DECK HEIGHT ADJUSTMENT The dual height-adjustment system was designed with both a traditional hand lever and a foot lever to lift and adjust the deck. It's perfect for smaller operators who may struggle with traditional hand lever lifts.

X-FACTOR® 3 DECK The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

TRANSMISSION The ZT-3400 integrated transmission boasts an industry-leading 1.125-inch axle for heavy loads (32" and 36" model uses ZT-3100).

PRO-STANCE°



See your professional Gravely® dealer for complete warranty details.

	32	36	48	52		60	50
	32	30	40	32	52	80	60
MODEL NUMBER	994157	994149	994161	994162	994163	994164	994165
ENGINE	KAWASAKI° FS 600V	KAWASAKI° FS 600V	KAWASAKI° FX 730V	KAWASAKI° FX 730V	KAWASAKI° FT 730 EFI	KAWASAKI° FX 730V	KAWASAKI° FT730-E
HORSEPOWER	18	3.5	23.5 HP	23.5 HP	26 HP	23.5 HP	26 HP
DISPLACEMENT	603 CC		726 CC	726 CC	726 CC	726 CC	726 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-3100 TRANSAXLE			HYDRO-GEAR® ZT-3400 TRANSAXLE			
FUEL CAPACITY	6 GAL			9 GAL			
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	8 MPH / 3 MPH		9 MPH / 4 MPH				
STARTER				ELECTRIC			
DECK							
DECK MATERIAL				7 GA.			
DECK CONSTRUCTION				FABRICATED			
NUMBER OF SPINDLES	-	2			3		
BLADE TIP SPEED (FPM)	18,3	220			18,000		
SPINDLE HOUSING MATERIAL				FORGED ALUMINUM			
SPINDLE BEARINGS				BALL BEARING			
DECK ENGAGEMENT	OGURA 2.75 ELECTRIC CLUTCH						
DECK LIFT SYSTEM				MANUAL			
CUTTING WIDTH	32 IN	36 IN	48 IN	52 IN	52 IN	60 IN	60 IN
CUTTING HEIGHTS				1.5 IN - 5.0 IN			
CUTTING POSITIONS				15			
WHEELS							
FRONT AXLE				RIGID			
FRONT	11 X 4.00-5 SEMI-PNEUMATIC			13 X 6.50-6 SEMI-PNEUMATIC			
REAR	18 X 6.50 - 8 RADIAL		20 X 10.50 - 8 RADIAL				
MACHINE							
WEIGHT	750 LBS	784 LBS	995 LBS	1015 LBS	1015 LBS	1043 LBS	1048 LBS
LENGTH	59.5 IN	59.5 IN	60.63 IN	60.63 IN	60.63 IN	62 IN	62 IN
WIDTH (w/o CHUTE)	33.5 IN	36.5 IN	50 IN	55.5 IN	55.5 IN	63 IN	63 IN
WIDTH (w/ CHUTE)	49 IN	49 IN	62.25 IN	67.75 IN	67.75 IN	75.25 IN	75.25 IN
HEIGHT				48 IN			
WARRANTY							
UNIT	5 YEAR / 1000 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS - SEE YOUR PROFESSIONAL GRAVELY® DEALER FOR COMPLETE WARRANTY DETAILS						
DECK SHELL & FRAME	LIMITED LIFETIME						

MULCHING KIT, OCDB KIT, HEADLIGHT KIT, TRIMMER MOUNT KIT, PACK BLOWER MOUNT KIT, BUCKET MOUNT KIT, REAR TWEEL KIT, LASEREDGE BLADES, TUNE UP KIT



