## **GRAVELY**



**48**"

**MODEL - 992527** 

25.5 HP / Kawasaki FX801 Engine

**52**"

**MODEL - 992528** 

25.5 HP / Kawasaki FX801 Engine

60"

**MODEL - 992523** 

26 HP / Kawasaki® FT730 EFI Engine

**MODEL - 992529** 

29.5 HP / Kawasaki® FX850 EFI Engine

**MODEL - 992526** 

31 HP / Kawasaki® FX921V Engine

**72**"

MODEL - 992525

31 HP / Kawasaki® FX921V Engine

COMFORTABLE SEAT High back seat has lumbar support and molded armrests. Its red double stitching gives a high-end look with black, dark grey, and red accents.

FULLY WELDED TUBULAR FRAME One glace and you can see its strength and ruggedness. Its wide front rail distributes weight for superior balance.

Also supports the deck lift for easy engagement. Includes a limited lifetime warranty.

PARKER TRANSAXLES Parker HTJ transaxles deliver a top speed of 11mph and have a 12cc pump. Filters are easily accessed from the rear for easy maintenance. This is one complete system which eliminates the need for additional parts, saving both time and money.

X-FACTOR® 3 Made with 7-gauge steel and specially designed for better grass dispersion thanks to its larger discharge opening, integrated baffles, and sloped front end. Reinforced spindle mounts protect blade operation while the six recessed anti-scalp wheels protect the turf on uneven terrain. Its flip-up rubber chute makes it easy to drive through gates and around obstacles. A 5/8" leading edge provides extra protection to the shell while stabilizer links keep vibration to a minimum. Includes a limited lifetime warranty.

DIAL HEIGHT ADJUSTMENT The dial wheel allows easy height adjustment between one and five inches. Toolless adjustable foot pedal with internal assist springs helps lift the deck with little effort.

## PRO-TURN 300



See your professional Gravely® dealer for complete warranty details.

	348	352	360	360	360	372
MODEL NUMBER	992527	992528	992523	992529	992526	992525
NGINE	KAWASAKI FX801	KAWASAKI FX801	KAWASAKI FT730 EFI	KAWASAKI FX801 EFI	KAWASAKI FX921V	KAWASAKI FX921V
ORSEPOWER	25.5 HP	25.5 HP	26 HP	29.5 HP	31 HP	31 HP
ISPLACEMENT	852 CC	852 CC	726 CC	852 CC	999 CC	999 CC
RIVE SYSTEM	PARKER HTJ TRANSMISSION					
UEL CAPACITY	12.5 GAL					
ROUND SPEED APPROX. Mph) (Forward/ leverse)	11 MPH / 5 MPH					
DECK						
ECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT					
ECK CONSTRUCTION	X-FACTOR® 3 DECK					
IUMBER OF SPINDLES	3					
BLADE TIP SPEED (FPM)	18,000					
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM					
PINDLE BEARINGS	BALL BEARING					
DECK ENGAGEMENT	OGURA GT2.75 OGURA GT3.5					
CUTTING WIDTH	48 IN.	52 IN.	60 IN.	60 IN.	60 IN.	72 IN.
CUTTING HEIGHTS	1.0 IN 5.5 IN.					
CUTTING POSITIONS	19					
WHEELS						
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES					
RONT	SMOOTH 15 X 6-6 PNEUMATIC					
REAR	24 X 12-16 BIAS PLY TURF					
FEATURES						
SEAT	SUSPENSION PLUSH SEAT WITH ARM RESTS					
FOLDABLE ROPS	STANDARD					
MACHINE						
VEIGHT	1235 LBS.	1320 LBS.	1347 LBS.	1346 LBS	1350 LBS.	1472 LBS.
LENGTH	83 IN.	83 IN.	83 IN.	83 IN.	83 IN.	83 IN.
WIDTH (w/o CHUTE)	51 IN.	55 IN.	63 IN.	63 IN.	63 IN.	75 IN.
VIDTH (w/ CHUTE)	63 IN.	67 IN.	75 IN.	75 IN.	75 IN.	87 IN.
HEIGHT (w/ ROPS EXT/ DOWN)	76.0 IN. /47.8 IN.					
WARRANTY						
	5 YEAR/1250 HOUR COMMERCIAL/NO HOUR LIMIT FIRST 2 YEARS- SEE YOUR PROFESSIONAL GRAVELY DEALER FOR COMPLETE WARRANTY DETAILS					

## **ATTACHMENTS & ACCESSORIES**

MULCHING KIT ELECTRIC DECK LIFT KIT TRAILER KIT KIT LED HEADLIGHT KIT POWERED BAGGER KIT OCDC KIT SUNSHADE KIT REAR TWEEL KIT RADIAL DRIVE CONVERSION KIT WHEEL COVER KIT LASEREDGE BLADE KIT TUNE UP KIT

