



# Z-STANCE<sup>®</sup>

## STAND TALL ON THE TURF

You'll ride with pride as you deliver that perfect Gravelly cut on the Z-Stance. This powerful commercial stand-on mower is easy to maneuver and a breeze to maintain. It's three deck sizes make quick work of a corporate campus or a gated backyard. You take a stand for comfort, ingenuity, and durability when you're on a Z-Stance.



### 32"

**MODEL - 994160**  
18.5 HP / KAWASAKI® FS600  
V-TWIN Engine

### 48"

**MODEL - 994159**  
22 HP / KAWASAKI® FS651  
V-TWIN Engine

### 52"

**MODEL - 994158**  
22 HP / KAWASAKI® FS651  
V-TWIN Engine

**ADJUSTABLE CRUISE BAR** Allows the operator to limit and expand the unit's maximum speed in tight working environments.

**THREE DECKS TO CHOOSE FROM** 10 gauge 48" and 52" X-Factor III decks or 32" deck in 7 gauge for added weight.

**POWERFUL V-TWIN ENGINES** 18.5 HP with the 32" or 22 HP on the 48" and 52" models.

**ADDED EFFICIENCY** Ingenious design allows quick and easy access to the fuel tank.

**HEIGHT-OF-CUT SYSTEM** Simple lever control for fast adjustments

**LOWERED CENTER OF GRAVITY** Reshaped geometry and redistributed weight provide increased hillside stability and confidence in your ride.

# Z-STANCE®



See your professional Gravely® dealer for complete warranty details.

	32	48	52
<b>MODEL NUMBER</b>	<b>994160</b>	<b>994159</b>	<b>994158</b>
<b>ENGINE</b>	KAWASAKI® FS600 V-TWIN		KAWASAKI® FS651 V-TWIN
<b>HORSEPOWER</b>	18.5 HP		22 HP
<b>DISPLACEMENT</b>	603 CC		726 CC
<b>DRIVE SYSTEM</b>	HYDRO-GEAR® ZT-3100 TRANSAXLE		
<b>FUEL CAPACITY</b>	4.5 GAL.		
<b>GROUND SPEED (APPROX. Mph)</b> <i>(Forward/Reverse)</i>	7 MPH / 3 MPH		
<b>STARTER</b>	ELECTRIC		
<b>DECK</b>			
<b>DECK MATERIAL</b>	7 GA.		10 GA.
<b>DECK CONSTRUCTION</b>	X-FACTOR® II		X-FACTOR® 3
<b>NUMBER OF SPINDLES</b>	2		3
<b>BLADE TIP SPEED (FPM)</b>	18,220	18,000	18,500
<b>SPINDLE HOUSING MATERIAL</b>	FORGED ALUMINUM		
<b>SPINDLE SHAFT</b>	STEEL		
<b>SPINDLE BEARINGS</b>	BALL BEARING		
<b>DECK ENGAGEMENT</b>	ELECTRIC CLUTCH		
<b>DECK LIFT SYSTEM</b>	MANUAL		
<b>CUTTING WIDTH</b>	32 IN.	48 IN.	52 IN.
<b>CUTTING HEIGHTS</b>	2.0 IN. - 5.0 IN.		1.5 IN. - 5.0 IN.
<b>CUTTING POSITIONS</b>	13		15
<b>WHEELS</b>			
<b>FRONT</b>	11 X 5-6 PNEUMATIC		
<b>REAR</b>	20 X 6.50 - 8 TURF		
<b>MACHINE</b>			
<b>WEIGHT</b>	669 LBS.	744 LBS.	763 LBS.
<b>LENGTH</b>		65.5 IN.	
<b>WIDTH (w/o CHUTE)</b>	32.8 IN.	49.5 IN.	55 IN.
<b>WIDTH (w/ CHUTE)</b>	44.8 IN.	61 IN.	66.75 IN.
<b>HEIGHT</b>		47.5 IN.	
<b>WARRANTY</b>			
<b>UNIT</b>	4 YEAR / 500 HOUR COMMERCIAL		
<b>ATTACHMENTS &amp; ACCESSORIES</b>			
MULCHING KIT, OPERATOR CONTROLLED DISCHARGE BAFFLE, HEADLIGHT KIT, TWEEL KIT, BLADE KIT, GRASS CATCHER			



GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2022 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company, Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit [gravely.com](http://gravely.com) for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.