Directions:

Floor Preparation: Strip old finish and wax using your preferred NCL floor stripper following label directions. For baseboards and corners, use an NCL baseboard stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply a thin uniform coats of ONE COAT 25™ Hi-Gloss Floor Finish. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

High Speed Buffing and Burnishing: ONE COAT 25™ Hi-Gloss Floor Finish is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. Prior to buffing or burnishing dust mop the floor surface using an NCL dust mop treatment. Buff or dry burnish using an NCL Aqua Magic buffing pad. For spray buffing, mop-on or autoscubber restoring use a prefered NCL gloss restorer.

Routine Maintenance: Dust mop using mop treated with an NCL dust mop treatment. Damp mop or clean with an automatic scrubber using your preferred NCL neutral floor cleaner following label directions.

Instrucciones para Uso:

Preparación de suelos: acabado viejo de Gaza y la cera con su piso separador NCL preferido siguiendo instrucciones de la etiqueta. Para zócalos y esquinas, utilizar un zócalo separador NCL siguiendo instrucciones de la etiqueta. Si es necesario, enjuague bien con agua limpia y deje secar completamente.

Aplicación: Usando un trapeador limpio o aplicador aplica una delgada capas uniformes de ONE COAT 25™ Hi-Gloss Floor Finish. Deje que se seque durante un mínimo de 30 minutos después de cada mano. No aplique más de 4 capas en un período de 24 horas. Piso debe estar completamente seco antes de permitir el tráfico en la zona.

High Speed pulido y bruñido: ONE COAT 25™ Hi-Gloss Floor Finish es un producto ideal para su uso con una alta velocidad de pulido o bruñido máquinas de 1000 rpm o superior. Antes de pulido o bruñido polvo fregar la superficie del suelo con un tratamiento trapeador NCL. Buff o seco pulir utilizando NCL Aqua Magic pulido pad. Para pulido con rociado, mop-on o autoscubber restaurar utilizar una preferida NCL restaurador de brillo.

Mantenimiento de rutina: Mopa con trapeador tratado con un tratamiento trapeador NCL. Pase un trapeador húmedo o limpiar con un lavador automático utilizando el limpiador de pisos neutro preferido siguiendo instrucciones de la etiqueta.

★★ MADE IN USA ★★

0510-29-0614

FOR COMMERCIAL AND INDUSTRIAL USE ONLY
QUESTIONS?
Call (800) 628-2436

7 52610 10510 0

To learn more about this product, scan this **QR code** to visit our website.

NCL®

World Class Cleaning Solutions®

Finishing

One Coat 25™

Super Hi-Gloss Floor Finish

A pure thermoplastic floor finish with exceptional durability, extended wear and a deep brilliant gloss!

KEEP OUT OF REACH OF CHILDREN. / SUBSISTENCIA FUERA DEL ALCANCE DE NIÑOS

See side panel for additional precautionary statements. / Ver panel lateral para las medidas preventivas adicionales.

NET CONTENTS: 1 GALLON / 3.79 LITERS

National Chemical Laboratories, Inc.
Philadelphia, PA 19123 USA • (800) 628-2436
www.nclonline.com

Product No.: 0510

KEEP OUT OF REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash hands after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations. This product is not known to be a "Hazardous Chemical" as defined by the OSHA HazCom 2012 Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first aid measures. SDS for this product is available on the web at www.nclonline.com

Inhalation: Move to fresh air. Get medical attention if symptoms occur.

Skin contact: Wash skin with soap and water. Get medical attention if irritation develops or persists.

Eye contact: Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if irritation develops and persists.

Ingestion: Rinse mouth thoroughly with water. Seek medical advice.

KEEP FROM FREEZING

SUBSISTENCIA FUERA DEL ALCANCE DE NIÑOS.

Palabra de advertencia

Prevención: Mantenga buenas prácticas de higiene industrial.

Respuesta: Lávese las manos después del uso.

Almacenamiento: Consérvese alejado de materiales incompatibles.

Eliminación: Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales / internacionales pertinentes.
Este producto no se sabe para ser un "Producto Químico Peligroso" según lo definido por el estándar OSHA HazCom 2012, 29 CFR 1910.1200.

Medidas additional de primeros auxilios:

Lea toda la etiqueta y SDS antes de usar este producto, así como medidas adicionales de primeros auxilios. SDS para el artículo está disponible en la web en www.nclonline.com

Inhalación: Traslade al aire libre. Obtenga atención médica en caso de síntomas.

Contacto cutáneo: Lavar la piel con jabón y agua. Buscar atención médica si la irritación aumenta o persiste.

Contacto ocular: Enjuagar los ojos cuidadosamente con abundante agua durante al menos 15 minutos. Buscar atención médica si la irritación se desarrolla y persiste.

Ingestión: Enjuáguese la boca cuidadosamente con agua. Busque atención médica.

CONTAINS: Diethylene Glycol Monoethyl Ether CAS# 111-90-0, Tris(2-Butoxyethyl) Phosphate CAS# 78-51-3

CLASSIFIED UL

Floor Coating and Finishing Material
As To Slip Resistance Only
18 EL

NCL® *World Class Cleaning Solutions®*

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail: info@nclonline.com