FAST BREAK™

Routine Wood Cleaner

DESCRIPTION

Fast drying, neutral pH formula cleans wood floors to restore natural beauty and luster. Uses specially selected, naturally derived ingredients to remove soils from the wood surface.

PRODUCT FEATURES / BENEFITS

- Gently removes dirt
- Restores natural beauty and luster
- Creates dirt resistant barrier
- Improves resistance to water stains
- Improves slip resistance of wood floors

DIRECTIONS FOR USE

Floor Cleaning:

Sweep, vacuum and/or dust mop floor surface prior to cleaning with FAST BREAK™ Routine Wood Cleaner for optimum results. Dust mop floor surface using a dust mop treated with either ONE-ON-ONE™ Oil-based Dust Mop Treatment or MID-COURT™ Water-Based Dust Mop Treatment.

Routine Cleaning / Tacking:

DAMP MOPPING

1. In a mop bucket / wringer, mix FAST BREAK™ Routine Wood Cleaner at a ratio of 32 ounces concentrate per gallon of cool water (1:4 dilution ratio).
2. Use a clean fresh wet mop. Wring the wet mop out completely so not to flood the surface with cleaning solution. Damp mop, rinsing the wet mop frequently. Mop with the grain of the wood, until the floor is completely free of dirt and foreign material.
3. Allow the floor surface to dry before walking on it.

TACKING WITH TOWELS

1. In a mop bucket / wringer, mix FAST BREAK™ Routine Wood Cleaner at a ratio of 32 ounces concentrate per gallon of cool water (1:4 dilution ratio).
2. Soak the towels in the bucket of diluted solution. Make sure that they are completely wet. Wring out a towel thoroughly to remove excess cleaner solution until it is just damp.
3. Fold the dampened towel, place on the floor and wrap around a broom. Wipe the floor in long strokes without lifting the towel from the surface. Go with the grain of the wood. Reposition and refold towel frequently to expose a fresh clean surface. Repeat until the floor is completely free of dirt.
4. Allow the floor surface to dry before walking on it.

Interim Cleaning Process:

AUTOMATIC SCRUBBER:

An automatic scrubber must be working properly to clean wood floors. This includes the solution flow, scrubbing pads, squeegees and vacuums. Water should not be left standing on the floor surface. Do not attempt to clean a wood floor using an automatic scrubber that is not functioning properly.

1. Mix FAST BREAK™ Routine Wood Cleaner at a ratio of 2 ounces concentrate per gallon of cool water (1:64 dilution ratio) in the solution tank of an automatic scrubber. Mount red cleaning pad. Do not pour this cleaning solution directly on the wood floor. Avoid leaving excess liquid on surface.
2. Autoscrub the floor surface in a single pass. Do not allow water to stand on the floor surface. An individual with a pick-up mop or dry towels must follow behind the scrubber to pick up any water that is not picked up by the machine. Pay special attention to corners.
3. Allow floor surface to dry before walking on it.

SPOT CLEANING WITH TOWELS:

1. Wipe up liquid spills and sweep up dry soil spills as soon as possible.
2. Mix FAST BREAK™ Routine Wood Cleaner at a dilution ratio of 1:4 concentrate with cool / warm water in a mop bucket / wringer.
3. Apply FAST BREAK™ Routine Wood Cleaner solution to towel and wring out thoroughly. Do not apply cleaning solution directly on the wood floor surface.
4. Using the dampened towel, clean the area as required. Use a clean dry towel to wipe up excess cleaning liquid. Avoid leaving excess liquid on wood floor surface.
5. Allow floor surface to dry before walking on it.

SPECIFICATIONS

pH	7.6
Specific Gravity (g/cc)	0.99 ± 0.01
Color	Blue
Odor	Alcohol
VOC's (%)	17.8
VOC's (%) (at 1:4 dilution)	3.6
Flash Point (°F)	102
Flash Point (°F) (at 1:4 dilution)	144
Freeze-Thaw Stability	Excellent
Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

WARNING: FLAMMABLE LIQUID AND VAPOR.
KEEP OUT OF REACH OF CHILDREN.

Prevention: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/clothing and eye/face protection.

Response: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use appropriate media to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

For Commercial and Industrial Use Only

CLASSIFIED UL **Floor Coating and Finishing Material As to Slip Resistance Only 18EL**

World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com