BOLT™

Ultra Concentrated No-Rinse Speed Stripper

DESCRIPTION

Bolt is an ultra concentrated formula that quickly penetrates and removes even extreme floor finish build-up. Excellent wetting and slow drying features save time and labor. Compared to leading floor strippers Bolt™ is 2 to 4 times more active. It contains no caustics, and does not require a neutralizing flood rinse.

PRODUCT FEATURES / BENEFITS

- Ultra concentrated
- Lightning Fast Stripping Performance
- Superb wetting system, remains wet longer to eliminate re-wetting which adds extra work.
- Requires no flood rinse or neutralization step / Saves time by eliminating neutralizing and rinsing
- Low odor formula for use in virtually any situation.
- Low foaming makes cleanup easy with automatic scrubbers and wet pick-up vacuums.

DIRECTIONS FOR USE

For the rapid removal of all floor finishes and waxes from resilient flooring including: vinyl, vinyl asbestos, vinyl composition, asphalt, linoleum, and rubber tiles. Also ideal for finished non-resilient surfaces such as: terrazzo, marble, ceramic, quarry tile, concrete, and poured epoxy flooring. Although excellent for any type of equipment, greatest savings are realized when using automatic scrubbing equipment.

Follow dilution recommendations below. Dilute using cold water only.

Light/Normal Buildup: 4 oz per gallon of water (1:32)

Heavy Buildup (Burnished): 16 oz per gallon of water (1:8)

Quart Dilutions:

Light/Normal Buildup: 1 quart per 8 gallons of water (1:32)

Heavy Buildup (Burnished): 1 quart per 2 gallons of water (1:8)

Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old liquified finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

Note: As some asphalt tiles may be damaged by prolonged soaking in concentrated strippers, a spot test is recommended before general use.

SPECIFICATIONS

Color	Clear
Odor	Sassafras
pH	12.7 ± 0.3
Upper Cloud Point	> 130°F
Lower Cloud Point	< 33°F
Viscosity (cps)	< 5
Water Solubility	Complete
Finish Removal	Excellent
Damage to Resilient Tiles	Minimal
Density (lbs/gal)	7.9 ± 0.1
Specific Gravity (g/cc)	0.95 ± 0.01
Free Rinsing	Yes
Low Foaming	Yes
Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF SWALLOWED, IN CONTACT WITH SKIN OR IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF THE REACH OF CHILDREN

Precautionary statement:

Prevention:

Do not breathe mist or vapor. Use only in well-ventilated areas. Wear protective gloves/clothing and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Keep out of reach of children

Response:

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.

Storage: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

For Commercial and Industrial Use Only

Stripper

World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com

© TDS-1069-0515