BRITE EYES®

Wet Look Premium Grade Floor Finish

DESCRIPTION

An instant deep wet look thermoplastic floor finish which can be high speed burnished or maintained with conventional methods. This unique premium grade floor finish is manufactured in high pressure reactors using integrated latex and oligomeric polymer emulsions chemically combined with super high pressure micronized wax emulsions, interacted plasticizers, preservatives, coalescent additives, leveling aids, and deionized water to offer maximum performance.

PRODUCT FEATURES / BENEFITS

- Fast drying / Allows faster re-coating time and less waiting
- May be used with conventional or high speed floor maintenance system
- Flexible Film / Allows for easy removal of black heel marks and scratches
- Designed for ease of application / May be applied by any personnel without extensive training.
- Immediate Wet Look / Offers high appearance level without buffing
- Can be high speed burnished on a daily maintenance schedule / Allows versatility and reduced inventory levels of additional products

DIRECTIONS FOR USE

A premium quality floor finish that imparts a deep, mirror like gloss to all floors. Easy to apply, yields a surface which is durable and resistant to detergents, scuffing, slipping, and heel marking. Gives outstanding performance on vinyl, vinyl composition, asphalt, rubber, worn no-wax, and linoleum resilient flooring. Use also for concrete, terrazzo, sealed and painted wood, cork, and most other floor materials.

Floor Preparation: Strip floor of old finish and wax, paying particular attention to baseboards, corners, under furniture, and built up areas. Rinse thoroughly and allow to completely dry.

Application: If desired, one or two coats of an approved sealer may be used, prior to finish application. Using a clean mop or applicator, apply a thin uniform coat of finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24 hour period, and floor should be thoroughly dry before traffic is allowed in area.

SPECIFICATIONS

Type	Integrated latex and oligomeric polymer
Detergent Resistant	Yes (after 24 hr.)
pH	8.2 ± 0.3
Leveling	Superior
Drying time (minutes)	30
Odor	Acrylic
Color	White, opaque
Recoatability	Excellent
Removability	Excellent
Durability	Superior
Soil Resistance	Superior
Film	Clear, non-yellowing
Scuff Resistance	Superior
Freeze thaw stable	Yes
Black Mark Resistance	Superior
Flash Point	None
Deep Gloss Appearance	Superior
Powdering	Nil
Slip Resistance	Excellent
High Speed Burnishing	Excellent
Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a “Hazardous Chemical” as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only

FLOOR CARE

CLASSIFIED UL Floor Coating and Finishing Material As to Slip Resistance Only 18EL

World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com