



PATRIOT
 **USA SCAG**

**52" & 61"
models**

**True Commercial-Grade.
Incredible Value.**

Specifications

Engine Options:

- 22hp Kawasaki FX, air-cooled, twin cylinder, vertical shaft
- 23hp Kawasaki FX, air-cooled, twin cylinder, vertical shaft

Fuel Capacity/Design:

6.5 gallon fuel tank with molded-in cupholder & storage tray

Travel Control:

Twin steering controls with gas dampers for smooth, precise maneuverability. Levers are adjustable.

Ground Speed:

- 52" models: Up to 8.5mph forward, 5mph reverse
- 61" models: Up to 10mph forward, 5mph reverse

Main Frame Construction:

Steel tube frame, full-length, fully-welded

Drive Tires:

- 52" models: 22 x 9.5 - 12, 4-ply
- 61" models: 23 x 9.5 - 12, 4-ply

Caster Tires:

- 52" models: 13 x 5 - 6
- 61" models: 13 x 6.5 - 6

Caster Pivot Bearings:

Greaseable bearings

Drive System:

Dual Hydro-Gear ZT-3100 (52") or ZT-3400 (61") integrated transaxles with charge pumps and spin-on oil filters; steel plate oil filter guards protect filters

Mower Maintenance:

Low-maintenance mower design has fewer grease points, saving you maintenance time

Electrical System:

12 Volt battery. Solenoid shift starter.

Engine Guard:

Super-tough rear engine guard protects the engine compartment from potential impact damage when backing up

WWW.SCAG.COM



(Continued)



Belts:	Kevlar cord. Self-adjusting, spring-loaded, self-tightening.
Drive/Load Pulleys:	Split Steel pulleys. Steel dust and debris covers over idler pulley bearings to keep foreign material out and extend bearing life.
Instrument Panel :	Key switch, throttle, manual choke, PTO switch, digital hourmeter
Seat:	Adjustable, thick cushioned seat with padded arm rests; retractable seat belt
Foot Plate:	Extra-large foot plate for improved comfort; easy to get on and off of mower. Pierced, extruded steel tread ensures solid footing. Rubber iso-mounted for additional operator comfort.
PTO - Electric Clutch:	Ogura clutch with adjustable air-gap for long component life, 52" 87 ft/lb or 61" 150 ft/lb.
Cutter Decks:	52" or 61" deck. Floating, adjustable, anti-scalping design.
Cutter Deck Construction:	Welded steel with 7-gauge deck skirt, 10-gauge top with 11-gauge reinforcement plate/baffles
Cutter Deck Drive:	Belt driven -- Straight belt for long life, not a twisted "mule" drive
Anti-Scalp:	One roller on left-front edge, two rollers on center-front edge, skid plate at rear-center of deck
Cutter Deck Spindles:	Heavy-duty, no-maintenance spindles with cast aluminum housing & sealed ball bearings; reliable, worry-free performance day in and day out
Cutter Deck Height Adjustment:	Foot pedal/peg lift with self-locking mechanism at transport position. Large knurled foot pedal/peg for "no-slip" deck lifting.
Cutting Range:	1.5" to 5" in .25" increments. Easily adjustable while seated.
Number of Cutter Blades:	3 Marbain blades
Deck Leveling:	4-corner cutter deck adjustment mechanisms allow for easy deck leveling and pitch adjustment to ensure a smooth, even cut
Total Length:	<ul style="list-style-type: none"> • 52" models = 73" • 61" models = 79"
Total Width (with discharge chute in mowing position):	<ul style="list-style-type: none"> • 52" models = 64.5" • 61" models = 73.5"
Total Width (with discharge chute in transport position):	<ul style="list-style-type: none"> • 52" models = 53" • 61" models = 62"
Height (with ROPS):	<ul style="list-style-type: none"> • 52" models = 61" • 61" models = 61.5"
Height (with ROPS folded):	<ul style="list-style-type: none"> • 52" models = 46.5" • 61" models = 47"
Weight:	<ul style="list-style-type: none"> • 52" models = 840 lbs. • 61" models = 900 lbs.
Warranty:	<ul style="list-style-type: none"> • 3 Yr. / 500 Hour Non-Commercial Mower Warranty*—Parts & labor • 2 Yr. Commercial Mower Warranty*—Parts & labor • 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.

*See Limited Warranty statement for complete details.



All specifications subject to change without notice. Actual ground speeds may vary.
September 2017

