

PIZZAZZ

Soil & Finish Build Up Remover

DESCRIPTION

A highly active revolutionary product for removing heavy soil and floor finish build up from floors, baseboards and walls. Elimination of common volatile chemicals such as ammonia and butyl improves customer appeal. Ideal for areas sensitive to odors. Its gelled formula, in combination with fast acting penetrating solvents, allows maximum performance and labor savings.

Caustic free and self neutralizing to provide maximum surface and user safety.

PRODUCT FEATURES / BENEFITS

- · Can be used in confined or enclosed areas / Odorless
- Fast acting solubilizers / Cuts project time and labor
- Concentrated RTU formula / Removes many layers of burnished floor finish in a single application
- Clings to vertical surfaces and eliminates runs / Unique foam gel
- · Caustic free / Eliminates rinsing and saves labor

DIRECTIONS FOR USE

For rapid removal of heavy soil and floor finish build up on floors, baseboards and walls. Conveniently packaged for spray and mop removal in small areas, For rapid removal of heavy soil and floor finish build up on floors, baseboards and walls. Conveniently packaged for spray and mop removal in small areas, hard to reach spaces and for quick effortless floor finish repair work. Odor free and rinse free to allow use by any personnel in almost any environment.

Shake well and invert can for use. Spray cleaner 6 to 10 inches from the baseboard, floor or cleaning surface. Wipe off spray immediately. Allow cleaner to work for 5 minutes before removing with wet vacuum, damp wiping or mopping. Heavy buildups may require wet scrubbing using a pad or brush prior to removal.

NOTE: Do not apply on painted surfaces. Before using, determine suitability and safety of this product on surface to be cleaned.

SPECIFICATIONS

Annorman	Cliabthy viagous gol	0/ \/OC:	> 5.0
Appearance	Slightly viscous ger	% VOC:	> 5.0
Color	Light Straw	Stripping	Outstanding
Odor	Non-Descriptive	Free Rinsing	Yes
Propellant	Propane/Butane Mixture	Shelf Life1 year minimum in original unopened container	
pH: (as is)	11.70 ± 1.0		

SAFETY INFORMATION

WARNING: IRRITANT: MAY BE HARMFUL IF SWALLOWED. CAUSES SKIN AND EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin, eyes and clothing. Do not ingest.

FIRST AID: Eyes: Flush with water for 15 minutes. Get medical aid. **Skin:** Thoroughly wash with water and apply emollient

cream. If irritation persists, get medical aid. **Ingestion:** Do not induce vomiting. Give milk, egg white, gelatin or water. Get immediate medical aid.

FOR PROFESSIONAL USE ONLY



HMIS HAZARD CODE			
1	HEALTH		
1	FLAMMABILITY		
0	REACTIVITY		
В	PERSONAL PROTECTION		



NATIONAL CHEMICAL LABORATORIES, INC.



SAFETY DATA SHEET

Section 1 - Identification

Product Identifier PIZZAZZ Soil & Finish Build Up Remover

Other means of identification 2008

Recommended use Soil & Floor Finish Build-Up Remover
Recommended restrictions For commercial and industrial use only.

Manufacturer / Importer / Supplier / Distributor Information

Company Name National Chemical Laboratories of PA, Inc.
Address 401 N. 10th Street - Philadelphia, PA 19123

 Telephone
 1 (215) 922-1200

 Supplier Email
 info@nclonline.com

 Contact
 CHEM-TEL

 Emergency Phone
 1 (800) 255-3924

Section 2 - Hazard(s) Identification

SDS Hazards and Warnings are based on the undiluted product. Refer to diluted SDS for Ready-To-Use Hazards and Warnings.

Classification Category **Physical Hazards** Gasses under pressure Liquefied gas **Health Hazards** Acute toxicity, dermal Δ Acute toxicity, inhalation 4 Acute toxicity, oral 1 Serious eye damage/eye irritation 1 Skin corrosion/irritation 1R

OSHA defined hazards Label Elements

Hazard Symbol



Signal Word Danger

Hazard Statement Contains gas under pressure; may explode if heated. Causes severe skin burns and eye damage. Harmful if inhaled. Harmful if

swallowed.

Not Classified.

Precautionary statement

Prevention Avoid breathing fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection.

Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Keep out of reach of children.

Response IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. If in eyes: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Storage Protect from sunlight. Do not expose to temperatures exceeding 122°F/50°C. Store in a well-ventilated place.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC)

None known.

Section 3 - Composition/Information on ingredients

Mixture			
Hazardous Components	Ingredient Name	CAS #	%
	2-(2-Butoxyethoxy) Ethanol	112-34-5	5 - 10
	Dipropylene Glycol Butyl Ether	29911-28-2	5 - 10
	Sodium dimethylbenzenesulfonate	1300-72-7	5 - 10
	2-Amino Ethanol	141-43-5	20 - 30
	Butane	106-97-8	1 - 4
	Propane	74-98-6	1 - 2

Composition Comments Components not listed are either non-hazardous or are below reportable limits.

Section 4 - First-aid Measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

None known

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Eye contact

Rinse mouth. Do not induce vomiting without advice from poison control center.

Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Most Important symptoms

/effects, acute and delayed

Burning pain and severe corrosive skin damage. Headache. Nausea, vomiting. Irritation of nose and throat. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result. May cause respiratory irritation.

Water fog. Dry chemical powder. Carbon dioxide (CO2).

Contents under pressure. Containers may explode when heated.

Indication of immediate medical attention and special treatment

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General Information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Section 5 - Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment

/instructions

Specific Methods

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard fire fighting procedures and consider the hazards of other involved materials.

Section 6 - Accidental release measures

Personal precautions, protective equipment and emergency procedures.

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering

them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Section 7 - Handling and storage

Precautions for safe handling

HARMFUL IF INHALED OR SWALLOWED. VAPOR HARMFUL. CAUSES SEVERE EYE AND SKIN DAMAGE. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Do not eat, drink or smoke when using this product. Keep out of reach of children. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 122°F/50°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 - Exposure control/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Type Value 2-Amino Ethanol (CAS 141-43-5) TWA 6 mg/m³, 3 ppm Butane (CAS 106-97-8) TWA 1000 ppm Propane (CAS 74-98-6) TWA 1000 ppm

US. ACGIH Threshold Limit Values

Component Type Value Propane (CAS 74-98-6) 1000 ppm TLV Butane (CAS 106-97-8) TLV 1000 ppm

2-Amino Ethanol (CAS 141-43-5) STEL 6 ppm Form

Form

2-Amino Ethanol (CAS 141-43-5) TWA 3 ppm 2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5) TWA Inhalable fraction and vapor. 10 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components Type Value

2-Amino Ethanol (CAS 141-43-5) STFL 15 mg/m³, 6 ppm 2-Amino Ethanol (CAS 141-43-5) TWA 8 mg/m^3 , 3 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Use personal protective equipment as required. Keep working clothes separately.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne

levels to an acceptable level. Provide

eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved chemical safety goggles. Provide an emergency eye wash fountain and quick drench shower in the

immediate work area.

Skin protection

Hand protection Wear chemical-resistant, impervious gloves. Suitable gloves can be recommended by the glove supplier.

Other If conditions risk exposure, wear suitable protective clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or Respiratory protection

to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material considerations

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants

Section 9 - Physical and chemical properties

Appearance

Physical state Gas/Liquid mixture.

Aerosol. Liquefied gas. Clear, thin liquid. Form

Color Straw. Odor Ammoniacal. Odor threshold Not available. рΗ 123

Melting point/freezing point

Initial boinging point and

Not available. 212 °F (100 °C) liquid

boiling range

Flash point No flash point. **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available. Flammability limit - upper (%) Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available. Vapor density Not available.

Relative density 1.02 ± 0.01 @ (75°F) (liquid)

Relative density temperature 75 °F (23.89 °C) Solubilities Soluble. (liquid) Partition Coefficient n-Not available.

octanol/water

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Viscosity Not available. **Viscosity Temperature** 75 °F (23.89 °C)

Other Information

VOC's 5 - 6 %

Pressure 68 - 80 psig @ 70F

Section 10 - Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possiblity of hazardous reactions Hazardous polymerization does not occur.

Conditions to AvoidAvoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous DecompositionNo hazardous decomposition products are known.

Products

Section 11 - Toxicological information

Information on likely routes of exposure

Ingestion Causes digestive tract burns.

Inhalation May cause respiratory tract irritation. This product may be aspirated onto the lungs and cause chemical pneumonitis.

Skin contact Causes severe skin burns.

Eve contact Causes serious eve damage.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects.

Acute toxicity May be harmful if swallowed.

Results Components Level Type Code **Species** 2-Amino Ethanol (CAS 141-43-5) Acute Dermal LD50 Rabbit 1025 mg/kg Acute Oral LD50 Rat 1715 mg/kg 2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5) Acute Dermal LD50 Rabbit 2764 mg/kg, (M Sodium dimethylbenzenesulfonate (CAS 1300-72-7) Acute Dermal LD50 Rabbit >2000 mg/kg Acute Oral LD50 Rat 7200 mg/kg

Skin corrosion/irritation Causes severe skin burns. Prolonged or repeated skin contact may cause drying.

Serious eye damage/ eye

irritation

Causes serious eye damage.

Respiratory sensitizationThis product is not expected to cause respiratory sensitization. **Skin sensitization**This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

Section 12 - Ecological Information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or

frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coeficient n-octanol / water log (Kow)

 Components
 Results

 2-Amino Ethanol (CAS 141-43-5)
 -1.31

 2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5)
 0.56

 Dipropylene Glycol Butyl Ether (CAS 29911-28-2)
 1.52 (est.)

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine

disruption, global warming potential) are expected from this component.

Section 13 - Disposal considerations

Disposal instructions Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material

products and its container must be disposed of in a safe manner.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers

may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

Section 14 - Transport information

DOT

UN number UN1950
Proper shipping name Aerosols
Transport hazard class(es) 2.2
Subsidary class(es) 8

Packing group Not Applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Labels required 2.2, 8
Packaging exemption 306

Packaging non bulk None/Ninguno
Packaging bulk None/Ninguno

Comment This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped

as a limited quantity until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the

The state of the s

"Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name Aerosols, non-flammable, corrosive, containing substances in Class 8, Packing Group III

Transport hazard class(es) 2.2 Subsidary class(es) 8

Packaging group Not Applicable.

Environmental hazardsNo.Labels required2.2, 8ERG Code10L

Special precautions for user

Other Information

Read safety instructions, SDS and emergency procedures before handling.

Passenger and Cargo Allowed.

aircraft

Cargo aircraft only Allowed.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950
UN proper shipping name AEROSOLS
Transport hazard class(es) 2.2
Subsidary class(es) 8

Packaging group Not Applicable.

No.

Environmental hazards
Marine pollutant

Labels required 2.2, 8
EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

Transportation in bulk Not applicable.

according to Annex II of MARPOL 73/78 and IBC Code

Section 15 - Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR707, Subpt. D)

Components Result Comment

Butane (CAS 106-97-8) N/A%
Propane (CAS 74-98-6) 20-30%

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

CERCLA Hazardous Substance List (40 CFR 302.4

Components Result 2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories Immediate Hazard Yes

Delayed Hazard No

Fire Hazard No
Pressure Hazard Yes
Reactivity Hazard No

SARA 302 Extremely hazardous substance Not regulated.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

 Chemical name
 CAS #
 % by wt.

 2-(2-Butoxyethoxy) Ethanol
 112-34-5
 5 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HSPs) List

Components

2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) 2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5)

Safe Drinking Water Act (SDWA) Not regulated.
Food and Drug Administration (FDA) Not regulated.

US state regulations

US.Massachusetts RTK - Substance List Components

Propane (CAS 74-98-6) Butane (CAS 106-97-8)

2-Amino Ethanol (CAS 141-43-5)

2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5)

US.New Jersey Worker and Community Right-to-Know Act Components

Propane (CAS 74-98-6) Butane (CAS 106-97-8)

2-Amino Ethanol (CAS 141-43-5)

2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5)

US.Pennsylvania RTK - Hazardous Substances Components

Propane (CAS 74-98-6) Butane (CAS 106-97-8)

2-Amino Ethanol (CAS 141-43-5)

2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5)

US.Rhode Island RTK Components

2-Amino Ethanol (CAS 141-43-5)

2-(2-Butoxyethoxy) Ethanol (CAS 112-34-5)

US - California Propsition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This

material is not known to contain any chemicals currently listed as carcinogens or

reproductive toxins.

International Inventories

Country(s) or region **Inventory Name** On Inventory (yes/no)* Australian Inventory of Chemical Substances (AICS) Australia Yes Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes **European Inventory of Existing Commercial Chemical Substances (EINECS)** Europe Europe **European List of Notifed Chemical Substances (ELINCS)** No Japan Inventory of Existing and New Chemical Substances (ENCS) Nο **Existing Chemicals List (ECL)** Korea No **New Zealand Inventory** New Zealand Yes **Philippine Inventory of Chemicals and Chemical Substances Philippines** Yes **Unites States Puerto Rico** Toxic Substances Control Act (TSCA) Inventory Yes

Section 16 - Other information, including date of preparation or last version

Issue date 4/17/2015 Version # 01

DisclaimerThe information contained herein was obtained from current and reliable sources. However, the data is provided without any

warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS.

Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this

product which may not be reflected in this SDS. The user should

review these regulations to ensure full compliance.

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

^{*}A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

For rapid removal of heavy soil and floor finish build up on floors, baseboards and walls. Conveniently packaged for spray and mop removal in small areas, hard to reach spaces and for quick effortless floor finish repair work. Low oder and rinse free formula for use by any personnel in almost any environment.

DIRECTIONS FOR USE

Shake well and invert can for use. Spray cleaner 6 to 10 inches from the baseboard, floor or cleaning surface. Allow cleaner to work for 5 minutes before removing with wet vacuum, damp wiping or mopping. Heavy buildups may require wet scrubbing using a pad or brush prior to removal.

INSTRUCCIONES PARA USO:

Agite bien e invierta la lata para su uso. Pulverice el limpiador 6 a 10 pulgadas de la baseboard, del piso o de la superficie de la limpieza. Permita que el limpiador trabaje durante 5 minutos antes de retirar con aspirador húmedo, limpieza húmeda o fregado. Las acumulaciones pesadas pueden requerir lavado húmedo usando una almohadilla o cevillo antes de la remoción.



DANGER: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. HARMFUL IF SWALLOWED. HARMFUL IN CONTACT WITH SKIN. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF INHALED. KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Avoid breathing fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Keep out of reach of children.

Response: IF SWALLOWED: Immediately call a POISON Center or doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 122°F/50°C. Store in a well-ventilated place

Disposal: Dispose of waste and residues in accordance with local authority requirements.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first aid measures. SDS for this product is available on the web at www.nclonline.com

PELIGRO: CONTIENE GAS A PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA. NOCIVO POR INGESTIÓN. DAÑINO EN CONTACTO CON LA PIEL. PROVOCA QUEMADURAS EN LA PIEL Y LESIONES OCULARES GRAVES. NOCIVO POR INHALACIÓN. MANTENER FUERA DEL ALCANCE DE LOS NIÑOS.

Consejos de prudencia

Prevención: Evite respirar humo / gas / niebla / vapores / aerosoles. Use guantes de protección / ropa de protección / protección ocular / protección facial. Recipiente a presión: No perforar o quemar, incluso después de su uso. Lávese bien después de manipularlo. Mantener fuera del alcance de los niños.

Respuesta: EN CASO DÉ INGESTIÓN: llamar inmediatamente un Centro de Control de Envenenamientos o a un médico o médico. Si en los ojos: Enjuague con cuidado con agua durante varios minutos. Quite los lentes de contacto, si los hay, y muy fácil de hacer. Continúe enjuagando. Si persiste la irritación de los ojos: obtener una opinión médica y de atención.

Almacenamiento: Proteger de la luz solar. No lo exponga a temperaturas que exceden 122 °F/ 50 °C. Almacenar en un lugar bien ventilado.

Eliminación: Deshacerse de los desechos y residuos de conformidad con los requisitos de la autoridad.

Este producto es una "sustancia química peligrosa" que se define por la OSHA Hazard Communication Standard,
29 CFR 1910,1200 .Todos los componentes son de la EPA de EE.UU. Lista de inventario TSCA.

Medidas additional de primeros auxilios:

Lea toda la etiqueta y SDS antes de usar este producto, así como medidas adicionales de primeros auxilios. SDS para el artículo está disponible en la web en www.nclonline.com

CONTAINS: 2-(2-Butoxyethoxy) Ethanol CAS# 112-34-5, Dipropylene Glycol Butyl Ether CAS# 29911-28-2, Sodium dimethylbenzenesulfonate CAS# 1300-72-7, 2-Amino Ethanol CAS# 141-43-5, Butane CAS# 106-97-8, Propane CAS# 74-98-6





To learn more about this product, scan this QR code to visit our website ** MADE IN USA **

LA-0001-2008-01 ©









Strippers

Pizzazz[™]

Soil and Floor Finish Build-up Remover

Utilizing fast acting solubilizers in a unique foaming gel to rapidly remove heavy soils & floor finish build-up from floors, baseboards & walls.

DANGER: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. HARMFUL IN CONTACT WITH SKIN. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF INHALED. KEEP OUT OF REACH OF CHILDREN. See side panel for additional precautionary statements.

PELIGRO: CONTIENE GAS A PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA. NOCIVO POR INGESTIÓN. DAÑINO EN CONTACTO CON LA PIEL. PROVOCA QUEMADURAS EN LA PIEL Y LESIONES OCULARES GRAVES. NOCIVO POR INHALACIÓN. MANTENER FUERA DEL ALCANCE DE LOS NIÑOS.

Ver panel lateral para las medidas preventivas adicionales.

NET WEIGHT: 18 oz. (1lb. 2 oz.) (510 g.)

National Chemical Laboratories, Inc. Philadelphia, PA 19123 USA • (800) 628-2436 www.nclonline.com

Product No.: 2008