P&G PRO LINE

AMBASSADOR

P&G PRO LINE PRODUCTIVITY POWER

Great Burnish Response with Frequent Burnishing of 3 to 5 Times Per Week

Product Order # 14

The floor finish designed to deliver a “wet look” gloss with frequent UHS (ultra high speed) burnishing habits.

- Great burnish response that “pops” with 2500+ rpm propane, battery or electric equipment
- Outstanding application among a broad range of environmental conditions and application techniques
- Excellent lay-down shine
- Resistant to dirt, scratching, scuffing and marking.
- Formulated with special acrylic copolymer technology to withstand heavy traffic & maintain high shine
- Exceeds UL slip resistance classification.
- Compliant with California Air Resources Board VOC (Volatile Organic Compound) limit.

Product Specifications

% Solids	20
pH	8.5
Specific Gravity	1.024
Viscosity, cps	15
Color	White

Coverage per gallon, sq. ft.	1,500 – 2,500
Floor Types	All finishable floor types, including VCT, terrazzo, vinyl

Recommended For

- Retail, Supermarket
- Healthcare
- Government
- Commercial facilities
- Building service contractors

Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

Another similar P&G Pro Line finish to consider: ***Grand Opening*** is a comparable UHS finish, designed for the ultimate in “wet look” gloss with daily burnishing.

SIZE	DESCRIPTION
4 - 1 gal./3.78L	Ready-to-use
1 – 5 gal./18.9L	Ready-to-use

P&G PRO LINE

AMBASSADOR

P&G PRO LINE PRODUCTIVITY POWER

Great Burnish Response with Frequent Burnishing of 3 to 5 Times Per Week

DIRECTIONS FOR USE

Initial Application:

1. Remove all old wax and floor finish with appropriate PGPL Floor Finish Stripper.
2. Rinse floor thoroughly with clear water and allow to dry.

3. Using a clean, dry rayon or microfiber flat mop, apply a uniform coat of finish. Allow to dry thoroughly (typically 30-40 minutes). Apply additional coats in the same manner and let dry. For very porous or highly worn floors, one initial coat of floor sealer is recommended.

Day-to-Day Maintenance:

1. Sweep or dust mop as necessary.
2. Auto-scrubbing is recommended or damp mopping with PGPL Finish Floor Cleaner.

3. For Frequent burnishing between 3 to 5 times per week to maintain gloss.

4. Periodic deep scrub and recoat will be required to replenish the base film for best burnish results.

	YES	NO
Acrylic Copolymer Base	**X**	
Metal Interlock	**X**	
UHS Repairable	**X**	
UL Classified as to Slip Resistance	**X**	
Strips Easily	**X**	
DOT Regulated		**X**