

QWIK-SCRUB Scrub & Recoat Cleaner

DESCRIPTION

QWIK-SCRUB is a heavy-duty, water-based cleaning concentrate designed for scrub / re-coat maintenance procedures. It is ideal for use in automatic scrubbers equipped with proper floor pad or brush. Using a mild pH range formulation, QWIK-SCRUB aggressively removes embedded soils and scuffs in upper layers of finish film, and prepares the surface for re-coating with a minimum of rinsing, saving time and labor.

PRODUCT FEATURES / BENEFITS

- Mild range pH formulation
- · Aggressively removes embedded soils / scuffs

DIRECTIONS FOR USE

DILUTE PRODUCT AS FOLLOWS:

Moderate soil /build-up Light finish removal Heavy soil /build-up Moderate finish removal Dilute 5 oz. (1:25) of QWIK-SCRUB per gallon of warm water Dilute 10 oz. (1:12) of QWIK-SCRUB per gallon of warm water

SCRUB/RE-COAT USING STANDARD 175 RPM FLOOR MACHINE:

Dilute QWIK-SCRUB in mop bucket according to above dilution directions. Liberally mop solution onto floor surface and allow to dwell for 1 to 4 minutes (depending on how deeply it is desired to scrub). With machine and scrub floor pad or brush, scrub surface of floor until all embedded soils and scuffs are removed from finish. After scrubbing, remove solution from floor with wet-dry

SPECIFICATIONS

Color	Pink
Odor	Buttery Orange
pH (Concentrate)	9.9 ± 0.3
Upper Cloud	> 140°F
Lower Cloud	< 25°F
Flash Point	None

Reduced rinsing saves time and labor

Use with standard floor machine or with automatic scrubber

vacuum or a clean mop. Damp mop rinse with clear water to remove any excess residue. Allow floor to completely dry prior to re-coating.

SCRUB/RE-COAT USING AUTOMATIC SCRUBBER:

Dilute QWIK-SCRUB in mop bucket according to above dilution directions. Liberally mop solution onto floor surface and allow to dwell for 1 to 4 minutes (depending on how deeply it is desired to scrub). Fill autoscrubber with clear water, mount scrubbing pad or medium grade brush. With vacuum off and squeegee up, scrub the floor until all embedded soils and scuffs are removed from finish. Lower squeegee and vacuum all scrubbing solution. Using clear water from the autoscrubber, rinse floor to remove any excess residue. Allow floor to completely dry prior to recoating.

Biodegradable	Yes
Specific Gravity (g/cc)	1.01 ± 0.01
Density (lbs/gal)	8.4 ± 0.1
Free Rinsing	Yes
Non Corrosive	Yes
Shelf Life 1 year minimum in original uno	pened container

SAFETY INFORMATION

WARNING: MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN.

Prevention: Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Wear eye/face protection.

Response: If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse.

Storage: Store away from incompatible materials.

Disposal: Dispose of waste and residues in accordance with local authority requirements.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

For Commercial and Industrial Use Only



CLEANER



401 N. 10th Street • Philadelphia, PA 19123 1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517 www.nclonline.com • e-mail:info@nclonline.com





Contact

Emergency Phone

NATIONAL CHEMICAL LABORATORIES, INC.

SAFETY DATA SHEET

	Section 1 - Identification
Product Identifier	QWIK-SCRUB Scrub & Recoat Cleaner
Other means of identification	0955
Recommended use	Detergent.
Recommended restrictions	For commercial and industrial use only.
Manufacturer / Importer / Suppli	er / Distributor Information
Company Name	National Chemical Laboratories of PA, Inc.
Address	401 N. 10th Street - Philadelphia, PA 19123
Telephone	1 (215) 922-1200
Supplier Email	info@nclonline.com

CHEM-TEL

1 (800) 255-3924

Section 2 - Hazard(s) Identification

SDS Hazards and Warnings are based on the undiluted product. Refer to diluted SDS for Ready-To-Use Hazards and Warnings.

	Classification	Category				
Physical Hazards	Not Classified	<u> </u>				
Health Hazards	Sensitization, skin	1				
	Serious eye damage/eye irritation	2A				
OSHA defined hazards	Not Classified.					
abel Elements						
Hazard Symbol						
	\checkmark					
Signal Word	Warning					
Hazard Statement	May cause an allergic skin reaction. Causes serior	us eye irritation.				
Precautionary statement						
Prevention	Avoid breathing mist or vapor. Wash thoroughly workplace. Wear protective gloves. Wear eye/fa		t not be allowed out of the			
Response	If on skin: Wash with plenty of water. If in eyes: present and easy to do. Continue rinsing. Specifi advice/attention. If eye irritation persists: Get m	c treatment (see this label). If skin irritation or ra	sh occurs: Get medical			
	Store away from incompatible materials.					
Storage	Store away from incompatible materials.					
Storage Disposal	Store away from incompatible materials. Dispose of contents/container in accordance wit	h local/regional/national/international regulation	15.			
-		h local/regional/national/international regulation	ns.			
Disposal Hazard(s) not otherwise	Dispose of contents/container in accordance wit		15.			
Disposal Hazard(s) not otherwise classified (HNOC)	Dispose of contents/container in accordance wit None known.		15.			
Disposal Hazard(s) not otherwise classified (HNOC)	Dispose of contents/container in accordance wit None known.		ns. %			
Disposal Hazard(s) not otherwise classified (HNOC) /ixture	Dispose of contents/container in accordance wit None known. Section 3 - Composition/Info	ormation on ingredients				
Disposal Hazard(s) not otherwise classified (HNOC) Mixture	Dispose of contents/container in accordance wit None known. Section 3 - Composition/Info Ingredient Name	ormation on ingredients CAS#	%			
Disposal Hazard(s) not otherwise classified (HNOC) Vixture	Dispose of contents/container in accordance wit None known. Section 3 - Composition/Info Ingredient Name 2-Butoxyethanol	CAS # 111-76-2	% 1 - 5			
Disposal Hazard(s) not otherwise classified (HNOC) Vixture	Dispose of contents/container in accordance wit None known. Section 3 - Composition/Info Ingredient Name 2-Butoxyethanol Nonylphenol, ethoxylated	CAS # 111-76-2 9016-45-9	% 1-5 1-5			
Disposal Hazard(s) not otherwise classified (HNOC) Aixture	Dispose of contents/container in accordance wit None known. Section 3 - Composition/Info Ingredient Name 2-Butoxyethanol Nonylphenol, ethoxylated Alcohols, C12-13 Ethoxylated	CAS # 111-76-2 9016-45-9 66455-14-9 8008-57-9	% 1 - 5 1 - 5 0.1 - 1			
Disposal Hazard(s) not otherwise classified (HNOC) Aixture Hazardous Components	Dispose of contents/container in accordance wit None known. Section 3 - Composition/Info Ingredient Name 2-Butoxyethanol Nonylphenol, ethoxylated Alcohols, C12-13 Ethoxylated Orange Oil	CAS # 111-76-2 9016-45-9 66455-14-9 8008-57-9 aid Measures	% 1 - 5 1 - 5 0.1 - 1			
Disposal Hazard(s) not otherwise classified (HNOC) Mixture	Dispose of contents/container in accordance wit None known. Section 3 - Composition/Info Ingredient Name 2-Butoxyethanol Nonylphenol, ethoxylated Alcohols, C12-13 Ethoxylated Orange Oil Section 4 - First-	CAS # 111-76-2 9016-45-9 66455-14-9 8008-57-9 aid Measures ion persists. wash skin with soap and water. In case of eczem	% 1 - 5 1 - 5 0.1 - 1 0.1 - 1			
Disposal Hazard(s) not otherwise classified (HNOC) Mixture Hazardous Components	Dispose of contents/container in accordance wit None known. Section 3 - Composition/Info Ingredient Name 2-Butoxyethanol Nonylphenol, ethoxylated Alcohols, C12-13 Ethoxylated Orange Oil Section 4 - First-o Move to fresh air. Get medical attention if irritat Remove contaminated clothing immediately and	CAS # 111-76-2 9016-45-9 66455-14-9 8008-57-9 aid Measures ion persists. wash skin with soap and water. In case of eczem ructions. Get medical attention if irritation persis at least 15 minutes. Remove contact lenses, if pre-	% 1 - 5 1 - 5 0.1 - 1 0.1 - 1 a or other skin disorders: ts.			

/effects, acute and delayed all Indication of immediate medical Planting attention and special treatment Planting General Information End Suitable extinguishing media W Unsuitable extinguishing D media Planting	Ilergic skin reaction. Derr Provide general supportive Insure that medical perso ontaminated clothing bed Sectio Vater fog. Foam. Dry cher Do not use water jet as an	natitis. e measures an nnel are awar fore reuse. on 5 - Fir mical powder.	nd treat s re of the r e-fig	··· ·	er observation. Symptoms ma					
Indication of immediate medical Platention and special treatment General Information Electron Suitable extinguishing media W Unsuitable extinguishing D media Specific hazards arising from D	rovide general supportive insure that medical perso ontaminated clothing bet Sectio Vater fog. Foam. Dry cher to not use water jet as an	e measures an innel are awar fore reuse. on 5 - Fir mical powder.	re of the	material(s) involved, and take pre						
General Information End Constrained Constrained Constr	ontaminated clothing bef Sectio Vater fog. Foam. Dry cher Do not use water jet as an	fore reuse. on 5 - Fir mical powder.	r e-fig	··· ·	cautions to protect themselve	y be delayed.				
Unsuitable extinguishing D media Specific hazards arising from D	Vater fog. Foam. Dry cher Do not use water jet as an	mical powder.		hting magging	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.					
Unsuitable extinguishing D media Specific hazards arising from D	o not use water jet as an		Carbon	nting measures						
Unsuitable extinguishing D media Specific hazards arising from D	-	extinguisher,		dioxide (CO2).						
	uring fire gasos bazarda		as this v	vill spread the fire.						
	During fire, gases hazardous to health may be formed.									
and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.									
Fire-fighting equipment N /instructions	Move containers from fire area if you can do it without risk. Use water spray to keep fire-exposed containers cool.									
General fire hazards N	lo unusual fire or explosio	on hazards not	ted.							
Specific Methods U	Ise standard firefighting p	procedures and	d consid	er the hazards of other involved r	naterials.					
	Section 6	5 - Accid	ental	release measures						
equipment and emergency approcedures. construction of the second	ppropriate protective equipation on tainers or spilled mate	uipment and c rial unless wea icant spillages	clothing aring ap	away from and upwind of spill/le during clean-up. Avoid breathing propriate protective clothing. Ens pe contained. For personal protect	mist or vapor. Do not touch da ure adequate ventilation. Loca	imaged Il authorities				
containment and cleaning up SI cc L/ pi w	MALL SPILLAGE: Wipe up ontamination. ARGE SPILLS: Stop the flo lastic sheet to prevent sp vaterways, sewer, basem	p with absorbe ow of material preading. Abso ents or confine	l, if this i orb in vei ed areas	rial (e.g. cloth, fleece). Clean surf s without risk. Dike the spilled ma miculite, dry sand or earth and p . Following product recovery, flus se. For waste disposal, see sectio	terial, where this is possible. C ace into containers. Prevent e h area with water.	Cover with				
Environmental precautions A	woid discharge into drain	s, water cours	ses or on	to the ground.						
	Secti	ion 7 - H	andli	ng and storage						
			ng. Avoid	breathing mist or vapor. Avoid p	vales and average Drawide as					
		iate personal		equipment. Observe good indu		lequate				
Conditions for safe storage, Si including any incompatibilities			protectiv		strial hygiene practices.	lequate				
_	tore in original tightly clo	osed container	protectiv Store a	ve equipment. Observe good indu	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatibilities	tore in original tightly clo	xposure	protectiv Store a	re equipment. Observe good indu way from incompatible materials	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatibilities Occupational exposure limits	tore in original tightly clo	ssed container xposure .910.1000)	protectiv Store a	re equipment. Observe good indu way from incompatible materials	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air	tore in original tightly clo Section 8 - E.	ssed container xposure .910.1000)	cont	ve equipment. Observe good indu way from incompatible materials rollpersonal protect	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatib ⁱ lities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2)	ssed container xposure .910.1000)	Type	ve equipment. Observe good indu way from incompatible materials rollpersonal protect	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2)	ssed container xposure 910.1000)	Type	ve equipment. Observe good indu way from incompatible materials rollpersonal protect	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value	tore in original tightly clo Section 8 - E2 Contaminants (29 CFR 1 2) 25	ssed container xposure 910.1000)	rotectiv Store a cont Type TWA	ve equipment. Observe good indu way from incompatible materials rollpersonal protect Value 240 mg/m ³ , 50 ppm	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2) 22	ssed container xposure 910.1000)	rotectiv Store a cont Type TWA Type	ve equipment. Observe good indu way from incompatible materials rolipersonal protect Value 240 mg/m ³ , 50 ppm Value	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2) 22	sed container xposure 910.1000)	rotectiv Store a cont Type TWA Type	ve equipment. Observe good indu way from incompatible materials rolipersonal protect Value 240 mg/m ³ , 50 ppm Value	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2) 2) mical Hazards	910.1000)	rotectiv Store a cont Type TWA Type TWA	ve equipment. Observe good indu way from incompatible materials rollpersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm	strial hygiene practices. (see Section 10 of the SDS).	lequate				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2) 2) mical Hazards 2)	910.1000)	rotectiv Store a cont Type TWA Type TWA Type	ve equipment. Observe good indu way from incompatible materials rolipersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm Value	strial hygiene practices. (see Section 10 of the SDS).	Samplin				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components 2-Butoxyethanol (CAS 111-76-2	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2) 2) mical Hazards 2)	910.1000)	rotectiv Store a cont Type TWA Type TWA Type	ve equipment. Observe good indu way from incompatible materials rolipersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm Value	strial hygiene practices. (see Section 10 of the SDS).					
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH. BEIs. Biological Expos	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2) es 2) mical Hazards 2) sure Indices	910.1000)	rotectiv Store a cont Type TWA Type TWA Type	ve equipment. Observe good indu way from incompatible materials rollpersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm Value 24 mg/m ³ , 5 ppm	strial hygiene practices. (see Section 10 of the SDS).	Samplin				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chem Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH. BEIs. Biological Expose Components	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2) es 2) mical Hazards 2) sure Indices 2)	value 200 mg/g	rotectiv Store a cont Type TWA Type TWA Type	ve equipment. Observe good indu way from incompatible materials rolipersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm Value 24 mg/m ³ , 5 ppm Determinate Butoxyacetic acid (BAA),	strial hygiene practices. (see Section 10 of the SDS).	Samplin Time				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH. BEIs. Biological Expos Components 2-Butoxyethanol (CAS 111-76-2	Section 8 - E Section 8 - E Contaminants (29 CFR 1 2) mical Hazards 2) sure Indices 2) e see the source docume	value 200 mg/g	rype TWA Type TWA Type TWA Type TWA	ve equipment. Observe good indu way from incompatible materials rolipersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm Value 24 mg/m ³ , 5 ppm Determinate Butoxyacetic acid (BAA), with hydrolysis	strial hygiene practices. (see Section 10 of the SDS).	Samplin Time				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH. BEIs. Biological Expos Components 2-Butoxyethanol (CAS 111-76-2 Seutoxyethanol (CAS 111-76-2 * - For sampling details, please	Section 8 - E Section 8 - E Contaminants (29 CFR 1 2) mical Hazards 2) sure Indices 2) e see the source docume	Value 200 mg/g ant. Airborne Com	rype TWA Type TWA Type TWA Type TWA	ve equipment. Observe good indu way from incompatible materials rollpersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm Value 24 mg/m ³ , 5 ppm Determinate Butoxyacetic acid (BAA), with hydrolysis	strial hygiene practices. (see Section 10 of the SDS).	Samplin Time				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH. BEIs. Biological Expos Components 2-Butoxyethanol (CAS 111-76-2 * - For sampling details, please US. California Code of Regulation	Section 8 - E Section 8 - E Contaminants (29 CFR 1 2) mical Hazards 2) sure Indices 2) e see the source docume ns, Title 8, Section 5155.	Value 200 mg/g Airborne Com	Type TWA Type TWA Type TWA Type TWA Type TWA	ve equipment. Observe good indu way from incompatible materials rollpersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm Value 24 mg/m ³ , 5 ppm Determinate Butoxyacetic acid (BAA), with hydrolysis	strial hygiene practices. (see Section 10 of the SDS).	Samplin Time				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH. BEIs. Biological Expos Components 2-Butoxyethanol (CAS 111-76-2 * - For sampling details, please US. California Code of Regulation Components	tore in original tightly clo Section 8 - E: Contaminants (29 CFR 1 2) mical Hazards 2) sure Indices 2) e see the source docume ns, Title 8, Section 5155.	Value 200 mg/g Airborne Cont	Type TWA Type TWA Type TWA Type TWA Type TWA	ve equipment. Observe good indu way from incompatible materials rollpersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm Value 24 mg/m ³ , 5 ppm Determinate Butoxyacetic acid (BAA), with hydrolysis	strial hygiene practices. (see Section 10 of the SDS).	Samplin Time				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH. BEIs. Biological Expos Components 2-Butoxyethanol (CAS 111-76-2 * - For sampling details, please US. California Code of Regulation Components 2-Butoxyethanol (CAS 111-76-2	tore in original tightly clo Section 8 - E: Contaminants (29 CFR 1 2) mical Hazards 2) sure Indices 2) e see the source docume ns, Title 8, Section 5155.	Value 200 mg/g ent. Airborne Cont	Type TWA Type TWA Type TWA Type TWA Type TWA	value 240 mg/m³ , 50 ppm Value 240 mg/m³ , 50 ppm Value 20 ppm Value 24 mg/m³, 5 ppm Determinate Butoxyacetic acid (BAA), with hydrolysis	strial hygiene practices. (see Section 10 of the SDS).	Samplin Time				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH. BEIs. Biological Expos Components 2-Butoxyethanol (CAS 111-76-2 * - For sampling details, please US. California Code of Regulation Components 2-Butoxyethanol (CAS 111-76-2 US. California Code of Regulation Components 2-Butoxyethanol (CAS 111-76-2 US.Minnesota Hazardous Substat	tore in original tightly clo Section 8 - E: Contaminants (29 CFR 1 2) as 2) mical Hazards 2) sure Indices 2) e see the source docume ns, Title 8, Section 5155. 2) nces List (Minn. Rules 52	Value 200 mg/g ent. Airborne Cont	rotectiv Store a Cont Type TWA Type TWA Type TWA Type TWA taminan Exposur Can be a Exposur	value 240 mg/m ³ , 50 ppm Value 240 mg/m ³ , 50 ppm Value 20 ppm Value 24 mg/m ³ , 5 ppm Determinate Butoxyacetic acid (BAA), with hydrolysis	strial hygiene practices. (see Section 10 of the SDS).	Samplin Time				
including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Air Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH Threshold Limit Value Component 2-Butoxyethanol (CAS 111-76-2 US. NIOSH: Pocket Guide to Chen Components 2-Butoxyethanol (CAS 111-76-2 US. ACGIH. BEIs. Biological Expos Components 2-Butoxyethanol (CAS 111-76-2 * - For sampling details, please US. California Code of Regulation Components 2-Butoxyethanol (CAS 111-76-2 US. California Code of Regulation Components 2-Butoxyethanol (CAS 111-76-2 US. Minnesota Hazardous Substat Components	tore in original tightly clo Section 8 - E Contaminants (29 CFR 1 2) as 2) mical Hazards 2) sure Indices 2) e see the source docume ns, Title 8, Section 5155. 2) nces List (Minn. Rules 52 2)	Value 200 mg/g ent. Airborne Cont	rotectiv Store a Cont Type TWA Type TWA Type TWA Type TWA taminan Exposur Can be a Exposur	ve equipment. Observe good indu way from incompatible materials rollpersonal protect Value 240 mg/m ³ , 50 ppm Value 20 ppm Value 24 mg/m ³ , 5 ppm Determinate Butoxyacetic acid (BAA), with hydrolysis ts e bbsorbed though the skin.	strial hygiene practices. (see Section 10 of the SDS).	Samplin Time				

US.OSHA Table Z-1 Limits for	Air Contaminants (29 CFR 1910.100)		
Components		Exposure	
2-Butoxyethanol (CAS 111-7	76-2)	Can be absorbed though the skin.	
US.OSHA Table Z-1-A (29 CFR	1910.100)		
Components		Exposure	
2-Butoxyethanol (CAS 111-7	76-2)	Can be absorbed though the skin.	
US. Tennesee. OELs Occupation	onal Exposure Limkits, Table Z1A		
Components		Exposure	
2-Butoxyethanol (CAS 111-7	76-2)	Can be absorbed though the skin.	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.		
Individual protection measures, su	ich as personal protective equipment		
Eye/face protection	Face shield is recommended. Wear saf	ety glasses with side shields (or goggles).	
Skin protection			
Hand protection	Wear appropriate chemical resistant g	loves.	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
Respiratory protection	In case of insufficient ventilation, wear	suitable respiratory equipment.	
Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.	
General hygiene considerations	Contaminated work clothing should no	bt be allowed out of the workplace.	

Section 9 - Physical and chemical properties

Appearance	Pink turbid liquid.
Physical state	Liquid.
Form	Thin Liquid.
Color	Pink.
Odor	Orange.
Odor threshold	Not available.
рН	9.9
Melting point/freezing point	Not available.
Initial boiling point and	212 °F (100 °C)
boiling range	
Flash point	> 212.0 °F (> 100.0 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Similar to water.
Vapor density	Similar to water.
Relative density	1.01 ± 0.01
Relative density temperature	75 °F (23.89 °C)
Solubilities	100 % Soluble.
Partition Coefficient n-	Not available
octanol/water	
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Viscosity	<10 cSt
Viscosity Temperature	75 °F (23.89 °C)

Section 10 - Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possiblity of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to Avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous Decomposition	No hazardous decomposition products are known.
Products	

Section 11 - Toxicological information

	Section	11-1	IOXICOIOG	ical inform	ation			
Information on likely routes of e	xposure							
Ingestion	Expected to be a low inge							
Inhalation	Prolonged inhalation may be harmful.							
Skin contact	May cause an allergic skin reaction. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.							
Eye contact	Causes serious eye irritati	Causes serious eye irritation.						
Symptoms related to the physical, chemical and toxicological characteristics	Rash. Severe eye irritatior allergic skin reaction. Der		ms may include	stinging, tearing, r	edness, swelli	ing, and blurred visic	on. May cause an	
Information on toxicological effe	ects.							
Acute toxicity	May cause an allergic skin	reaction.						
Components			Level	Туре	Code	Species	Results	
2-Butoxyethano	I (CAS 111-76-2)		Acute	Dermal	LD50	Rabbit	400 mg/kg	
			Acute	Inhalation	LC50	Rat	450 mg/l, 4 hrs	
N			Acute	Oral	LD50	Rat	560 mg/kg	
	hoxylated (CAS 9016-45-9)		Acute	Oral	LD50	Mouse	4290 mg/kg, bw	
Alconois, C12-13	Ethoxylated (CAS 66455-14-9)	Acute	Dermal	LD50	Rat	> 2000 mg/kg, 2	
			Acute	Dermal	LD50	Rabbit	3300 mg/kg, 24	
			Acute	Inhalation	LC50	Rat	> 100 mg/m³, 6 > 1.6 mg/l, 4 Hc	
Skin corrosion/irritation	Prolonged skin contact ma	ay cause t	emporary irrita	tion.				
Serious eye damage/ eye irritation	Causes serious eye irritati	on.						
Respiratory sensitization	This product is not expect	ed to caus	se respiratory se	ensitization.				
Skin sensitization	May cause an allergic skin	reaction.						
Germ cell mutagenicity	No data available to indica	ate produ	ct or any compo	onents present at g	reater than 0.	.1% are mutagenic o	r genotoxic.	
Carcinogenicity	This product is not consid	ered to be	e a carcinogen b	y IARC, ACGIH, NT	P, or OSHA.			
IARC Monographs. Overall Evalu	ation of Carcinogenicity		Decult	Comm	ant			
Component 2-Butoxyethanol (CAS 111-76-2)			Result 3			o carcinogenicity to		
			5	huma		s careinogenieity to		
Reproductive toxicity	This product is not expect	ed to caus	se reproductive	or developmental	effects.			
Specific target organ toxicity - single exposure	Not classified.							
Specific target organ toxicity - repeated exposure	Not classified.							
Aspiration hazard	Not classified.							
Chronic effects	May be harmful if absorbe 2-Butoxy ethanol may be have not been observed in	absorbed	through the ski			epeated and prolong	ged. These effects	
	Sectio	on 12 -	Ecologic	al Informat	tion			
Ecotoxicity	The product contains a su	bstance w	vhich is very tox	ic to aquatic organ	isms.			
Component(s) Alcohols, C12-13 Ethoxylated,	66455-14-9							
Aquatic								
Acute Crustacea		EC50	Water flea (Daphnia magna)		0.39 -0.56 mg/l,	48 hours	
Fish		LC50	Flathead mi	nnow (Pimephales	promelas)	0.72 -2.7 mg/l, 9	6 hours	
Nonylphenol, ethoxylated, 90	16-45-9							
Aquatic								
Acute Crustacea		EC50	Daphnia ma	gna		65 mg/l, 48 hour	rs	
Crustacea		EC50	Water flea (Daphnia magna)		12.2 mg/l, 48 ho	urs	
elastatea		LC50 Bluegill (lepomis macrochirus) 1 - 1.8 mg/l 96 hours					0.170	
Fish		LC50	Bluegill (lep	omis macrochirus)		1 10 116/1901	ours	
				,		1 10	ours	
Fish Persistence and degradability				,			ours	
Fish Persistence and degradability	No data is available on the No data available.			,			ours	
Fish Persistence and degradability Bioaccumulative potential	No data is available on the No data available.			,			ours	
Fish Persistence and degradability Bioaccumulative potential Partition coeficient n-octant Components 2-Butoxyethanol (CAS 111	No data is available on the No data available. ol / water log (Kow) 1-76-2)		bility of this pro	,		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ours	
Fish Persistence and degradability Bioaccumulative potential Partition coeficient n-octand Components	No data is available on the No data available. DI / water log (Kow)		bility of this pro	,		eg,e	ours	

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 - Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	Waste codes should be assigned by the user based on the application for which the product was used.
Waste from residues / unused products	Dispose in accordance with all applicable regulations.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Section 14 - Transport information

DOT IATA IMDG Transportation in bulk according to Annex II of MARPOL 73/78 and IBC Code Not regulated as dangerous goods. Not regulated as dangerous goods. Not regulated as dangerous goods. This substance/mixture is not intended to be transported in bulk.

Section 15 - Regulatory Information

US federal regulations	•		Chemical" as defined by t S. EPA TSCA Inventory Lis		nmunication Standard,	29 CFR 1910.1200.
TSCA Section 12(b) Ex	port Notification (40 CFI					
US. OSHA Specifically Regulated Substances (29 CFR 1910.100						
• •	bstance List (40 CFR 302					
Component	•		Res	ult		
·	hanol (CAS 111-76-2)		LIST			
•		A at of 1090 (0)		LD		
	nts and Reauthorization	-	AKA)			
Hazard Categories	Immediate Hazard Delayed Hazard	Yes No				
	Fire Hazard	No				
	Pressure Hazard	No				
SABA 202 Extremely b	Reactivity Hazard	No Not listed.				
SARA 302 Extremely h SARA 311/312 Hazard		Yes				
-		Tes				
SARA 313 (TRI reportion	nical name			CAS #	% by wt.	
					•	
	toxyethanol			111-76-2	1 - 5	
Other federal regulations						
	ction 112 Hazardous Air	•	•	Not regulate		
	ction 112(r) Accidental		ition (40 CFR 68.130)	Not regulate	d.	
Safe Drinking Water A		gulated.				
Food and Drug Admin	istration (FDA) Not re	gulated.				
US state regulations			. .			
US.Massachusetts RTH	C - Substance List		Components	111 76 0		
			2-Butoxyethanol (CAS	111-76-2)		
US.New Jersey Worke	r and Community Right-	to-Know Act	Components			
			2-Butoxyethanol (CAS	111-76-2)		
US.Pennsylvania RTK	- Hazardous Substances		Components			
			2-Butoxyethanol (CAS	111-76-2)		
US.Rhode Island RTK			Components			
			2-Butoxyethanol (CAS	111-76-2)		
US - California Propsit	ion 65		This product does not birth defects or other		known to the State of C	alifornia to cause cancer,
International Inventories						
Country(s) or region	Invento	ory Name				On Inventory (yes/no)*
Australia	Austra	lian Inventory	of Chemical Substances	AICS)		Yes
Canada	Dome	stic Substances	List (DSL)			Yes
Canada	Non-D	omestic Substa	ances List (NDSL)			No
China			Chemical Substances in (China (IECSC)		Yes
Europe			of Existing Commercial Cl	. ,	(EINECS)	No
Europe	•	•	fed Chemical Substances		· ·	No
Japan	•		and New Chemical Subst			No
-						

Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
Unites States Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
WALLY ALL STREET AND A STREET AND A STREET	en alter and the termination of the second and determined by the second state of the termination of termin	

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

*A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 - Other information, including date of preparation or last version

Issue date	10/9/2014
Version #	01
Disclaimer	The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS. Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this SDS. The user should review these regulations to ensure full compliance.

Directions:

DILUTE PRODUCT AS FOLLOWS:

Moderate soil /build-up, Light finish removal .. Dilute 5 oz. (1:25) of QWIK-SCRUB per gallon of warm water Heavy soil /build-up, Heavy finish removal .. Dilute 10 oz. (1:12) of QWIK-SCRUB per gallon of warm water

SCRUB/RE-COAT USING STANDARD 175 RPM FLOOR MACHINE:

Dilute QWIK-SCRUB in mop bucket according to above dilution directions. Liberally mop solution onto floor surface and allow to dwell for 1 to 4 minutes (depending on how deeply it is desired to scrub). With machine and scrub floor pad or brush, scrub surface of floor until all embedded soils and scuffs are removed from finish. After scrubbing, remove solution from floor with wet-dry vacuum or a clean mop. Damp mop rinse with clear water to remove any excess residue. Allow floor to completely dry prior to re-coating.

SCRUB/RE-COAT USING AUTOMATIC SCRUBBER:

Dilute QWIK-SCRUB in mop bucket according to above dilution directions. Liberally mop solution onto floor surface and allow to dwell for 1 to 4 minutes (depending on how deeply it is desired to scrub). Fill autoscrubber with clear water, mount scrubbing pad or medium grade brush. With vacuum off and squeegee up, scrub the floor until all embedded soils and scuffs are removed from finish. Lower squeegee and vacuum all scrubbing solution. Using clear water from the autoscrubber, rinse floor to remove any excess residue. Allow floor to completely dry prior to re-coating.

Instrucciones para Uso:

PRODUCTO DILUÍDO COMO SIGUE:

El suelo moderado/la acumulación, Retiro ligero del final ... Diluye 5 onzas (1:25) de QWIK-SCRUB por galón de agua caliente Suelo pesado/acumulación, Retiro pesado del finalDiluya 10 onzas (1:12) de QWIK-SCRUB por galón de agua caliente

Scrub/re-coat USANDO LA MÁQUINA del PISO del ESTÁNDAR 175 RPM:

Diluído QWICK-SCRUB adentro aliofifan el cubo según direcciones antedichas de la dilusión. Aliofife liberalmente la solución sobre superficie del piso y permita para morar por 1 a 4 minutos (dependiendo de cómo se desea profundamente para fregar). Con la máquina y friegue el cojín o el cepillo del piso, friegue la superficie del piso hasta todos los suelos encajados y la rasca se quitan de final. Después de fregar, quite la solución de piso con vacío mojado-seco o un limpio aljofifa. La humedad aljofifa la aclaración con aqua clara para guitar cualquier exceso de residuo. Permita que el piso se segue totalmente antes de re-coating.

Scrub/re-coat USANDO A DEPURADOR AUTOMÁTICO:

Diluído QWIK-SCRUB adentro aliofifan el cubo según direcciones antedichas de la dilusión. Aliofife liberalmente la solución sobre superficie del piso y permita para morar por 1 a 4 minutos (dependiendo de cómo se desea profundamente para fregar). Llene el autoscrubber de agua clara, del cojín del montaje o del cepillo del grado del medio que friega. Con vacío apagado y el enjugador para arriba, friegue el piso hasta todos los suelos encajados y lo rasca se guitan de final. Baje el enjugador y limpie toda la solución con la aspiradora que friega. Con el agua clara del autoscrubber, aclare el piso para guitar cualquier exceso de residuo. Permita que el piso se segue totalmente antes de re-coating.

** MADE IN USA **

0955-29-1014









World Class Cleaning Solutions®

Qwik-Scrub[™]

Scrub & Recoat Cleaner

Heavy duty formula aggressively removes embedded soils and scuffs from upper layers of finish. For proper preparation of surface prior to re-finishing.

WARNING: MAY CAUSE AN ALLERGIC SKIN REACTION. See back panel for additional precautions and treatment. **ATENCIÓN:** PUEDE PROVOCAR UNA REACCIÓN ALÉRGICA EN LA PIEL. Ver panel lateral para las medidas preventivas adicionales. NET CONTENTS: 1 GALLON / 3.79 LITERS

National Chemical Laboratories, Inc. Philadelphia, PA 19123 USA • (800) 628-2436 www.nclonline.com



Floor Cleaner

Response: If on skin: Wash with plenty of water. If in eves: Rinse cautiously with water for several minutes Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:



Product No.: 0955

WARNING: MAY CAUSE AN ALLERGIC SKIN REACTION, CAUSES SERIOUS EYE IRRITATION, KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eve protection/face protection.

Read the entire label and SDS before using this product. and for additional first aid measures. SDS for this product is available on the web at www.nclonline.com

ATENCIÓN: PUEDE PROVOCAR UNA REACCIÓN ALÉRGICA EN LA PIEL, PROVOCA IRRITACIÓN OCULAR GRAVE, MANTENER FUERA DEL ALCANCE DE LOS NIÑOS.

Conseios de prudencia

Prevención: Evite respirar la niebla o vapor. Lavar a fondo después de la manipulación. Las prendas de trabajo contaminadas no se debe permitir salir del lugar de trabaio. Llevar guantes de protección. Use / la cara oio.

Respuesta: Sí en la piel: Lavar con abundante agua. Si en los oios: Aclarar cuidadosamente con agua durante varios minutos. Quítese los lentes de contacto, si lleva y resulta fácil de hacer. Proseguir con el lavado. El tratamiento específico (ver esta etiqueta). En caso de irritación de la piel o erupción cutánea: Consultar a un médico / atención. Si persiste la irritación ocular: Consultar a un médico / atención. Lave la ropa contaminada antes de volverla a usar.

Almacenamiento: Almacene leios de materiales incompatibles.

Eliminación: Eliminar los desperdicios y residuos de conformidad con los requisitos de las autoridades locales.

Este producto es un "auímico peligroso" según lo definido por la Norma de Comunicación de Peligros de OSHA, 29 CFR 1910.1200. Todos los componentes están en la Lista de inventario de la EPA TSCA.

Medidas additional de primeros auxilios:

Lea toda la etiqueta y SDS antes de usar este producto, así como medidas adicionales de primeros auxilios. SDS para el artículo está disponible en la web en www.nclonline.com

CONTAINS: 2-Butoxyethanol CAS# 111-76-2, Nonylphenol, ethoxylated CAS # 9016-45-9, Alcohols, C12-13 Ethoxylated CAS# 66455-14-9. Orange Oil CAS# 8008-57-9

Class Cleaning Solutions*

401 N. 10th Street • Philadelphia, PA 19123 1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517 www.nclonline.com • e-mail: info@nclonline.com